MSDS for #01565 - MAIME	RI OIL MEDIUM	Faye
	IA MAIMERI S.P.A.	Revision nr.113 Dated 3/9/2014
AUXILIARY PRODUC	<b>TS</b> 58604 Petroleum essence	Printed on 3/9/2014 Page n. 1 / 8
	Safety data sheet	
SECTION 1. Identification of	f the substance/mixture and of the compan	ny/undertaking
1.1. Product identifier		
Code: Product name Chemical name and synonym EC number Registration Number	58604 AUXILIARY PRODUCTS 58604 Petroleu Alifatic hydrocarbon 920-750-0 01-2119473851-33	im essence
1.2. Relevant identified uses of the su	bstance or mixture and uses advised against	
Intended use	Thinner for oil painting.	
1.3. Details of the supplier of the safe	ty data sheet	
Name Full address District and Country	INDUSTRIA MAIMERI S.P.A. Via Gianni Maimeri, 1 20060 Mediglia Italia Tel. +39 02 906981 Fax +39 02 90698999	(MI)
e-mail address of the competent pers responsible for the Safety Data Shee		
Product distribution by	INDUSTRIA MAIMERI S.P.A. VIA G.MAIMERI 1 (MI) ITALY	20060 BETTOLINO DI MEDIGLIA
1.4. Emergency telephone number		
For urgent inquiries refer to	Australia : 131126 USA:  1 800 222 1222 Regno Unito NHS Direct (UK): +44 (0) 845 46 4	47
SECTION 2. Hazards identi	ication.	
2.1. Classification of the substance o	r mixture.	
amendments and supplements). T 1907/2006 and subsequent amendm	ardous pursuant to the provisions set forth in EC Regulation he product thus requires a safety datasheet that complies ents. g the risks for health and/or the environment are given in section	with the provisions of EC Regulation
2.1.1. Regulation 1272/2008 (CLP) and	I following amendments and adjustments.	
Hazard classification and indication: Flam. Liq. 2 H225 Asp. Tox. 1 H304 STOT SE 3 H336 Aquatic Chronic 2 H411 Note P		
2.1.2. 67/548/EEC and 1999/45/EC Dire	ectives and following amendments and adjustments.	
Danger Symbols: F-2	(n-N	
R phrases: 11	51/53-65-66-67	
The full wording of the Risk (R) and h	azard (H) phrases is given in section 16 of the sheet.	

Item Numbers: 01565-1024, 01565-1026

EPY 8.1.21

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Danger

Signal words:

H	lazard statements:	
	H225	Highly flammable liquid and vapour.
	H304	May be fatal if swallowed and enters airways.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.
	EUH066	Repeated exposure may cause skin dryness or cracking.
F	Precautionary statements	St.
	P210	Keep away from heat / sparks / open flames / hot surfaces. No smoking.
	P233	Keep container tightly closed.
	P241	Use explosion-proof electrical / ventilating / lighting / equipment.
	P242	Use only non-sparking tools.
	P243	Take precautionary measures against static discharge.
	P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves / protective clothing / eye protection / face protection.
	P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
	P303+P361+P353	IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
	P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P310	Immediately call a POISON CENTER or doctor / physician.
	P312	Call a POISON CENTER or doctor / physician if you feel unwell.
	P331	DO NOT induce vomiting.
	P370+P378	In case of fire: Use CO2, powder for extinction.
	P391	Collect spillage.
	P403+P235	Store in a well-ventilated place. Keep cool.
	P405	Store locked up.
	P501	Dispose of contents / container to in accordance with local and national norms
Ν	Ir. EC:	920-750-0

### 2.3. Other hazards.

Information not available.

# **SECTION 3. Composition/information on ingredients.**

## 3.1. Substances.

# Contains:

Identification. Conc. %. Classification 67/548/EEC. ALIFATIC HYDROCARBON CAS. R66, R67, Xn R65, N R51/53, Note P 100 EC. 920-750-0 INDEX. 01-2119473851-33 Reg. no.

Classification 1272/2008 (CLP).

Flam. Liq. 2 H225, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Note P

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T + = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F + = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

Item Numbers: 01565-1024, 01565-1026

EPY 8.1.21

AUXILIARY PRODUCTS 58604 Petroleum essence

Revision nr.113 Dated 3/9/2014 Printed on 3/9/2014 Page n. 3 / 8

SECTION 3. Composition/information on ingredients. ..../>>

### 3.2. Mixtures.

Information not relevant.

## **SECTION 4. First aid measures.**

### 4.1. Description of first aid measures.

Not specifically necessary. Observance of good industrial hygiene is recommended.

# 4.2. Most important symptoms and effects, both acute and delayed.

- No episodes of damage to health ascribable to the product have been reported.
- **4.3. Indication of any immediate medical attention and special treatment needed.** Information not available.

## **SECTION 5. Firefighting measures.**

#### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

58604 Petroleum essence

AUXILIARY PRODUCTS
SECTION 7. Handling and storage. ... />>

### 7.2. Conditions for safe storage, including any incompatibilities.

Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Information not available.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration. Personal protection equipment must comply with the rules in force indicated below. HAND PROTECTION

Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitryl or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### **SECTION 9.** Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	colourless
Odour	characteristic
Odour threshold.	Not available.
pH.	
Melting point / freezing point.	Not available.
Initial boiling point.	100 °C.
Boiling range.	100/120 °C
Flash point.	< 21 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,700 Kg/l
Solubility	SOLUBLE IN WHITE SPIRIT

Revision nr.113 Dated 3/9/2014 Printed on 3/9/2014 Page n. 4 / 8

#### **INDUSTRIA MAIMERI S.P.A. AUXILIARY PRODUCTS** 58604 Petroleum essence SECTION 9. Physical and chemical properties. ... / >> Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Not available. Decomposition temperature. Viscosity Not available. Explosive properties Not available. Not available. Oxidising properties 9.2. Other information. VOC (Directive 1999/13/EC) : 100,00 % - 700,00 g/litre VOC (volatile carbon) : 0

# **SECTION 10. Stability and reactivity.**

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

#### **10.3. Possibility of hazardous reactions.** No hazardous reactions are foreseeable in normal conditions of use and storage.

## 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials.

Information not available.

#### **10.6. Hazardous decomposition products.** Information not available.

# **SECTION 11. Toxicological information.**

Ingestion LD50, acute, rat:> 5000mg/kg (under evaluation) .

#### 11.1. Information on toxicological effects.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

# **SECTION 12. Ecological information.**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

**12.1. Toxicity.** Information not available.

#### **12.2. Persistence and degradability.** Information not available.

#### **12.3. Bioaccumulative potential.** Information not available.

**12.4. Mobility in soil.** Information not available.

12.5. Results of PBT and vPvB assessment.

vPvB substances contained: ALIFATIC HYDROCARBON

#### 12.6. Other adverse effects.

Information not available.

Revision nr.113 Dated 3/9/2014 Printed on 3/9/2014

Page n. 5/8

# AUXILIARY PRODUCTS

58604 Petroleum essence

Revision nr.113 Dated 3/9/2014 Printed on 3/9/2014 Page n. 6 / 8

				Fage II: 078	
SECTION 13. Disposal	l considerations.				
3.1. Waste treatment method: Reuse, when possible. Pro- product should be evaluated a Disposal must be performed t Avoid littering. Do not contam Waste transportation may be CONTAMINATED PACKAGII Contaminated packaging must	duct residues should be according to applicable re through an authorised was inate soil, sewers and wa subject to ADR restriction NG	gulations. ste management f terways. is.	irm, in compliance with nation		g this
SECTION 14. Transpo	rt information.				
current edition of the Code of These goods must be pack	International Carriage of ked in their original pack loading and unloading	Dangerous Goods kagings or in pacl dangerous goods	s by Road (ADR) and in all t kagings made of materials r	according to the provisions set out i he applicable national regulations. esistant to their content and not rea isks deriving from these substances	acting
Road and rail transport:					
ADR/RID Class: Packing Group: Label: Nr. Kemler: Proper Shipping Name:	3 UN: II 3/N 33	3295			
Carriage by sea (shipping):					
IMO Class: Packing Group: Label: EMS: Marine Pollutant.	3 UN: II 3/N F-E/S-D NO	3295			
Transport by air:					
IATA: Packing Group: Label:	3 UN: II 3/N	3295			
SECTION 15. Regulato	ory information.				
15.1. Safety, health and enviro	0	islation specific	for the substance or mixtu	ure.	
Seveso category.	7b, 9ii				
Restrictions relating to the prod Product. Point. 3 -		s pursuant to Anne	x XVII to EC Regulation 1907	//2006	
Substances in Candidate List (/ None.	Art. 59 REACH).				
Substances subject to authorisa None.	arion (Annex XIV REACH).				
Substances subject to exportati None.	ion reporting pursuant to (E	C) Reg. 689/2008:			
Substances subject to the Rotte None.	erdam Convention:				
Substances subject to the Stoc None.	kholm Convention:				

Item Numbers: 01565-1024, 01565-1026

Page 6 of 8

MERIS.P.A.Revision nr.113<br/>Dated 3/9/201458604 Petroleum essencePrinted on 3/9/2014<br/>Printed on 3/9/2014

## SECTION 15. Regulatory information. ... / >>

**AUXILIARY PRODUCTS** 

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Asp. Tox. 1 STOT SE 3	Flammable liquid, category 2 Aspiration hazard, category 1 Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2 H225	Hazardous to the aquatic environment, chronic toxicity, category 2 Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R11 R51/53	HIGHLY FLAMMABLE. TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments

Page 7 of 8

# **AUXILIARY PRODUCTS**

# SECTION 16. Other information. ... / >>

- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. The Merck Index. 10th Edition
- 9. Handling Chemical Safety
- 10. Niosh Registry of Toxic Effects of Chemical Substances
- 11. INRS Fiche Toxicologique (toxicological sheet)
- 12. Patty Industrial Hygiene and Toxicology
- 13. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 14. ECHA website

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

58604 Petroleum essence

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Item Numbers: 01565-1024, 01565-1026

Revision nr.113 Dated 3/9/2014 Printed on 3/9/2014 Page n. 8/8