21707-1105

Safety Data Sheet

Blick Matte

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Blick Matte Creative 06-990-12 6/21/22 SDS Number: Revision Date:

Version: Product Type: Product Use: Art Material

Supplier Details:

Phone:

Emergency: Chemtel 1-800-255-3924

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1
Physical, Flammable Aerosols, 1
Physical, Gases Under Pressure, Liquefied Gas
Health, Skin corrosion/irritation, 2
Health, Serious Eye Damage/Eye Irritation, 2 A
Health, Specific target organ toxicity - Single exposure, 3
Health, Carcinogenicity, 1
Health, Carcinogenicity, 1

Health, Germ cell mutagenicity, 1 Health, Aspiration hazard, 1 Health, Acute toxicity, 4 Oral

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms



GHS Hazard Statements:

H222 - Extremely flammable aerosol

H280 - Contains gas under pressure; may explode if heated
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H319 - Causes serious eye irritation
H330 - May cause drowsiness or dizziness
H350 - May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
H340 - May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the

H304 - May be fatal if swallowed and enters airways H302 - Harmful if swallowed

GHS Precautionary Statements:

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.

SDS Number: Creative 06-990-12 Revision Date: 6/21/22 Page: 1/22

Page 1 of 22 Item Numbers: 21707-1105

Blick Matte

P210 - Keep away from heat/sparks/open flames/hot surfaces. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use.

P260 - Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P261 - Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 - Wash skin thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection. P281 - Use personal protective equipment as required.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P302 + P352 - If on skin: Wash with plenty of water and soap.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.
P308 + P313 - IF exposed or concerned: Get medical advice/ attention.
P312 - Call a POISON CENTER or doctor/ physician if you feel unwell.

P331 - Do NOT induce vomiting.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention. P337 + P313 - If eye irritation persists: Get medical advice/attention.

P382 - Take off contaminated clothing and wash before reuse.

P405 - Store locked up.

P410 + P403 - Protect from sunlight. Store in a well-ventilated place. P412 - Do not expose to temperatures exceeding 50 °C/ 122 °F.

P501 - Dispose of contents/ container to an approved waste disposal plant.

COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
68476-86-8	10-30%	Petroleum gases, liquefied
67-64-1	30-50%	Acetone .
1330-20-7		Xylene (o-,m-,p- isomers)
108-21-4	5-10%	Isopropyl acetate
123-42-2	2-10%	Diacetone alcohol
108-10-1	1-5%	2-Pentanone, 4-methyl-
78-93-3	1-5%	Methyl ethyl ketone
628-63-7	1-5%	n-Amyl acetate
100-41-4	.1-1%	Ethy1benzene
624-41-9	.5-4%	1-Butanol, 2-methyl-, acetate
9004-70-0	.5-4%	Nitrocellulose
67-63-0	.5-4%	Isopropyl alcohol

FIRST AID MEASURES

Inhalation: Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician. Skin Contact:

Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek

medical attention.

Eye Contact: Flush with warm water for 15 minutes. Seek medical attention.

Ingestion: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a

physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

5 FIRE FIGHTING MEASURES

Flash Point: Flash point of propellant <0 degrees F.

LEI: Lower: 1.8 % (VOL.) Gas in air (propellant portion) UEL: Upper: 9.5 % (VOL.) Gas in air (propellant portion)

Extinguishing Media:

SDS Number: Creative 06-990-12 Page: 2/22 Revision Date: 6/21/22

Page 2 of 22 Item Numbers: 21707-1105

Blick Matte

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials. Unusual Fire & Explosion Hazards:

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite. Special Fire Fighting Propedures:

Special Fire Fighting Procedures:

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel.

Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus.

Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely.

Material will float on water, avoid spreading the fire.

6

ACCIDENTAL RELEASE MEASURES

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7

HANDLING AND STORAGE

Handling Precautions:

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

Storage Requirements:

Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

Personal Protective Equipment:

Protective Equipment:

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

Respiratory Protection

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above exposure levels an approved self-contained breathing apparatus or airline respirator with full face-piece is required

Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised:

SDS Number: Creative 06-990-12

Page: 3/22

Revision Date: 6/21/22

Item Numbers: 21707-1105 Page 3 of 22

Blick Matte

We. take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Acetone cas#:(67-64-1) [30-50%]

Components with workplace control parameters

500 ppm TWA USA. ACGIH Threshold Limit Values

(TLV)

Eye & Upper Respiratory Tract irritation Central Nervous System impairment

Hematologic effects

Substances for which there is a Biological Exposure Index or Indices

Not classifiable as a human carcinogen

750 ppm USA. ACGIH Threshold Limit Values

(TLV)
Eye & Upper Respiratory Tract irritation

Central Nervous System impairment Hematologic effects

Substances for which there is a Biological Exposure Index or Indices (see BEI section)

Not classifiable as a human carcinogen

STEL 1,000 ppm USA. OSHA - TABLE Z-1 Limits for 2,400 mg/m3 Air Contaminants - 1910.1000
The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors.

1,000 ppm

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air 2,400 mg/m3

Contaminants

The value in mg/m3 is approximate.

USA. NIOSH Recommended 250 ppm TWA 590 mg/m3 Exposure Limits

USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 TWA 750 ppm

1,800 mg/m3

Xylene (o-,m-,p- isomers) cas#:(1330-20-7) [5-10%]

Components with workplace control parameters

USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants TWA 100 ppm

435 mg/m3

TWA 100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -435 mg/m3 1910.1000

150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -STEL 655 mg/m3 1910.1000

100 ppm 434 mg/m3 USA. ACGIH Threshold Limit Values (TLV)

Not classifiable as a human carcinogen

STEL 150 ppm USA. ACGIH Threshold Limit Values (TLV)

651 mg/m3

Not classifiable as a human carcinogen

TWA 100 ppm USA. ACGIH Threshold Limit Values (TLV)

SDS Number: Creative 06-990-12 Page: 4/22 Revision Date: 6/21/22

Page 4 of 22 Item Numbers: 21707-1105

Blick Matte

Eye & Upper Respiratory Tract irritation Central Nervous System impairment Substances for which there is a Biological Exposure Index or Indices (see BEI section) Not classifiable as a human

STEL 150 ppm USA. ACGIH Threshold Limit Values (TLV)
Eye & Upper Respiratory Tract irritation Central Nervous System impairment Substances for which
there is a Biological Exposure Index or Indices (see BEI section) Not classifiable as a human carcinogen

USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants 100 ppm

435 mg/m3

The value in mg/m3 is approximate.

USA, OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 TWA 100 ppm

435 mg/m3

USA. OSHA - TABLE Z-1 Limits for Air Contaminants -STEL 150 ppm

655 mg/m3 1910.1000

Isopropyl acetate cas#:(108-21-4) [5-10%]

Components with workplace control parameters

250 ppm 950 mg/m3 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

The value in mg/m3 is approximate.

100 ppm USA. ACGIH Threshold Limit Values

(TLV)
Eye & Upper Respiratory Tract irritation
Central Nervous System impairment

200 ppm USA. ACGIH Threshold Limit Values (TLV)

Eye & Upper Respiratory Tract irritation Central Nervous System impairment

TWA 250 ppm USA. OSHA - TABLE Z-1 Limits for

950 mg/m3 Air Contaminants - 1910.1000

310 ppm USA, OSHA - TABLE Z-1 Limits for STEL

1,185 mg/m3 Air Contaminants - 1910.1000 See Appendix D - Substances with No Established RELs

Diacetone alcohol cas#.(123-42-2) [2-10%]

Components with workplace control parameters

USA. ACGIH Threshold Limit Values (TLV) TWA 50 ppm

Eye & Upper Respiratory Tract irritation

TWA 50 ppm USA. NIOSH Recommended Exposure Limits 240 mg/m3

TWA 50 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1

240 mg/m3 Limits for Air Contaminants

The value in mg/m3 is approximate.

TWA 50 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

240 mg/m3 1910.1000

SDS Number: Creative 06-990-12 Page: 5/22 Revision Date: 6/21/22

Page 5 of 22 Item Numbers: 21707-1105

Blick Matte

2-Pentanone, 4-methyl- cas#.(108-10-1) [1-5%]

Components with workplace control parameters

USA. ACGIH Threshold Limit Values (TLV) 50 ppm

STEL 75 ppm USA. ACGIH Threshold Limit Values (TLV)
Upper Respiratory Tract irritation Headache Dizziness 2010 Adoption Substances for which there is a Biological Exposure Index or Indices (see BEI section) Confirmed animal carcinogen with

unknown relevance to humans

TWA 50 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

205 mg/m3 1910.1000

STEL 75 ppm 300 mg/m3 USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants 100 ppm

410 mg/m3

The value in mg/m3 is approximate.

TWA 20 ppm USA. ACGIH Threshold Limit Values (TLV)
Upper Respiratory Tract irritation Headache Dizziness 2010 Adoption Substances for which there is a Biological Exposure Index or Indices (see BEI section) Confirmed animal carcinogen with unknown relevance to humans

50 ppm USA. NIOSH Recommended Exposure Limits

205 mg/m3

ST 75 ppm 300 mg/m3 USA. NIOSH Recommended Exposure Limits

Methyl ethyl ketone cas#:(78-93-3) [1-5%]

n-Amyl acetate cas#:(628-63-7) [1-5%]

Components with workplace control parameters

USA, OSHA - TABLE Z-1 Limits for Air Contaminants -100 ppm

525 mg/m3 1910.1000

USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants TWA 100 ppm

525 mg/m3

The value in mg/m3 is approximate. 100 ppm

TWA

525 mg/m3 Ethylbenzene cas#:(100-41-4) [.1-1%]

Components with workplace control parameters

USA. ACGIH Threshold Limit Values (TLV) 100 ppm Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Substances for which there is a Biological Exposure Index or Indices (see BEI section) Confirmed animal carcinogen with unknown relevance to humans

USA. NIOSH Recommended Exposure Limits

SDS Number: Creative 06-990-12 Page: 6/22 Revision Date: 6/21/22

Page 6 of 22 Item Numbers: 21707-1105

Blick Matte

USA. ACGIH Threshold Limit Values (TLV) Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Substances for which there is a Biological Exposure Index or Indices (see BEI section) Confirmed animal carcinogen with unknown relevance to humans

TWA 100 ppm 435 mg/m3 USA. NIOSH Recommended Exposure Limits

ST 125 ppm USA. NIOSH Recommended Exposure Limits

545 mg/m3

USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants TWA 100 ppm

435 mg/m3

The value in mg/m3 is approximate.

100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -TWA

435 mg/m3 1910.1000

STEL 125 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

545 mg/m3 1910.1000

1-Butanol, 2-methyl-, acetate cas#:(624-41-9) [.5-4%]

Components with workplace control parameters

USA. ACGIH Threshold Limit Values (TLV) TWA 50 ppm

Upper Respiratory Tract irritation

STEL 100 ppm USA. ACGIH Threshold Limit Values (TLV)

Upper Respiratory Tract irritation

Nitrocellulose cas#:(9004-70-0) [.5-4%]

Isopropyl alcohol cas#:(67-63-0) [.5-4%]

Components with workplace control parameters

USA. ACGIH Threshold Limit Values TWA 200 ppm

(TLV)
Eye & Upper Respiratory Tract irritation Central Nervous System impairment Not classifiable as a human carcinogen

STEL 400 ppm USA. ACGIH Threshold Limit Values

Eye & Upper Respiratory Tract irritation Central Nervous System impairment Not classifiable as a human carcinogen

USA. OSHA - TABLE Z-1 Limits for TWA 400 ppm 980 mg/m3 Air Contaminants - 1910.1000

500 ppm STEL

USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 1,225 mg/m3

TWA 400 ppm USA. Occupational Exposure Limits

980 mg/m3 (OSHA) - Table Z-1 Limits for Air

Contaminants

SDS Number: Creative 06-990-12 Page: 7/22 Revision Date: 6/21/22

Page 7 of 22 Item Numbers: 21707-1105

Blick Matte

The value in mg/m3 is approximate.

400 ppm USA. NIOSH Recommended

980 mg/m3 Exposure Limits

500 ppm ST USA. NIOSH Recommended

1,225 mg/m3 Exposure Limits

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless aerosol

Viscosity: Solubility: NA Negligible

Flammability: Freezing/Melting Pt.: NΑ NE

Partition Coefficient: NE Flash Point: Flash point of propellant < 0°F

Vapor Pressure: >30psi Vapor Density: >1 Air = 1 pH: NA Auto-Ignition Temp: NE

Evap. Rate: Upper: 9.5%(vol) Gas in Air Ether = 1 Slower UFL/LFL: Lower:1.8% (vol) Gas in Air

STABILITY AND REACTIVITY 10

Chemical Stability: Stable

Conditions to Avoid: Heat, spark, and open flame. Strong Oxidizing Agents. Materials to Avoid:

Hazardous Decomposition: Combustion will produce Carbon Monoxide. Carbon Dioxide, and nitrogen-oxygen compounds.

Hazardous Polymerization: Will not occur.

TOXICOLOGICAL INFORMATION

Acetone cas#:(67-64-1) [30-50%]

Information on toxicological effects

LD50 Oral - rat - 5,800 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Tremor. LC50 Inhalation - rat - 8 h - 50,100 mg/m3 Inhalation: no data available

LD50 Dermal - guinea pig - 7,426 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Mild skin irritation - 24 h

Serious eve damage/eve irritation: Eves - rabbit Result: Eve irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

SDS Number: Creative 06-990-12 Page: 8/22 Revision Date: 6/21/22

Page 8 of 22 Item Numbers: 21707-1105

Blick Matte

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Kidney - Irregularities - Based on Human Evidence

Xylene (o-,m-,p- isomers) cas#:(1330-20-7) [5-10%]

Information on toxicological effects

Acute toxicity: Oral LD50 no data available Inhalation LC50
Dermal LD50
Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eve damage/eve irritation: Eves: no data available

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:
IARC: 2B - Group 2B: Possibly carcinogenic to humans (Ethylbenzene)
IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Xylene)
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

Page: 9/22 SDS Number: Creative 06-990-12 Revision Date: 6/21/22

Page 9 of 22 Item Numbers: 21707-1105

Blick Matte

RTECS: Not available

Isopropyl acetate cas#:(108-21-4) [5-10%]

Information on toxicological effects

Acute toxicity: LD50 Oral - rat - 6,750 mg/kg LC50 Inhalation - rat - 8 h - 50,600 mg/m3

Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: Al4930000

prolonged or repeated exposure can cause; Nausea, Headache, Vomiting, narcosis

Diacetone alcohol cas#:(123-42-2) [2-10%]

Information on toxicological effects

Acute toxicity

Oral LD50 LD50 Oral - rat - 2,520 mg/kg Remarks: Behavioral:Tremor. Behavioral:Convulsions or effect on seizure threshold. Liver:Other

changes. Inhalation LC50 LC50 Inhalation - rat - 4 h - 1500 ppm Dermal LD50 LD50 Dermal - rabbit - 13,500 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes - rabbit - Severe eye irritation - 24 h

Respiratory or skin sensitization: no data available

SDS Number: Creative 06-990-12 Page: 10 / 22 Revision Date: 6/21/22

Page 10 of 22 Item Numbers: 21707-1105

Blick Matte

Germ cell mutagenicity: no data available

Carcinogenicity:

ARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: Central nervous system depression, Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Blood disorders, Dematitis, Blurred vision, Effects due to ingestion may include:, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information: RTECS: SA9100000

2-Pentanone, 4-methyl- cas#:(108-10-1) [1-5%]

Information on toxicological effects

Acute toxicity:
Oral LD50 LD50 Oral - rat - 2,080 mg/kg
Inhalation LC50 LC50 Inhalation - rat - 4 h - 8.2 - 16.4 mg/m3
Dermal LD50 LD50 Dermal - rabbit - > 16,000 mg/kg

Other information on acute toxicity no data availa

Skin corrosion/irritation: Skin - rabbit - Mild skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit - Moderate eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:
IARC: 2B - Group 2B: Possibly carcinogenic to humans (4-Methylpentan-2-one)
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Revision Date: 6/21/22 SDS Number: Creative 06-990-12 Page: 11/22

Page 11 of 22 Item Numbers: 21707-1105

Blick Matte

Reproductive toxicity: no data available

Teratogenicity: Developmental Toxicity - mouse - Inhalation:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Effects on Embryo or Fetus: Fetal death.

Developmental Toxicity - mouse - Inhalation:
Specific Developmental Abnormalities: Central nervous system. Specific Developmental Abnormalities: Musculoskeletal system. Specific Developmental Abnormalities: Cardiovascular (circulatory) system. no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): May cause respiratory irritation.

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: Blurred vision, Dermatitis, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information: RTECS: SA9275000

Methyl ethyl ketone cas#:(78-93-3) [1-5%]

Information on toxicological effects

Acute toxicity: Oral I D50 no data available Inhalation LC50 Dermal LD50 Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

SDS Number: Creative 06-990-12 Page: 12 / 22 Revision Date: 6/21/22

Page 12 of 22 Item Numbers: 21707-1105

Blick Matte

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation Toxic if inhaled. May cause respiratory tract irritation. Ingestion Toxic if swallowed. Skin Toxic if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Dizziness, Gastrointestinal disturbance, Weakness, Confusion., Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: Not available

n-Amyl acetate cas#:(628-63-7) [1-5%]

Information on toxicological effects

Acute toxicity: Oral LD50 LD50 Oral - rabbit - 7,400 mg/kg Inhalation LC50 no data available Dermal LD50 Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

SDS Number: Creative 06-990-12 Page: 13 / 22 Revision Date: 6/21/22

Page 13 of 22 Item Numbers: 21707-1105

Blick Matte

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: AJ1925000

Ethylbenzene cas#:(100-41-4) [.1-1%]

Information on toxicological effects

Acute toxicity: Oral LD50 no data available Inhalation LC50

Dermal LD50 LD50 Dermal - rabbit - 15,433 mg/kg

Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

classification.

IARC: 28 - Group 28: Possibly carcinogenic to humans (Ethylbenzene)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):

no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: Central nervous system depression, Nausea, Headache, Vomiting, Ataxia., Tremors

Synergistic effects: no data available

Additional Information: RTECS: DA0700000

SDS Number: Creative 06-990-12 Page: 14 / 22 Revision Date: 6/21/22

Page 14 of 22 Item Numbers: 21707-1105

Blick Matte

1-Butanol, 2-methyl-, acetate cas#:(624-41-9) [.5-4%]

Information on toxicological effects

Acute toxicity: Oral LD50 no data available Inhalation LC50 Dermal LD50

Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

Larcinogeniony:

LARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH:

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):

no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Synergistic effects: no data available

Additional Information:

RTECS: EL5466666

Nitrocellulose cas#:(9004-70-0) [.5-4%]

Information on toxicological effects

Acute toxicity: no data available Inhalation: no data available

Dermal: no data available

SDS Number: Creative 06-990-12 Revision Date: 6/21/22 Page: 15 / 22

Page 15 of 22 Item Numbers: 21707-1105

Blick Matte

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

NTP OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: Not available

Contact with eyes can cause:, Redness, Blurred vision, Prolonged or repeated exposure to skin causes defatting and dermatitis., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Liver - Irregularities - Based on Human Evidence Heart - Irregularities - Based on Human Evidence (Ethanol)

Isopropyl alcohol cas#:(67-63-0) [.5-4%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 5,045 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Somnolence (general

depressed activity). LC50 Inhalation - rat - 8 h - 16000 ppm

LD50 Dermal - rabbit - 12,800 mg/kg

no data available

Skin corrosion/irritation: Skin - rabbit Result: Mild skin irritation

Serious eye damage/eye irritation: Eyes - rabbit Result: Eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:
This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA

Reproductive toxicity: no data available

SDS Number: Creative 06-990-12 Page: 16 / 22 Revision Date: 6/21/22

Page 16 of 22 Item Numbers: 21707-1105

Blick Matte

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: NT8050000

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects.

Kidney - Irregularities - Based on Human Evidence

ECOLOGICAL INFORMATION

Acetone cas#:(67-64-1) [30-50%]

Information on ecological effects

Toxicity: no data available

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 13,500.00 mg/l - 48 h. other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Xylene (o-,m-,p- isomers) cas#:(1330-20-7) [5-10%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

Isopropyl acetate cas#:(108-21-4) [5-10%]

Information on ecological effects

Toxicity:

SDS Number: Creative 06-990-12 Page: 17 / 22 Revision Date: 6/21/22

Page 17 of 22 Item Numbers: 21707-1105

Blick Matte

Toxicity to fish LC0 - Leuciscus idus melanotus - 260 mg/l - 48 h. LC50 - Leuciscus idus melanotus - 265 mg/l - 48 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Diacetone alcohol cas#:(123-42-2) [2-10%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Lepomis macrochirus (Bluegill) - 420 mg/l - 96 h. Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 9,000 mg/l - 24 h.

and other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

2-Pentanone, 4-methyl- cas#:(108-10-1) [1-5%]

Information on ecological effects

Toxicity:

Toxicity to fish LC0 - Leuciscus idus melanotus - 480 mg/l - 48 h.
Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 1,550 - 3,623 mg/l - 24 h.
and other aquatic invertebrates
Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - 980 - 2,000 mg/l - 48 h.

Persistence and degradability: Biodegradability Biotic/Aerobic

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

Methyl ethyl ketone cas#:(78-93-3) [1-5%]

Information on ecological effects

Toxicity: no data available

SDS Number: Creative 06-990-12 Revision Date: 6/21/22 Page: 18 / 22

Page 18 of 22 Item Numbers: 21707-1105

Blick Matte

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

n-Amyl acetate cas#:(628-63-7) [1-5%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Gambusia affinis (Mosquito fish) - 65 mg/l - 96 h.

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life. no data available

Ethylbenzene cas#:(100-41-4) [.1-1%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Cyprinodon variegatus (sheepshead minnow) - 88.00 mg/l - 96 h. LC50 - Lepomis macrochirus (Bluegill) - 80.00 mg/l - 96 h NOEC - Cyprinodon variegatus (sheepshead minnow) - 88 mg/l - 96 h LC50 - Oncorhynchus mykiss (rainbow trout) - 4.2 mg/l - 96 h Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 2.90 mg/l - 48 h. and other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

1-Butanol, 2-methyl-, acetate cas#:(624-41-9) [.5-4%]

Information on ecological effects

Toxicity: no data available

SDS Number: Creative 06-990-12 Page: 19 / 22 Revision Date: 6/21/22

Page 19 of 22 Item Numbers: 21707-1105

Blick Matte

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

Nitrocellulose cas#:(9004-70-0) [.5-4%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Isopropyl alcohol cas#:(67-63-0) [.5-4%]

Information on ecological effects

Toxicity: Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h.

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h. other aquatic invertebrates

Immobilization EC50 - Daphnia magna (Water flea) - 8,851 mg/l - 24 h
Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h.
EC50 - Algae - > 1,000.00 mg/l - 24 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

13 DISPOSAL CONSIDERATIONS

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or

SDS Number: Creative 06-990-12 Page: 20 / 22 Revision Date: 6/21/22

Page 20 of 22 Item Numbers: 21707-1105

Blick Matte

restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14

TRANSPORT INFORMATION

Aerosols (limited quantity), Class 2.1, ERG 126

AIR (IATA) Aerosols (limited quantity), Class 2.1, ERG 126, UN No. 1950

Vessel Aerosol (Limited Quantity), Class 2.1, UN No 1950

15

REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[10-30%] Petroleum gases, liquefied (68476-86-8) TSCA

[30-50%] RQ(5000LBS), Acetone (67-64-1) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

[5-10%] RQ(100LBS), Xylene (o-,m-,p- isomers) (1330-20-7) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

[5-10%] isopropyl acetate (108-21-4) MASS, OSHAWAC, PA, TSCA, TXAIR

[2-10%] Diacetone alcohol (123-42-2) MASS, OSHAWAC, PA, TSCA, TXAIR

[1-5%] RQ(5000LBS), 2-Pentanone, 4-methyl- (108-10-1) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, PROP65, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

[1-5%] RQ(5000LBS), Methyl ethyl ketone (78-93-3) CERCLA, HAP, HWRCRA, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

[1-5%] RQ(5000LBS), n-Amyl acetate (628-63-7) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

[.1-1%] Ethylbenzene (100-41-4) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, PRIPOL, SARA313, TOXICPOL, TSCA, TXAIR

[.5-4%] 1-Butanol, 2-methyl-, acetate (624-41-9) TSCA

[.5-4%] Nitrocellulose (9004-70-0) CFATS, GADSL, MASS, NJHS, OSHAPSM, PA, TSCA

[.5-4%] Isopropyl alcohol (67-63-0) MASS, NJHS, NRC, OSHAWAC, PA, SARA313, TSCA, TXAIR



This product can expose you to chemicals including Methyl isobutyl ketone, and Ethylbenzene, which are known to the State of California to cause cancer, and Methyl isobutyl ketone (MIBK), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Regulatory Code Legend

RQ = Reportable Quantity
TSCA = Toxic Substances Control Act
CERCLA = Superfund clean up substance
HAP = Hazardous Air Pollutants
MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances

SDS Number: Creative 06-990-12 Page: 21 / 22

Revision Date: 6/21/22

Item Numbers: 21707-1105 Page 21 of 22

Blick Matte

OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)
TXAIR = TX Air Contaminants with Health Effects Screening Level
TXHWL = TX Hazardous Waste List
CSWHS = Clean Water Act Hazardous substances
EPCRAWPC = EPCRA Water Priority Chemicals
PROP65 = CA Prop 65
HWRCRA = RCRA Hazardous Wastes
PRIPOL = Clean Water Act Priority Pollutants
TOXICPOL = Clean Water Act Priority Pollutants
CFATS = DHS Chemicals of Interest
GADSL = Global Automotive Declarable Substance List (GADSL)
OSHAPSM = OSHA Chemicals Requiring process safety management
NRC = Nationally Recognized Carcinogens

16

OTHER INFORMATION

NFPA: Health = 2, Fire = 4, Reactivity = 0, Specific Hazard = n/a



Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 6/21/22

SDS Number: Creative 06-990-12 Page: 22 / 22 Revision Date: 6/21/22

Item Numbers: 21707-1105 Page 22 of 22