Page 1 of 7

SAFETY DATA SHEET CHARBONNEL MIXTION A DORER 3 HEURES / 3H GOLD SIZE

According to Regulation (EU) No 453/2010

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name CHARBONNEL MIXTION A DORER 3 HEURES / 3H GOLD SIZE

Product No. 63682

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive for gilding

1.3. Details of the supplier of the safety data sheet

Supplier ColArt International SA

5 Rue Rene Panhard

Z.I.Nord

72021 Le Mans Cedex 2 +33 2 43 83 83 00

Lefranc-Bourgeois@colart.fr

Contact Person Jon Lloyd Group Regulatory Affairs Manager +44 (0)20842434224; j.lloyd@colart.co.uk

1.4. Emergency telephone number

33 (0)2 43 83 83 00 This number is only available during office hours.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) R10, R52/53, R66, R67.

2.2. Label elements

Risk Phrases

R10 Flammable.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Safety Phrases

S2 Keep out of the reach of children.

S37 Wear suitable gloves.

S46 If swallowed, seek medical advice immediately and show this container or

label.

S51 Use only in well-ventilated areas.

S56 Dispose of this material and its container to hazardous or special waste

collection point.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hydrocarbons, C9-C11, < 2% aromatics 30-60%

CAS-No.: 64742-48-9 EC No.: 919-857-5

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 3 - H226 Xn;R65

EUH066 R10,R66,R67.

STOT SE 3 - H336 Asp. Tox. 1 - H304

SDS No. 12673 Page 2 of 7

MSDS for #27020 - CH**RHISTIPPINHELLMISTIPON A DORER 3 HEURES / 3H GOLD SIZE**

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.; STRAIGHT RUN KEROSINE

10-30%

CAS-No.: 64742-88-7 EC No.: 265-191-7

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 3 - H226 Xn;R65.
EUH066 N;R51/53.
Asp. Tox. 1 - H304 R66,R10.
Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition Comments

The product contains organic solvents.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Remove victim immediately from source of exposure. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Provide rest, warmth and fresh air. Get medical attention immediately!

Skin contact

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

Protective equipment for fire-fighters

Use protective equipment appropriate for surrounding materials.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Do not smoke, use open fire or other sources of ignition. Avoid inhalation of vapours and contact with skin and eyes.

SDS No. 12673 Page 3 of 7

MSDS for #27020 - CHARBORD NEEL MEXTON A DORER 3 HEURES / 3H GOLD SIZE

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

6.4. Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Provide good ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool and well-ventilated place. Store in closed original container in a dry place.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.2. Exposure controls

Protective equipment





Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

In case of inadequate ventilation use suitable respirator.

Hand protection

Use protective gloves.

Eye protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Liquid

Colour Lightly coloured.
Odour Characteristic.
Solubility Insoluble in water
Initial boiling point and boiling range >150 760 mm Hg

Melting point (°C)

No information available.

Relative density 0.9 20

Vapour density (air=1)
No information available.

Vapour pressure

SDS No. 12673 Page 4 of 7

MSDS for #27020 - CH**RESONE OLD NUTS LIME ON A DORER 3 HEURES / 3H GOLD SIZE**

Evaporation rate

No information available.

Evaporation Factor

No information available.

pH-Value, Conc. Solution

Not applicable.

pH-Value, Diluted Solution

Not applicable.

Viscosity 1.5 10-4 mPas 40

Solubility Value (G/100G H2O@20°C)

Not applicable.

Flash point 38 CC (Closed cup).

Auto Ignition Temperature (°C) 250

Flammability Limit - Lower(%) No information available. Flammability Limit - Upper(%) No information available.

9.2. Other information

Not determined.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

Avoid contact with acids and oxidising substances.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity:

Acute Toxicity (Oral LD50)

Not determined.

Acute Toxicity (Dermal LD50)

Not determined.

Acute Toxicity (Inhalation LC50)

Not determined.

Inhalation

Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness.

Ingestion

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

Eye contact

May cause severe irritation to eyes.

SDS No. 12673 Page 5 of 7

MSDS for #27020 - CHREGORIAN METALINISTION A DORER 3 HEURES / 3H GOLD SIZE

Target Organs

Skin Eyes Respiratory system, lungs

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute Toxicity - Fish

Not determined.

Acute Toxicity - Aquatic Invertebrates

Not determined.

Acute Toxicity - Aquatic Plants

Not determined.

Acute Toxicity - Microorganisms

Not determined.

12.2. Persistence and degradability

Degradability

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

Not relevant

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

 UN No. (ADR/RID/ADN)
 1263

 UN No. (IMDG)
 1263

 UN No. (ICAO)
 1263

14.2. UN proper shipping name

Proper Shipping Name PAINT RELATED MATERIAL
Proper Shipping Name PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

IMDC Class 3

SDS No.

12673

Page 6 of 7 MSDS for #27020 - CHREGORD PUNCEL MINITION A DORER 3 HEURES / 3H GOLD SIZE

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group Ш IMDG Packing group ш ICAO Packing group Ш

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

14.6. Special precautions for user

Hazard No. (ADR) 30 Flammable liquid (flash-point between 23°C and 60°C, inclusive) or flammable liquid or solid in the

molten state with a flash-point above 60°C, heated to a temperature equal to or above its flash-point, or s

heating liquid.

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments

Water hazard classification

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Issued By HS&E Manager. **Revision Date** 04/07/2012

Revision 1

10/03/2011

Risk Phrases In Full

R10

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

SDS No. 12673 Page 7 of 7

MSDS for #27020 - CH**ARISTIPOLITIES MISSTEON A DORER 3 HEURES / 3H GOLD SIZE**

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in a process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such