Version 3.1 (10/12/2013) - Page 1/9

**RÉSINE ÉPOXY: RÉSINE - 766334A** 

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

# SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: RÉSINE ÉPOXY: RÉSINE

Product code: 766334A.

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Casting material

# 1.3. Details of the supplier of the safety data sheet

Registered company name: PEBEO S A.

Address: 305 AVENUE DU PIC DE BERTAGNE - BP106 -.13881.GEMENOS CEDEX.FRANCE.

Telephone: 33 (0) 4.42.32.08.08. Fax: 33 (0) 4.42.32.01.70.

cdedeyne@pebeo.com www.pebeo.com

## 1.4. Emergency telephone number: 33 (0) 1.45.42.59.59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

## SECTION 2: HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

# In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the

# In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Skin irritation (Xi, R 38).

Eye irritation (Xi, R 36).

Skin sensitisation (Xi, R 43).

Aquatic environmental hazard, chronic toxicity: toxic (N, R 51/53).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

# 2.2. Label elements

## In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS07

GHS09

Signal Word: WARNING

Product identifiers:

603-074-00-8

REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE

MOLECULAR WEIGHT < 700)

BISPHÉNOL-F-ÉPICHLORHYDRINE, RÉSINE ÉPOXYDIQUES (POIDS MOLÉCULAIRE MOYEN < EC 500-006-8

DÉRIVÉS ÉPOXYDIQUES

Version 3.1 (10/12/2013) - Page 2/9

PEBEO S A

## **RÉSINE ÉPOXY: RÉSINE - 766334A**

EC 201-283-5 TOLUÈNE-4-SULFONATE DE MÉTHYLE

Additional labeling:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response:

P321 Specific treatment (see ... on this label).

P337 + P313 If eye irritation persists: Get medical advice/attention.

Precautionary statements - Disposal:

P501 Dispose of contents/container to ...

# 2.3. Other hazards

The mixture does not contain any substances classified as 'Substances of Very High Concern' (SVHC) by the European CHemical's Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

No substances fulfil the criteria set forth in annexe II section A of the REACH regulation (EC) no 1907/2006.

## 3.2. Mixtures

# **Composition:**

Composition:				
Identification	(EC) 1272/2008	67/548/EEC	Note	%
INDEX: 603-074-00-8	GHS07, GHS09	Xi,N		50 <= x % < 100
CAS: 25068-38-6	Wng	Xi;R36/38-R43		
EC: 500-033-5	Eye Irrit. 2, H319	N;R51/53		
REACH: 01-2119456619-26-0018	Skin Irrit. 2, H315			
	Skin Sens. 1, H317			
REACTION PRODUCT:	Aquatic Chronic 2, H411			
BISPHENOL-A-(EPICHLORHYDRIN)				
EPOXY RESIN (NUMBER AVERAGE				
MOLECULAR WEIGHT < 700)				
CAS: 28064-14-4	GHS07, GHS09	Xi,N		25 <= x % < 50
EC: 500-006-8	Wng	Xi;R36/38-R43		
REACH: 01-2119454392-40-xxxx	Skin Irrit. 2, H315	N;R51/53		
	Skin Sens. 1, H317			
BISPHÉNOL-F-ÉPICHLORHYDRINE,	Eye Irrit. 2, H319			
RÉSINE ÉPOXYDIQUES (POIDS	Aquatic Chronic 2, H411			
MOLÉCULAIRE MOYEN < 700)				
DÉRIVÉS ÉPOXYDIQUES	GHS07, GHS09	Xi,N		10 <= x % < 25
	Wng	Xi;R36/38-R43		
	Skin Irrit. 2, H315	N;R51/53		
	Skin Sens. 1, H317			
	Eye Irrit. 2, H319			
	Aquatic Chronic 2, H411			

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH) Version 3.1 (10/12/2013) - Page 3/9
PEBEO S A **RÉSINE ÉPOXY : RÉSINE - 766334A** 

CAS: 80-48-8	GHS07	Xn	2.5 <= x % < 10
EC: 201-283-5	Wng	Xn;R22	
	Acute Tox. 4, H302	Xi;R36/38-R43	
TOLUÈNE-4-SULFONATE DE MÉTHYLE	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
	Eye Irrit. 2, H319		

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. Description of first aid measures

## In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

## In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

## In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

## 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

# 5.1. Extinguishing media

# Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

## Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

# 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

Version 3.1 (10/12/2013) - Page 4/9

RÉSINE ÉPOXY : RÉSINE - 766334A

## 5.3. Advice for firefighters

No data available.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

## For non fire-fighters

Avoid any contact with the skin and eyes.

## For fire-fighters

Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

## 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

## 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

## 6.4. Reference to other sections

No data available.

## SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

## 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

## Fire prevention:

Prevent access by unauthorised personnel.

# Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid skin and eye contact with this mixture.

# Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

# 7.2. Conditions for safe storage, including any incompatibilities

No data available.

## Storage

Keep out of reach of children.

## Packaging

Always keep in packaging made of an identical material to the original.

# 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

No data available.

## 8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Version 3.1 (10/12/2013) - Page 5/9

# **RÉSINE ÉPOXY : RÉSINE - 766334A**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):







Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Recommended properties:

- Impervious gloves in accordance with standard EN374

### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

# General information:

Physical state: viscous liquid.

# Important health, safety and environmental information

pH: Not relevant.
Boiling point/boiling range: not relevant.
Flash point interval: not relevant.

Vapour pressure (50°C): Below 110 kPa (1.10 bar).

Density: > 1
Water solubility: Insoluble.
Melting point/melting range: not relevant.
Self-ignition temperature: not relevant.
Decomposition point/decomposition range: not relevant.

## 9.2. Other information

No data available.

Version 3.1 (10/12/2013) - Page 6/9

**RÉSINE ÉPOXY : RÉSINE - 766334A** 

## SECTION 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

## 10.5. Incompatible materials

# 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

## SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

May cause an allergic reaction by skin contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and a respiratory tract sensitiser as well as an irritant.

Constituents with a low molecular weight irritate the eyes, mucous membranes and the skin

Repeated contact with the skin may cause irritation and hypersensitisation, possibly in combination with other epoxide compounds.

# 11.1.1. Substances

No toxicological data available for the substances.

## 11.1.2. Mixture

# Respiratory or skin sensitisation:

Contains epoxy compounds. May cause an allergic reaction.

# SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

## 12.1. Toxicity

## **12.1.2.** Mixtures

No aquatic toxicity data available for the mixture.

# 12.2. Persistence and degradability

No data available.

# 12.3. Bioaccumulative potential

No data available.

## 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

No data available.

# 12.6. Other adverse effects

No data available.

Version 3.1 (10/12/2013) - Page 7/9

RÉSINE ÉPOXY: RÉSINE - 766334A

#### SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

20 01 27 \* paint, inks, adhesives and resins containing dangerous substances

15 01 02 plastic packaging

# SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2013).

# 14.1. UN number

3082

# 14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(dérivés époxydiques)

## 14.3. Transport hazard class(es)

- Classification:



9

# 14.4. Packing group

Ш

## 14.5. Environmental hazards

- Environmentally hazardous material:



# 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M6	III	9	90	5 L	274 335 601	E1	3	Е

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	9	-	III	5 L	F-A,S-F	274 335	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	9	-	III	964	450 L	964	450 L	A97	E1
								A158	
	9	-	III	Y964	30 kg G	-	-	A97	E1
								A158	

Version 3.1 (10/12/2013) - Page 8/9

**RÉSINE ÉPOXY: RÉSINE - 766334A** 

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

## SECTION 15: REGULATORY INFORMATION

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## - Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Regulation EC 1272/2008 modified by regulation EC 618/2012

#### - Container information:

No data available.

#### - Particular provisions:

No data available.

## - Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704):

NFPA 704, Labelling: Health=2 Inflammability=3 Instability/Reactivity=1 Specific Risk=none



## 15.2. Chemical safety assessment

No data available.

## SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols:



Irritant



Dangerous for the environment

Contains:

DÉRIVÉS ÉPOXYDIOUES

EC 201-283-5 EC 500-006-8 TOLUÈNE-4-SULFONATE DE MÉTHYLE

BISPHÉNOL-F-ÉPICHLORHYDRINE, RÉSINE ÉPOXYDIQUES (POIDS MOLÉCULAIRE MOYEN <

603-074-00-8 REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT < 700)

Risk phrase:

R 51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Version 3.1 (10/12/2013) - Page 9/9

## PEBEO S A

R 43

# **RÉSINE ÉPOXY: RÉSINE - 766334A**

May cause sensitisation by skin contact.

R 36/38	Irritating to eyes and skin.
	Contains epoxy constituents. See information supplied by the manufacturer.
Safety phrase :	
S 2	Keep out of the reach of children.
S 24	Avoid contact with skin.
S 29	Do not empty into drains.
S 37	Wear suitable gloves.
S 46	If swallowed, seek medical advice immediately and show this container or label.
C 12	Voor away from food, drink and animal foodingstuffs

S 13 Keep away from food, drink and animal feedingstuffs.

S 25 Avoid contact with eyes.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S 39 Wear eye/face protection.

S 64 If swallowed, rinse mouth with water (only if the person is conscious).

# Title for H, EUH and R indications mentioned in section 3:

H302	Harmful if swallowed.
H315	Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

R 22 Harmful if swallowed. R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

## Abbreviations:

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark GHS09 : Environment