43211-4592

NAZDAR INK TECHNOLOGIES

SAFETY DATA SHEET

Published Date Nov-13-2023

Revision Date Nov-13-2023 **Revision Number** 2.7

1. IDENTIFICATION

Product identifier Product code Product name Product category

59LF124 **Brilliant Orange** 59000 Series SV Enamel Screen Ink

Other means of identification Synonyms

Recommended use of the chemical and restrictions on use Industrial Printing Operations **Recommended use**

None

Details of the supplier of the safety data sheet UNITED STATES UNITED KINGDOM Nazdar Company Nazdar Limited Barton Road 8501 Hedge Lane Terrace Shawnee, KS 66227 Tel: +001-913-422-1888 Heaton Mersey Stockport, England SK4 3EG Tel: +44 161 442 2111 Tel: +001-800-677-4657 Fax: +001-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887 24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Skin sensitization	Category 1 - (H317)
Carcinogenicity	Category 1B - (H350)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Aspiration hazard	Category 1 - (H304)
Flammable liquids	Category 3 - (H226)

Label elements



Danger

Hazard statements

H226 - Flammable liquid and vapor H304 - May be fatal if swallowed and enters airways

H317 - May cause an allergic skin reaction

Page 1/12

Page 1 of 12

Revision Date Nov-13-2023

H350 - May cause cancer

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

P201 - Obtain special instructions before use

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P403 + P235 - Store in a well-ventilated place. Keep cool

Hazards not otherwise classified (HNOC)

Causes mild skin irritation. Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No.	Weight-%	Trade secret	Note
Stoddard solvent	8052-41-3	10 - 30	*	
Barium sulfate	7727-43-7	10 - 30	*	
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	1 - 5	*	
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5	*	
2-Butanone, oxime	96-29-7	0.1 - < 1	*	
Ethyl benzene (constituent)	100-41-4	0.1 - < 1	*	1
Naphthalene (constituent)	91-20-3	0.1 - < 1	*	1
Cobalt Compounds	Not Available	0.1 - < 1	*	

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note

1. Hazardous Constituent contained in Complex Substance(s) required for disclosure

4. FIRST-AID MEASURES

Description of first aid measures

General Advice Eye Contact	Show this safety data sheet to the doctor in attendance. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Most important symptoms and eff	ects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Item Numbers: 43211-4592

Page 3 of 12

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Conditions for safe storage, including any incompatibilities

Storage

Handling

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

Incompatible Products

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Chemical name	ACGIH TLV
Stoddard solvent 8052-41-3	TWA: 100 ppm
	TWA: 5 mg/m ³ inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 20 ppm

Ethyl benzene (constituent) 100-41-4	TWA: 20 ppm
Naphthalene (constituent) 91-20-3	TWA: 10 ppm Skin
Chemical name Stoddard solvent	OSHA PEL
8052-41-3	TWA: 500 ppm TWA: 2900 mg/m ³
Barium sulfate	TWA: 2500 mg/m ³ total dust
7727-43-7	TWA: 5 mg/m ³ respirable fraction
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm TWA: 435 mg/m ³
Ethyl benzene (constituent)	TWA: 100 ppm
100-41-4	TWA: 435 mg/m ³
Naphthalene (constituent)	TWA: 10 ppm
91-20-3	TWA: 50 mg/m ³
Chamical name	
Chemical name Stoddard solvent	OSHA PEL (vacated) TWA: 100 ppm
8052-41-3	TWA: 100 ppm TWA: 525 mg/m ³
Barium sulfate	TWA: 525 mg/m ²
7727-43-7	TWA: 5 mg/m ³ respirable fraction
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm
1330-20-7	TWA: 435 mg/m ³
	STEL: 150 ppm
	STEL: 655 mg/m ³
Ethyl benzene (constituent)	TWA: 100 ppm
100-41-4	TWA: 435 mg/m ³
	STEL: 125 ppm
	STEL: 545 mg/m ³ TWA: 10 ppm
Naphthalene (constituent) 91-20-3	TWA: 10 ppm TWA: 50 mg/m ³
51-20-3	STEL: 15 ppm
	STEL: 75 mg/m ³
Chemical name	Ontario TWAEV
Stoddard solvent	TWA: 525 mg/m ³
8052-41-3	
Barium sulfate 7727-43-7	TWA: 5 mg/m ³ inhalable particulate matter
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm
Ethyl benzene (constituent) 100-41-4	TWA: 20 ppm
Naphthalene (constituent) 91-20-3	TWA: 10 ppm Skin
Chemical name	Mexico OEL (TWA)
Stoddard solvent 8052-41-3	TWA/VLE-PPT: 100 ppm
Barium sulfate 7727-43-7	TWA/VLE-PPT: 10 mg/m ³
Xylenes (o-, m-, p- isomers)	TWA/VLE-PPT: 100 ppm
1330-20-7	STEL/PPT-CT: 150 ppm
Ethyl benzene (constituent) 100-41-4	TWA/VLE-PPT: 20 ppm
Naphthalene (constituent)	TWA/VLE-PPT: 10 ppm
91-20-3	STEL/PPT-CT: 15 ppm

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In

Page 5 of 12

Revision Date Nov-13-2023

	case of insufficient ventilation, wear suitable respiratory equipment.	
Individual protection measures, such as personal protective equipment		
Eye/Face Protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.	
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.	
Hand Protection	Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.	
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.	
General Hygiene Consideration	s Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and	chemical properties		
Physical state	Liquid	Appearance	Colored
Odor	Characteristic	Odor Threshold	No information available
Property	Values	Remarks • Method	
pH		No data available	
Melting Point / Freezing Point Boiling Point / Boiling Range	No information available 149 °C / 300 °F 	No data available	
Flash Point	46 °C / 115 °F	Setaflash closed cup	
Evaporation rate		No data available	
Flammability Limit in Air			
Upper flammability limit		No data available	
Lower flammability limit		No data available	
Vapor Pressure		No data available	
Vapor Density		No data available	
Specific Gravity	1.18		
Water Solubility		No data available	
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/wat		No data available	
Autoignition Temperature	No information available	No data available	
Hyphen		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	

Item Numbers: 43211-4592

Revision Date Nov-13-2023

Explosive Properties Oxidizing Properties	No data available No data available		
Other information			
Photochemically Reactive	No		
Weight Per Gallon (Ibs/gal)	9.85		
VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
(less water)			

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

<u>Hazardous decomposition products</u> Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Specific test data for the substance or mixture is not available.
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Chemical name	Oral LD50	
Barium sulfate 7727-43-7	= 307000 mg/kg (Rat)	
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	
2-Butanone, oxime 96-29-7	= 930 mg/kg (Rat)	
Ethyl benzene (constituent) 100-41-4	= 3500 mg/kg (Rat)	
Naphthalene (constituent) 91-20-3	= 1110 mg/kg (Rat)	
Chemical name	Dermal LD50	
Stoddard solvent 8052-41-3	> 3000 mg/kg (Rabbit)	
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 2000 mg/kg (Rabbit)	
Xylenes (o-, m-, p- isomers)	> 4350 mg/kg (Rabbit)	

Page 7 of 12

1330-20-7		
2-Butanone, oxime 96-29-7	1000 - 1800 mg/kg (Rabbit)	
Ethyl benzene (constituent) 100-41-4	= 15400 mg/kg (Rabbit)	
Naphthalene (constituent) 91-20-3	= 1120 mg/kg (Rabbit)	
Cobalt Compounds	> 5000 mg/kg (Rabbit)	
Chemical name	Inhalation LC50	
Stoddard solvent 8052-41-3	> 5.5 mg/L (Rat)4 h	
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 590 mg/m³ (Rat)4 h	
Xylenes (o-, m-, p- isomers) 1330-20-7	= 29.08 mg/L (Rat)4 h	
2-Butanone, oxime 96-29-7	> 4.83 mg/L (Rat)4 h	
Ethyl benzene (constituent) 100-41-4	= 17.4 mg/L (Rat)4 h	
Naphthalene (constituent) 91-20-3	> 0.4 mg/L (Rat)4 h	
Cobalt Compounds	> 10 mg/L (Rat)1 h	

Symptoms related to the physical, chemical and toxicological characteristics

Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritation Irritation Corrosivity Sensitization	Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).	
Mutagenic Effects	Specific test data for the substance or mixture is not available.	
Carcinogenic effects	Specific test data for the substance or mixture is not available. May cause cancer. (based on components).	
Reproductive Effects	Specific test data for the substance or mixture is not available.	
STOT - single exposure	Specific test data for the substance or mixture is not available.	
STOT - repeated exposure	Specific test data for the substance or mixture is not available. Causes damage to organs	
	through prolonged or repeated exposure. (based on components).	
Chronic Toxicity	Specific test data for the substance or mixture is not available	
Aspiration hazard	Specific test data for the substance or mixture is not available. May be fatal if swallowed and	
	enters airways. (based on components).	
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.	
Chemical name	ACGIH	
Ethyl benzene (constituent) 100-41-4	АЗ	
Naphthalene (constituent)	A3	
91-20-3		
Chemical name	IARC	
Ethyl benzene (constituent)	Group 2B	
100-41-4		
Naphthalene (constituent) 91-20-3	Group 2B	
Cobalt Compounds	Group 2B	

Symptoms

Page 8 of 12

Chemical name	NTP
Naphthalene (constituent) 91-20-3	Reasonably Anticipated
Chemical name	OSHA
Ethyl benzene (constituent) 100-41-4	X
Naphthalene (constituent) 91-20-3	X

Numerical measures of toxicity - Product Information

Unknown acute toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	20,000.00 mg/kg
ATEmix (dermal)	86,668.80 mg/kg
ATEmix (inhalation-gas)	99,999.00
ATEmix (inhalation-dust/mist)	118.20 mg/l
ATEmix (inhalation-vapor)	866.70 mg/l

12. ECOLOGICAL INFORMATION

<u>Ecotoxicity</u> Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants
2-Butanone, oxime	72h EC50 Desmodesmus subspicatus: = 83 mg/L
96-29-7	
Ethyl benzene (constituent)	72h EC50 Pseudokirchneriella subcapitata: = 4.6 mg/L
100-41-4	96h EC50 Pseudokirchneriella subcapitata: > 438 mg/L
	72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L static
	96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L static

Chemical name	Fish
Solvent naphtha, petroleum, heavy aromatic	96h LC50 Pimephales promelas: = 19 mg/L (static)
64742-94-5	96h LC50 Oncorhynchus mykiss: = 2.34 mg/L
	96h LC50 Lepomis macrochirus: = 1740 mg/L (static)
	96h LC50 Pimephales promelas: = 45 mg/L (flow-through)
	96h LC50 Pimephales promelas: = 41 mg/L
Xylenes (o-, m-, p- isomers)	96h LC50 Pimephales promelas: = 13.4 mg/L (flow-through)
1330-20-7	96h LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L (static)
	96h LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L
	96h LC50 Poecilia reticulata: 30.26 - 40.75 mg/L (static)
	96h LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L (flow-through)
	96h LC50 Lepomis macrochirus: = 19 mg/L
	96h LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L (static)
	96h LC50 Pimephales promelas: 23.53 - 29.97 mg/L (static)
	96h LC50 Cyprinus carpio: = 780 mg/L (semi-static)
	96h LC50 Cyprinus carpio: > 780 mg/L
2-Butanone, oxime	96h LC50 Pimephales promelas: 777 - 914 mg/L (flow-through)
96-29-7	96h LC50 Poecilia reticulata: = 760 mg/L (static)
Ethyl benzene (constituent)	96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L (static)
100-41-4	96h LC50 Oncorhynchus mykiss: = 4.2 mg/L (semi-static)
	96h LC50 Pimephales promelas: 7.55 - 11 mg/L (flow-through)
	96h LC50 Lepomis macrochirus: = 32 mg/L (static)
	96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L (static)
	96h LC50 Poecilia reticulata: = 9.6 mg/L (static)
Naphthalene (constituent)	96h LC50 Oncorhynchus mykiss: = 1.6 mg/L (flow-through)

Page 9 of 12

91-20-3	96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L (static) 96h LC50 Pimephales promelas: = 1.99 mg/L (static) 96h LC50 Lepomis macrochirus: = 31.0265 mg/L (static) 96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L (flow-through)
Chemical name	Crustacea
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	48h EC50 Daphnia magna: = 0.95 mg/L
Xylenes (o-, m-, p- isomers) 1330-20-7	48h EC50 water flea: = 3.82 mg/L 48h LC50 Gammarus lacustris: = 0.6 mg/L
2-Butanone, oxime 96-29-7	48h EC50 Daphnia magna: = 750 mg/L
Ethyl benzene (constituent) 100-41-4	48h EC50 Daphnia magna: 1.8 - 2.4 mg/L
Naphthalene (constituent) 91-20-3	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L Static 48h EC50 Daphnia magna: = 1.96 mg/L Flow through 48h LC50 Daphnia magna: = 2.16 mg/L

Persistence and Degradability No information available.

Bioaccumulation

Chemical name	Partition coefficient
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	2.9 - 6.1
Xylenes (o-, m-, p- isomers) 1330-20-7	2.77 - 3.15
2-Butanone, oxime 96-29-7	0.65
Ethyl benzene (constituent) 100-41-4	3.2
Naphthalene (constituent) 91-20-3	3.6

13. DISPOSAL CONSIDERATIONS			
Waste treatment methods			
Waste Disposal Methods	Contain and dispose of waste according to local regulations.		
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.		
	14. TRANSPORT INFORMATION		
Note:	This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.		
DOT_ UN/ID no Proper Shipping Name Transport hazard class(es)	In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33]. UN1210 Printing Ink 3		

Page 9/12

Revision Date Nov-13-2023

Packing Group	III
ICAO / IATA / IMDG / IMO	
UN/ID no	UN1210
Proper Shipping Name	Printing Ink
Transport hazard class(es)	3
Packing Group	111

15. REGULATORY INFORMATION

International Inventories

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5	1.0
Ethyl benzene (constituent)	100-41-4	0.1 - < 1	0.1
Naphthalene (constituent)	91-20-3	0.1 - < 1	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61) This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Chemical name	CAS No.	Weight-%
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Ethyl benzene (constituent)	100-41-4	0.1 - < 1
Naphthalene (constituent)	91-20-3	0.1 - < 1
Cobalt Compounds	Not Available	0.1 - < 1

US State Regulations

Chemical name	Massachusetts
Stoddard solvent	×
8052-41-3	
Barium sulfate	×
7727-43-7	
Xylenes (o-, m-, p- isomers)	×
1330-20-7	
Ethyl benzene (constituent)	×
100-41-4	
Naphthalene (constituent)	×
91-20-3	

	Minnesota Right To Know
Stoddard solvent 8052-41-3	X
Barium sulfate 7727-43-7	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
2-Butanone, oxime 96-29-7	X
Ethyl benzene (constituent) 100-41-4	X

Revision Date Nov-13-2023

Naphthalene (constituent)	X
91-20-3	
Chemical name	New Jersey
Stoddard solvent 8052-41-3	×
Barium sulfate 7727-43-7	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Ethyl benzene (constituent) 100-41-4	X
Naphthalene (constituent) 91-20-3	×
Cobalt Compounds	X

Chemical name	Pennsylvania
Stoddard solvent	Х
8052-41-3	
Barium sulfate	×
7727-43-7	
Xylenes (o-, m-, p- isomers)	X
1330-20-7	
Ethyl benzene (constituent)	X
100-41-4	
Naphthalene (constituent)	×
91-20-3	
Cobalt Compounds	X

<u>California Proposition 65</u> This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical name	California Proposition 65
Ethyl benzene (constituent)	Carcinogen
Naphthalene (constituent)	Carcinogen

<u>Canada</u>

Chemical name	NPRI - National Pollutant Release Inventory
Stoddard solvent	Part 5 Substance - Volatile Organic Compounds with Additional
8052-41-3	Reporting Requirements
Solvent naphtha, petroleum, heavy aromatic	Part 5 Substance - Volatile Organic Compounds with Additional
64742-94-5	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants
Xylenes (o-, m-, p- isomers)	Part 1, Group A Substance
1330-20-7	Part 5 Substance - Volatile Organic Compounds with Additional
	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants
Ethyl benzene (constituent)	Part 1, Group A Substance
100-41-4	Part 4 Substance - Criteria Air Contaminants
Naphthalene (constituent)	Part 1, Group A Substance
91-20-3	Part 4 Substance - Criteria Air Contaminants
Cobalt Compounds	Part 1, Group B Substance

16. OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Revision Date Nov-13-2023

TWA STEL Ceiling	TWA (time-weighted average) STEL (Short Term Exposure Limit) Maximum limit value
Cening	
ACGIH: (American Conference of Gov A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen IARC: (International Agency for Reset Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Hun Group 2B - Possibly Carcinogenic to Hun Group 3 - Not Classifiable as to Carcinog NTP: (National Toxicity Program) Known - Known Carcinogen Reasonably Anticipated to be a Human C OSHA: (Occupational Safety & Health J X - Present	arch on Cancer) nans nans enicity in Humans carcinogen

Revision Date

Nov-13-2023

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet