

NAZDAR
INK TECHNOLOGIES

43212-1102

SAFETY DATA SHEET

Published Date
Nov-13-2023

Revision Date
Nov-13-2023

Revision Number
2.6

1. IDENTIFICATION**Product identifier**

Product code 5536
Product name Extender Base
Product category 5500 Series SV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Industrial Printing Operations

Details of the supplier of the safety data sheet

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: +001-913-422-1888	Stockport, England SK4 3EG
Tel: +001-800-677-4657	Tel: +44 161 442 2111
Fax: +001-913-422-2294	
www.nazdar.com	

Emergency telephone number

USA: Chemtrec: +001-800-424-9300
Outside USA: Chemtrec: +001-703-527-3887
24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION**Classification**

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)
Carcinogenicity	Category 1B - (H350)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Aspiration hazard	Category 1 - (H304)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

Label elements

Signal word
Danger

Hazard statements

H225 - Highly flammable liquid and vapor

5536 Extender Base

Revision Date Nov-13-2023

H304 - May be fatal if swallowed and enters airways
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H350 - May cause cancer
 H373 - May cause damage to organs through prolonged or repeated exposure
 H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P201 - Obtain special instructions before use
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
 P308 + P313 - IF exposed or concerned: Get medical advice/attention
 P331 - Do NOT induce vomiting
 P403 + P235 - Store in a well-ventilated place. Keep cool

Hazards not otherwise classified (HNOC)

Causes mild skin irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Mixture**

Chemical name	CAS No.	Weight-%	Trade secret	Note
Petroleum distillates, hydrotreated light	64742-47-8	10 - 30	*	
Solvent naphtha, petroleum, light aromatic	64742-95-6	10 - 30	*	
Calcium carbonate	1317-65-3	10 - 30	*	
Talc	14807-96-6	5 - 10	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	5 - 10	*	1
Ethylene glycol monopropyl ether	2807-30-9	5 - 10	*	
Crystalline silica (cristobalite)	14464-46-1	5 - 10	*	
Resin	Not Available	1 - 5	*	
Ethyl alcohol	64-17-5	1 - 5	*	
1,3,5-Trimethylbenzene (constituent)	108-67-8	1 - 5	*	1
Cumene (constituent)	98-82-8	0.1 - < 1	*	1
Quartz, crystalline silica	14808-60-7	0.1 - < 1	*	

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note

1. Hazardous Constituent contained in Complex Substance(s) required for disclosure

4. FIRST-AID MEASURES**Description of first aid measures****General Advice**

Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention. Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Inhalation

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Ingestion

5536 Extender Base

Revision Date Nov-13-2023

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE**Precautions for safe handling****Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

Incompatible Products

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters**

5536 Extender Base

Revision Date Nov-13-2023

Exposure limits

Chemical name	ACGIH TLV
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter
1,2,4-Trimethylbenzene (constituent) 95-63-6	TWA: 10 ppm
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.025 mg/m ³ respirable particulate matter
Ethyl alcohol 64-17-5	STEL: 1000 ppm
1,3,5-Trimethylbenzene (constituent) 108-67-8	TWA: 10 ppm
Cumene (constituent) 98-82-8	TWA: 5 ppm
Quartz, crystalline silica 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter

Chemical name	OSHA PEL
Calcium carbonate 1317-65-3	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction
Crystalline silica (cristobalite) 14464-46-1	TWA: 50 µg/m ³
Ethyl alcohol 64-17-5	TWA: 1000 ppm TWA: 1900 mg/m ³
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m ³ Skin
Quartz, crystalline silica 14808-60-7	TWA: 50 µg/m ³

Chemical name	OSHA PEL (vacated)
Calcium carbonate 1317-65-3	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction
Talc 14807-96-6	TWA: 2 mg/m ³ respirable dust
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m ³ respirable dust
Ethyl alcohol 64-17-5	TWA: 1000 ppm TWA: 1900 mg/m ³
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m ³ Skin
Quartz, crystalline silica 14808-60-7	TWA: 0.1 mg/m ³ respirable dust

Chemical name	Ontario TWA EV
Talc 14807-96-6	TWA: 2 mg/m ³ respirable fraction
Ethylene glycol monopropyl ether 2807-30-9	TWA: 25 ppm TWA: 110 mg/m ³ Skin
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m ³ respirable fraction
Ethyl alcohol 64-17-5	STEL: 1000 ppm
Cumene (constituent) 98-82-8	TWA: 50 ppm
Quartz, crystalline silica 14808-60-7	TWA: 0.10 mg/m ³ respirable fraction

Chemical name	Mexico OEL (TWA)
Talc 14807-96-6	TWA/VLE-PPT: 2 mg/m ³ respirable fraction STEL/PPT-CT: 2 mg/m ³ respirable fraction
Crystalline silica (cristobalite)	TWA/VLE-PPT: 0.025 mg/m ³ respirable fraction

5536 Extender Base

Revision Date Nov-13-2023

14464-46-1 Ethyl alcohol 64-17-5	STEL/PPT-CT: 1000 ppm
Cumene (constituent) 98-82-8	TWA/VLE-PPT: 50 ppm
Quartz, crystalline silica 14808-60-7	TWA/VLE-PPT: 0.025 mg/m ³ respirable fraction

Appropriate engineering controls**Engineering Measures**

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Wear safety glasses with side shields (or goggles). If splashes are likely to occur: Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

Skin Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Hand Protection

Chemical resistant protective gloves.
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other
Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.
Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid	Appearance	Colored
Odor	Characteristic	Odor Threshold	No information available
Property	Values	Remarks • Method	
pH		No data available	
Melting Point / Freezing Point	No information available	No data available	
Boiling Point / Boiling Range	> 149 °C / 300 °F		
Flash Point	21 °C / 70 °F	Pensky Martens Closed Cup (PMCC)	
Evaporation rate		No data available	
Flammability Limit in Air			

5536 Extender Base

Revision Date Nov-13-2023

Upper flammability limit		No data available
Lower flammability limit		No data available
Vapor Pressure		No data available
Vapor Density		No data available
Specific Gravity	1.1	
Water Solubility		No data available
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition Temperature	No information available	No data available
Hyphen		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available
Explosive Properties	No data available	
Oxidizing Properties	No data available	

Other information

Photochemically Reactive	Yes
Weight Per Gallon (lbs/gal)	9.18

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
52.51	70.14	4.82	577.92

10. STABILITY AND REACTIVITY**Reactivity**

No information available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous decomposition productsThermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO₂). Carbon monoxide.**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation	Specific test data for the substance or mixture is not available.
Eye Contact	Specific test data for the substance or mixture is not available.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Chemical name	Oral LD50
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg (Rat)
1,2,4-Trimethylbenzene (constituent)	= 3280 mg/kg (Rat)

5536 Extender Base

Revision Date Nov-13-2023

95-63-6	
Ethylene glycol monopropyl ether 2807-30-9	= 3089 mg/kg (Rat)
Ethyl alcohol 64-17-5	= 7060 mg/kg (Rat)
Cumene (constituent) 98-82-8	= 1400 mg/kg (Rat)

Chemical name	Dermal LD50
Petroleum distillates, hydrotreated light 64742-47-8	> 2000 mg/kg (Rabbit)
Solvent naphtha, petroleum, light aromatic 64742-95-6	> 2000 mg/kg (Rabbit)
1,2,4-Trimethylbenzene (constituent) 95-63-6	> 3160 mg/kg (Rabbit)
Ethylene glycol monopropyl ether 2807-30-9	= 870 mg/kg (Rabbit)
Cumene (constituent) 98-82-8	= 12300 µL/kg (Rabbit)

Chemical name	Inhalation LC50
Petroleum distillates, hydrotreated light 64742-47-8	> 5.2 mg/L (Rat) 4 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 3400 ppm (Rat) 4 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 18 g/m ³ (Rat) 4 h
Ethylene glycol monopropyl ether 2807-30-9	= 1530 ppm (Rat) 7 h
Ethyl alcohol 64-17-5	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
1,3,5-Trimethylbenzene (constituent) 108-67-8	= 24 g/m ³ (Rat) 4 h
Cumene (constituent) 98-82-8	> 3577 ppm (Rat) 6 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Specific test data for the substance or mixture is not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Specific test data for the substance or mixture is not available.
Eye damage/irritation Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).
Irritation Specific test data for the substance or mixture is not available.
Corrosivity Specific test data for the substance or mixture is not available.
Sensitization Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).
Mutagenic Effects Specific test data for the substance or mixture is not available.
Carcinogenic effects Specific test data for the substance or mixture is not available. May cause cancer. (based on components).
Reproductive Effects Specific test data for the substance or mixture is not available.
STOT - single exposure Specific test data for the substance or mixture is not available.
STOT - repeated exposure Specific test data for the substance or mixture is not available. May cause damage to organs through prolonged or repeated exposure. (based on components).
Chronic Toxicity Specific test data for the substance or mixture is not available.
Aspiration hazard Specific test data for the substance or mixture is not available. May be fatal if swallowed and enters airways. (based on components).
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH
Crystalline silica (cristobalite) 14464-46-1	A2

5536 Extender Base

Revision Date Nov-13-2023

Ethyl alcohol 64-17-5	A3
Cumene (constituent) 98-82-8	A3
Quartz, crystalline silica 14808-60-7	A2

Chemical name	IARC
Crystalline silica (cristobalite) 14464-46-1	Group 1
Cumene (constituent) 98-82-8	Group 2B
Quartz, crystalline silica 14808-60-7	Group 1

Chemical name	NTP
Crystalline silica (cristobalite) 14464-46-1	Known
Cumene (constituent) 98-82-8	Reasonably Anticipated
Quartz, crystalline silica 14808-60-7	Known

Chemical name	OSHA
Crystalline silica (cristobalite) 14464-46-1	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X

Numerical measures of toxicity - Product Information

Unknown acute toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	59,952.00 mg/kg
ATEmix (dermal)	17,823.60 mg/kg
ATEmix (inhalation-gas)	99,999.00
ATEmix (inhalation-dust/mist)	18.90 mg/l
ATEmix (inhalation-vapor)	136.60 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Specific test data for the substance or mixture is not available. Harmful to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants
Cumene (constituent) 98-82-8	72h EC50 Pseudokirchneriella subcapitata: = 2.6 mg/L

Chemical name	Fish
Petroleum distillates, hydrotreated light 64742-47-8	96h LC50 Pimephales promelas: = 45 mg/L (flow-through) 96h LC50 Lepomis macrochirus: = 2.2 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 2.4 mg/L (static)
Solvent naphtha, petroleum, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: = 9.22 mg/L
Talc	96h LC50 Brachydanio rerio: > 100 g/L (semi-static)

5536 Extender Base

Revision Date Nov-13-2023

14807-96-6	
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L (flow-through)
Ethylene glycol monopropyl ether 2807-30-9	96h LC50 Pimephales promelas: > 5000 mg/L (static)
Ethyl alcohol 64-17-5	96h LC50 Pimephales promelas: 13400 - 15100 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L (static) 96h LC50 Pimephales promelas: > 100 mg/L (static)
1,3,5-Trimethylbenzene (constituent) 108-67-8	96h LC50 Pimephales promelas: = 3.48 mg/L
Cumene (constituent) 98-82-8	96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: = 4.8 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: = 2.7 mg/L (semi-static) 96h LC50 Poecilia reticulata: = 5.1 mg/L (semi-static)

Chemical name	Crustacea
Solvent naphtha, petroleum, light aromatic 64742-95-6	48h EC50 Daphnia magna: = 6.14 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: = 6.14 mg/L
Ethyl alcohol 64-17-5	48h LC50 Daphnia magna: 9268 - 14221 mg/L 48h EC50 Daphnia magna: = 2 mg/L Static
Cumene (constituent) 98-82-8	48h EC50 Daphnia magna: 7.9 - 14.1 mg/L Static 48h EC50 Daphnia magna: = 0.6 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Partition coefficient
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63
Ethyl alcohol 64-17-5	-0.32
Cumene (constituent) 98-82-8	3.7

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION**Note:**

This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

UN/ID no
Proper Shipping Name

UN1210
Printing Ink

5536 Extender Base

Revision Date Nov-13-2023

Transport hazard class(es) 3
Packing Group II

ICAO / IATA / IMDG / IMO

UN/ID no UN1210
Proper Shipping Name Printing Ink
Transport hazard class(es) 3
Packing Group II

15. REGULATORY INFORMATION**International Inventories**

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
1,2,4-Trimethylbenzene (constituent)	95-63-6	5 - 10	1.0
Ethylene glycol monopropyl ether	2807-30-9	5 - 10	1.0
Cumene (constituent)	98-82-8	0.1 - < 1	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Chemical name	CAS No.	Weight-%
Ethylene glycol monopropyl ether	2807-30-9	5 - 10
Cumene (constituent)	98-82-8	0.1 - < 1
Xylenes (o-, m-, p- isomers)	1330-20-7	0.1 - < 1
Xylenes (o-, m-, p- isomers) (constituent)	1330-20-7	0.1 - < 1
Methanol	67-56-1	0.1 - < 1

US State Regulations

Chemical name	Massachusetts
Calcium carbonate 1317-65-3	X
Talc 14807-96-6	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Crystalline silica (cristobalite) 14464-46-1	X
Ethyl alcohol 64-17-5	X
1,3,5-Trimethylbenzene (constituent) 108-67-8	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Chemical name	Minnesota Right To Know
Calcium carbonate	X

5536 Extender Base

Revision Date Nov-13-2023

1317-65-3	
Talc 14807-96-6	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Crystalline silica (cristobalite) 14464-46-1	X
Ethyl alcohol 64-17-5	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X

Chemical name	New Jersey
Calcium carbonate 1317-65-3	X
Talc 14807-96-6	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Ethylene glycol monopropyl ether 2807-30-9	X
Crystalline silica (cristobalite) 14464-46-1	X
Ethyl alcohol 64-17-5	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X

Chemical name	Pennsylvania
Calcium carbonate 1317-65-3	X
Talc 14807-96-6	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Ethylene glycol monopropyl ether 2807-30-9	X
Crystalline silica (cristobalite) 14464-46-1	X
Ethyl alcohol 64-17-5	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X

California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical name	California Proposition 65
Cumene (constituent)	Carcinogen
Methanol	Developmental

Canada

Chemical name	NPRI - National Pollutant Release Inventory
Petroleum distillates, hydrotreated light 64742-47-8	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements
Solvent naphtha, petroleum, light aromatic 64742-95-6	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements

5536 Extender Base

Revision Date Nov-13-2023

1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
Ethylene glycol monopropyl ether 2807-30-9	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
Ethyl alcohol 64-17-5	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
1,3,5-Trimethylbenzene (constituent) 108-67-8	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements Part 4 Substance - Criteria Air Contaminants
Cumene (constituent) 98-82-8	Part 1, Group A Substance Part 4 Substance - Criteria Air Contaminants

16. OTHER INFORMATION**Key or legend to abbreviations and acronyms used in the safety data sheet****Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA TWA (time-weighted average)
 STEL STEL (Short Term Exposure Limit)
 Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
 A2 - Suspected Human Carcinogen
 A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans
 Group 2A - Probably Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans
 Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen
 Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date

Nov-13-2023

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet