

SAFETY DATA SHEET

Print DateRevision DateRevision NumberMay-30-2015May-30-20151

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code 5515

Product name Cobalt Blue

Product category 5500 Series Flat Poster Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: 1-913-422-1888 Stockport, England SK4 3EG
Tel: 1-800-677-4657 Tel: +44 161 442 2111

Fax: 1-913-422-2294 www.nazdar.com

Emergency telephone number

USA: Chemtrec: 1-800-424-9300 Outside USA: Chemtrec: 1-703-527-3887 24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Aspiration toxicity	Category 1 - (H304)
Flammable liquids	Category 3 - (H226)

Label elements







Signal Word Danger

Hazard Statements

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation H226 - Flammable liquid and vapor

P331 - Do NOT induce vomiting

Page 1/12

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Hazards not otherwise classified (HNOC)

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Component	CAS-No	Weight %	Trade Secret	Note
Stoddard solvent	8052-41-3	10 - 30	*	
Petroleum naphtha, light aromatic	64742-95-6	10 - 30	*	
Talc	14807-96-6	10 - 30	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	5 - 10	*	1
Crystalline silica (cristobalite)	14464-46-1	5 - 10	*	
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	*	
Inert Pigment	Trade Secret	1 - 5	*	
Titanium dioxide	13463-67-7	1 - 5	*	
1,3,5-Trimethylbenzene (constituent)	108-67-8	1 - 5	*	1
Cumene (constituent)	98-82-8	< 1	*	1
Quartz, crystalline silica	14808-60-7	< 0.5	*	
Ethyl benzene (constituent)	100-41-4	< 0.5	*	1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

4. FIRST AID MEASURES

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

InhalationRemove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Page 2/12

Item Numbers: 43212-5182

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from Storage

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Component	ACGIH TLV
Stoddard solvent 8052-41-3	TWA: 100 ppm
Talc 14807-96-6	TWA: 2 mg/m³ (particulate matter)
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.025 mg/m³ (respirable fraction)
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³
Cumene (constituent) 98-82-8	TWA: 50 ppm
Quartz, crystalline silica 14808-60-7	TWA: 0.025 mg/m³ (respirable fraction)
Ethyl benzene (constituent) 100-41-4	TWA: 20 ppm

Component	OSHA PEL
Stoddard solvent	TWA: 100 ppm
8052-41-3	TWA: 525 mg/m ³

Page 3/12

Page 3 of 12 Item Numbers: 43212-5182

5515 - Cobalt Blue

Revision Date May-30-2015

	TWA: 500 ppm TWA: 2900 mg/m³	
ГаІс 14807-96-6	TWA: 2 mg/m³ (respirable dust)	
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m³ (respirable dust)	
Fitanium dioxide 13463-67-7	TWA: 10 mg/m³ (total dust) TWA: 15 mg/m³ (total dust)	
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m³ Skin	
Quartz, crystalline silica 14808-60-7	TWA: 0.1 mg/m³ (respirable dust)	
Ethyl benzene (constituent) 100-41-4	TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³	

Component	Ontario TWAEV
Stoddard solvent 8052-41-3	TWA: 525 mg/m ³
Talc 14807-96-6	TWA: 2 mg/m³ (respirable)
Crystalline silica (cristobalite) 14464-46-1	TWA: 0.05 mg/m³ (respirable)
Ethylene glycol monopropyl ether 2807-30-9	TWA: 25 ppm TWA: 110 mg/m³ Skin
Titanium dioxide 13463-67-7	TWA: 10 mg/m³ (total dust)
Cumene (constituent) 98-82-8	TWA: 50 ppm
Quartz, crystalline silica 14808-60-7	TWA: 0.10 mg/m³ (respirable)
Ethyl benzene (constituent) 100-41-4	TWA: 100 ppm STEL: 125 ppm

Component	Mexico OEL (TWA)
Stoddard solvent	TWA/LMPE-PPT: 100 ppm
8052-41-3	TWA/LMPE-PPT: 523 mg/m ³
	STEL/LMPE-CT: 200 ppm
	STEL/LMPE-CT: 1050 mg/m ³
Talc	TWA/LMPE-PPT: 2 mg/m³ (respirable fraction)
14807-96-6	
Crystalline silica (cristobalite)	TWA/LMPE-PPT: 0.05 mg/m³ (respirable fraction)
14464-46-1	
Titanium dioxide	TWA/LMPE-PPT: 10 mg/m³ (as Ti)
13463-67-7	STEL/LMPE-CT: 20 mg/m³ (as Ti)
Cumene (constituent)	TWA/LMPE-PPT: 50 ppm
98-82-8	TWA/LMPE-PPT: 245 mg/m ³
	STEL/LMPE-CT: 75 ppm
	STEL/LMPE-CT: 365 mg/m ³
Quartz, crystalline silica	TWA/LMPE-PPT: 0.1 mg/m³ (respirable fraction)
14808-60-7	
Ethyl benzene (constituent)	TWA/LMPE-PPT: 100 ppm
100-41-4	TWA/LMPE-PPT: 435 mg/m ³
	STEL/LMPE-CT: 125 ppm
	STEL/LMPE-CT: 545 mg/m ³

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face Protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved **Respiratory Protection**

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid **Appearance** Colored Liquid

Odor Characteristic Odor Threshold No information available

Values Remarks • Method **Property**

No data available pН No data available

Melting point/freezing point > 149 °C / 300 °F **Boiling point/Boiling Range**

Flash Point 29 °C / 85 °F Pensky Martens Closed Cup (PMCC)

Evaporation rate No data available

Flammability Limit in Air Upper flammability limit No data available

Lower flammability limit No data available Vapor Pressure No data available

Vapor Density No data available

Specific Gravity 1.17 Water Solubility No data available

Solubility in other solvents No data available Partition coefficient: n-octanol/water No data available **Autoignition Temperature** No data available **Decomposition temperature** No data available

Kinematic viscosity No data available **Dynamic viscosity** No data available

Explosive Properties No data available **Oxidizing Properties** No data available

Other Information

Photochemically Reactive Yes Weight Per Gallon (lbs/gal) 9.76

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
42.95	58.2	4.2	502.86

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Page 5/12

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

InhalationThere is no data for this product.Eye ContactThere is no data for this product.Skin ContactThere is no data for this product.IngestionThere is no data for this product.

Component	Oral LD50
Petroleum naphtha, light aromatic 64742-95-6	8400 mg/kg(Rat)
1,2,4-Trimethylbenzene (constituent) 95-63-6	3400 mg/kg(Rat)
Ethylene glycol monopropyl ether 2807-30-9	3089 mg/kg(Rat)
Titanium dioxide 13463-67-7	>10000 mg/kg(Rat)
1,3,5-Trimethylbenzene (constituent) 108-67-8	5000 mg/kg(Rat)
Cumene (constituent) 98-82-8	1400 mg/kg(Rat)
Quartz, crystalline silica 14808-60-7	500 mg/kg (Rat)
Ethyl benzene (constituent) 100-41-4	3500 mg/kg(Rat)

Component	LD50 Dermal
Petroleum naphtha, light aromatic 64742-95-6	>2000 mg/kg(Rabbit)
1,2,4-Trimethylbenzene (constituent) 95-63-6	>3160 mg/kg(Rabbit)
Ethylene glycol monopropyl ether 2807-30-9	960 μL/kg(Rabbit)
Cumene (constituent) 98-82-8	>3160 mg/kg(Rabbit)
Ethyl benzene (constituent) 100-41-4	15354 mg/kg (Rabbit)

Component	Inhalation LC50
Petroleum naphtha, light aromatic 64742-95-6	3400 ppm (Rat) 4 h >5.2 mg/L (Rat) 4 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	18 g/m³(Rat)4 h
1,3,5-Trimethylbenzene (constituent) 108-67-8	24 g/m³(Rat) 4 h
Cumene (constituent) 98-82-8	39000 mg/m³(Rat) 4 h
Ethyl benzene (constituent) 100-41-4	17.2 mg/L (Rat)4 h

Item Numbers: 43212-5182 Page 6 of 12

Information on toxicological effects

Symptoms There is no data for this product.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

There is no data for this product. Skin corrosion/irritation Eye damage/irritation There is no data for this product. There is no data for this product. Irritation There is no data for this product. Corrosivity There is no data for this product. Sensitisation **Mutagenic Effects** There is no data for this product. **Reproductive Effects** There is no data for this product. STOT - single exposure STOT - repeated exposure There is no data for this product. There is no data for this product. **Chronic Toxicity** There is no data for this product Aspiration hazard There is no data for this product.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

<u>oaromogement</u>	The table below indicates whether	or each agency has noted any ingredient as a careinegen.
Component		ACGIH
Ethyl benzene (constituent)		A3
100-41-4		

Component	IARC
Crystalline silica (cristobalite) 14464-46-1	Group 1
Titanium dioxide 13463-67-7	Group 2B
Cumene (constituent) 98-82-8	Group 2B
Quartz, crystalline silica 14808-60-7	Group 1
Ethyl benzene (constituent) 100-41-4	Group 2B

Component	NTP
Quartz, crystalline silica 14808-60-7	Known

Component	OSHA
Crystalline silica (cristobalite) 14464-46-1	X
Titanium dioxide 13463-67-7	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	×

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 23,641.00 mg/kg
ATEmix (dermal) 8,081.00 mg/kg
ATEmix (inhalation-dust/mist) 36.80 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Page 7/12

Item Numbers: 43212-5182 Page 7 of 12

Component	Algae/aquatic plants
Cumene (constituent)	72h EC50 Pseudokirchneriella subcapitata: 2.6 mg/L
98-82-8	
Ethyl benzene (constituent)	96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]
100-41-4	72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L
	[static]
	72h EC50 Pseudokirchneriella subcapitata: 4.6 mg/L
	96h EC50 Pseudokirchneriella subcapitata: >438 mg/L

Component	Fish
Petroleum naphtha, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: 9.22 mg/L
Talc 14807-96-6	96h LC50 Brachydanio rerio: >100 g/L [semi-static]
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]
1,3,5-Trimethylbenzene (constituent) 108-67-8	96h LC50 Pimephales promelas: 3.48 mg/L
Cumene (constituent) 98-82-8	96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L [flow-through] 96h LC50 Oncorhynchus mykiss: 2.7 mg/L [semi-static] 96h LC50 Oncorhynchus mykiss: 4.8 mg/L [flow-through] 96h LC50 Poecilia reticulata: 5.1 mg/L [semi-static]
Ethyl benzene (constituent) 100-41-4	96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static] 96h LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through] 96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static] 96h LC50 Lepomis macrochirus: 32 mg/L [static] 96h LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static] 96h LC50 Poecilia reticulata: 9.6 mg/L [static]

Component	Crustacea
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: 6.14 mg/L
1,3,5-Trimethylbenzene (constituent) 108-67-8	24h EC50 Daphnia magna: 50 mg/L
Cumene (constituent) 98-82-8	48h EC50 Daphnia magna: 7.9 - 14.1 mg/L [static] 48h EC50 Daphnia magna: 0.6 mg/L
Ethyl benzene (constituent) 100-41-4	48h EC50 Daphnia magna: 1.8 - 2.4 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Component	Partition coefficient
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63
Cumene (constituent) 98-82-8	3.55
Ethyl benzene (constituent) 100-41-4	3.118

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Page 8/12

Item Numbers: 43212-5182 Page 8 of 12

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1210
Proper Shipping Name Printing Ink

Hazard Class 3
Packing Group

ICAO / IATA / IMDG / IMO

UN/ID no. UN1210
Proper Shipping Name Printing Ink

Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
1,2,4-Trimethylbenzene (constituent)	95-63-6	5 - 10	1.0
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	1.0
Ethyl benzene (constituent)	100-41-4	< 0.5	0.1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

7101		
Component	CAS-No	Weight %
Ethylene glycol monopropyl ether	2807-30-9	1 - 5

U.S. State Regulations

Component	Massachusetts Right To Know
Stoddard solvent 8052-41-3	X
Talc 14807-96-6	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	Х
Crystalline silica (cristobalite) 14464-46-1	X
Titanium dioxide 13463-67-7	X
1,3,5-Trimethylbenzene (constituent) 108-67-8	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

Component	Minnesota Right To Know
Stoddard solvent	X

5515 - Cobalt Blue

Revision Date May-30-2015

8052-41-3	
Talc 14807-96-6	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Crystalline silica (cristobalite) 14464-46-1	X
Titanium dioxide 13463-67-7	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

Component	New Jersey Right To Know
Stoddard solvent 8052-41-3	X
Talc 14807-96-6	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Crystalline silica (cristobalite) 14464-46-1	X
Ethylene glycol monopropyl ether 2807-30-9	X
Titanium dioxide 13463-67-7	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

Component	Pennsylvania Right To Know
Stoddard solvent 8052-41-3	X
Talc 14807-96-6	×
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Crystalline silica (cristobalite) 14464-46-1	X
Ethylene glycol monopropyl ether 2807-30-9	X
Inert Pigment	X
Titanium dioxide 13463-67-7	X
Cumene (constituent) 98-82-8	X
Quartz, crystalline silica 14808-60-7	X
Ethyl benzene (constituent) 100-41-4	X

<u>California Prop. 65</u>
This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65
Titanium dioxide	Carcinogen
Cumene (constituent)	Carcinogen
Quartz, crystalline silica	Carcinogen

Page 10 / 12

> Ethyl benzene (constituent) Carcinogen

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this

Canada

Component	NPRI - National Pollutant Release Inventory
Stoddard solvent 8052-41-3	Part 5, Other Groups and Mixtures
Petroleum naphtha, light aromatic 64742-95-6	Part 5, Other Groups and Mixtures
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethylene glycol monopropyl ether 2807-30-9	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
1,3,5-Trimethylbenzene (constituent) 108-67-8	Part 5, Isomer Groups total of 1,2,3-Trimethylbenzene, CAS No. 526-73-8, and 1,3,5-Trimethylbenzene, CAS No. 108-67-8, except 1,2,4-Trimethylbenzene, CAS No. 95-63-6 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Cumene (constituent) 98-82-8	Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethyl benzene (constituent) 100-41-4	Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999

16. OTHER INFORMATION

HMIS: Health **Flammability** Reactivity **Personal Protection** 3

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen IARC: (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)
Known - Known Carcinogen
Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date May-30-2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

Page 11 of 12 Item Numbers: 43212-5182

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of MSDS

Page 12/12