

# SAFETY DATA SHEET

Issue Date 29-May-2015 Revision Date 19-Aug-2015 Version 2

# 1. IDENTIFICATION

Product identifier

**Product Name AEROTEX WHITE** 

Other means of identification

**Product Code** ATEX1000

ATEX10001, ATEX100003, ATEX100004, ATEX100005, ATEX100007, ATEX100008, ATEX100009, ATEX100010, ATEX100012, ATEX100013, ATEX100014, ATEX100015, ATEX100016, ATEX100017, ATEX100019, ATEX100020, ATEX100021, ATEX100022, Synonyms

ATEX100023, ATEX100033, ATEX100035, ATEX100055

Recommended use of the chemical and restrictions on use

Restricted to professional users. Textile ink. **Recommended Use** 

Uses advised against No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** 

Rutland Group 10021 Rodney Street Pineville, NC 28134 Tel: 704-553-0046

E-mail address product\_safety@rutlandinc.com

Emergency telephone number

**Emergency Telephone** INFOTRAC 1-352-323-3500

Revision Date 19-Aug-2015

# 2. HAZARDS IDENTIFICATION

# Classification

# **OSHA Regulatory Status**

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

# Label elements

# **Emergency Overview**

The product contains no substances which at their given concentration, are considered to be hazardous to health

Appearance viscous Physical state liquid Odor Slight

# Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

Not applicable

Unknown acute toxicity 38.1% of the mixture has not undergone testing for acute toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
TITANIUM DIOXIDE	13463-67-7	10 - 30	*
CALCINED KAOLIN CLAY	66402-68-4	10 - 30	*
SILICON DIOXIDE	7631-86-9	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

# **Description of first aid measures**

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

**Skin contact** Wash skin with soap and water.

**Inhalation** Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

# Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

# Indication of any immediate medical attention and special treatment needed

Page 2/9

Revision Date 19-Aug-2015

# 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

No information available.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

**Environmental precautions** See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place

Store at temperatures not exceeding 35 °C/ 95 °F

Incompatible materials None known based on information supplied.

Revision Date 19-Aug-2015

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7		(vacated) TWA: 10 mg/m <sup>3</sup> total dust	
CALCINED KAOLIN CLAY	STEL: 10 mg/m <sup>3</sup> Zr	TWA: 5 mg/m³ Zr	IDLH: 25 mg/m <sup>3</sup> Zr
66402-68-4	TWA: 5 mg/m <sup>3</sup> Zr TWA: 0.02 mg/m <sup>3</sup>	(vacated) TWA: 5 mg/m³ Zr	TWA: 5 mg/m³ except Zirconium
	Mn	(vacated) STEL: 10 mg/m³ Zr	tetrachloride Zr
	TWA: 0.1 mg/m <sup>3</sup> Mn		STEL: 10 mg/m³ Zr
SILICON DIOXIDE	-	(vacated) TWA: 6 mg/m <sup>3</sup>	-
7631-86-9		TWA: 20 mppcf	
		: (80)/(% SiO2) mg/m <sup>3</sup> TWA	

NIOSH IDLH Immediately Dangerous to Life or Health

Chemical Name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick OEL
TITANIUM DIOXIDE	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
13463-67-7		TWA: 3 mg/m <sup>3</sup>		
CALCINED KAOLIN CLAY	TWA: 5 mg/m <sup>3</sup> TWA: 0.2	TWA: 5 mg/m³ TWA: 0.2	TWA: 5 mg/m <sup>3</sup> TWA: 0.02	-
66402-68-4	mg/m³	mg/m³	mg/m³	
	STEL: 10 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	
		Adverse reproductive effect		
SILICON DIOXIDE	=	TWA: 4 mg/m <sup>3</sup>	=	TWA: 10 mg/m <sup>3</sup>
7631-86-9		TWA: 1.5 mg/m <sup>3</sup>		_

Chemical Name	Newfoundland OEL	Northwest Territories OEL	Nova Scotia OEL	Nunavut OEL
TITANIUM DIOXIDE	TWA: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
13463-67-7		TWA: 10 mg/m <sup>3</sup>	_	TWA: 10 mg/m <sup>3</sup>
CALCINED KAOLIN CLAY	=	-	TWA: 5 mg/m <sup>3</sup> TWA: 0.02	-
66402-68-4			mg/m³	
			TWA: 0.1 mg/m <sup>3</sup>	

Chemical Name	Ontario OEL	Prince Edward Island	Quebec OEL	Saskatchewan OEL	Yukon OEL
		OEL			
TITANIUM DIOXIDE	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	STEL: 20 mg/m <sup>3</sup>
13463-67-7				STEL: 20 mg/m <sup>3</sup>	TWA: 30 mppcf
					TWA: 10 mg/m <sup>3</sup>
CALCINED KAOLIN CLAY	TWA: 5 mg/m <sup>3</sup> TWA:	TWA: 5 mg/m <sup>3</sup> TWA:	TWA: 5 mg/m <sup>3</sup>	-	TWA: 5 mg/m <sup>3</sup>
66402-68-4	0.2 mg/m <sup>3</sup>	0.02 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup>		_
	STEL: 10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>			
SILICON DIOXIDE	TWA: 10 mg/m <sup>3</sup>	-	TWA: 6 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	-
7631-86-9	_			STEL: 20 mg/m <sup>3</sup>	

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Item Numbers: 43221-1017 Page 4 of 9

Revision Date 19-Aug-2015

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state liquid viscous **Appearance** 

Odor Slight Color colored No information available Odor threshold

Remarks • Method **Property** Values

-2 °C / 28 °F Melting point/freezing point

Boiling point / boiling range No information available 100 °C / 212 °F Flash point **Evaporation rate** No information available Flammability (solid, gas) Flammability Limit in Air No information available

Upper flammability limit: No information available Lower flammability limit: No information available Vapor pressure No information available

Vapor density No information available **Specific Gravity** 1.7

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity Dynamic viscosity No information available No information available **Explosive properties Oxidizing properties** No information available

**Other Information** 

Softening point No information available Molecular weight No information available **VOC Content** No information available Density No information available **Bulk density** No information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

# **Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions** 

None under normal processing.

# Conditions to avoid

Extremes of temperature and direct sunlight.

# Incompatible materials

None known based on information supplied.

# **Hazardous Decomposition Products**

None known based on information supplied.

Revision Date 19-Aug-2015

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

**Product Information** No data available Inhalation No data available. Eye contact No data available. No data available. Skin contact

Ingestion No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
TITANIUM DIOXIDE	> 10000 mg/kg (Rat)	-	-
13463-67-7			

# Information on toxicological effects

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available No information available. Germ cell mutagenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

Chemical Name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE 13463-67-7	-	Group 2B	-	X
SILICON DIOXIDE 7631-86-9	-	Group 3	-	-

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

No information available. Reproductive toxicity STOT - single exposure STOT - repeated exposure No information available. No information available. lungs, Respiratory system, Skin. Target Organ Effects Aspiration hazard No information available.

# Numerical measures of toxicity - Product Information

ATEmix (oral) No information available ATEmix (dermal) No information available ATEmix (inhalation-gas) No information available ATEmix (inhalation-dust/mist) No information available ATEmix (inhalation-vapor) No information available

Revision Date 19-Aug-2015

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

39.6% of the mixture consists of components(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

# **Bioaccumulation**

No information available.

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U122

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
FORMALDEHYDE	U122	Included in waste streams:	-	U122
50-00-0		K009, K010, K038, K040,		
		K156, K157		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
CALCINED KAOLIN CLAY 66402-68-4	Toxic

# 14. TRANSPORT INFORMATION

Not regulated DOT <u>TDG</u> Not regulated Not regulated <u>MEX</u> ICAO (air) Not regulated <u>IATA</u> Not regulated <u>IMDG</u> Not regulated Not regulated RID Not regulated ADR <u>ADN</u> Not regulated

Item Numbers: 43221-1017 Page 7 of 9

Revision Date 19-Aug-2015

# 15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Does not comply **EINECS/ELINCS** Does not comply **ENCS** Does not comply **IECSC** Does not comply Does not comply **KECL** Does not comply **PICCS AICS** Does not comply

<u>Legend:</u>
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
CALCINED KAOLIN CLAY - 66402-68-4	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

# CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
CALCINED KAOLIN CLAY 66402-68-4	-	X	-	-

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

# **US State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
FORMALDEHYDE - 50-00-0	Carcinogen

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE 13463-67-7	X	X	X
CALCINED KAOLIN CLAY	X	=	X

Page 8/9

Revision Date 19-Aug-2015

66402-68-4			
PROPYLENE GLYCOL IND. 57-55-6	Х	•	Х
SILICON DIOXIDE 7631-86-9	Х	Х	Х
AMMONIA 7664-41-7	Х	Х	Х
FORMALDEHYDE 50-00-0	Х	Х	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 0 Flammability 1 Instability 0 Physical and Chemical Properties -

HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection B

Issue Date29-May-2015Revision Date19-Aug-2015

**Revision Note** 

(M)SDS sections updated 15

# **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**