

Pioneer Adhesive Products of America Corporation

227 Thorn Ave. • Orchard Park, New York 14127 (716) 662-8100 FAX: (716) 662-6732

email: vinny@pioneeradhesive.com or rob@pioneeradhesive.com

(FSRFNTIAL I	MATERIA Y THE SAME AS	L SAFETY DATA SH	<u>EET</u> OR FO <u>RM OSHA- 20)</u>			
(ESSENTIALLY THE SAME AS U.S. DEPT. OF LABOR FORM OSHA- 20) SECTION !						
CHEMICAL NAMES AND SYNONY	MS: ETHYLEN	IE VINYL ACETATE				
TRADE NAMES AND SYNONYMS	EMULSIO	N				
CHEMICAL FAMILY:	ADHESIV	E				
FORMULA:	RP2585-2	500-2G PH8				
SECTION IL HAZARDOUS INGRE	HENTS					
HAZARDOUS COMPONENTS	OSHA PE	L ACCIH TI	V CAS REG	% OPTIONAL		
(CHEMICAL NAME/ COMMON NAME) THO REPORTABLE QUANTITIES	OF INGREDIENT	S ARE PRESENT***				
"NO toxic chemical(s) subject to the	e reporting require	ements of section 313	of Title III and of CFR 372	are present***		
HMIS HAZARD CODE: HEALTH/ FI	LAMMABILITY/ RE	EACTIVITY/PERSON	AL PROTECTION:			
F-0-0-B						
Substances listed in the Ingredients substance is on the list of potential of	Section are those carcinogens sited i	identified as being pr in OSHA Hazard Com	esent at a concentration of munications Standard.	1 % or greater, or 0.1 % if the		
substance is on the list of potential carcinogens sited in OSHA Hazard Communications Standard.						
SECTION IN PHYSICAL DATA						
BOILING POINT (Deg. F): 21	2 Deg. F		SPECIFIC GRAVITY: (H	201- 1.05-1.15		
VAPOR PRESSURE (mm Ha): OF				<u></u>		
	WATER		PERCENT VOLATILE B	Y VOLUME: APPROX, 40%		
VAPOR DENSITY (Air = 1):	WATER		_			
			_	Y VOLUME: APPROX. 40%		
SOLUBILITY IN WATER: SO	WATER	GHT, SWEET ODOR	_	Y VOLUME: APPROX. 40%		
SOLUBILITY IN WATER: SO	WATER DLUBLE HITE SYRUP; SLI		_	Y VOLUME: APPROX. 40%		
SOLUBILITY IN WATER: SC APPEARANCE AND ODOR: W	WATER DLUBLE HITE SYRUP; SLI		_	Y VOLUME: APPROX. 40%		
SOLUBILITY IN WATER: SO APPEARANCE AND ODOR: WIRE SECTION 1V- FIRE AND EXPLOSE	WATER DLUBLE HITE SYRUP; SLI	TA NONE	_	Y VOLUME: APPROX, 40% WATER = 1); OF WATER		
SOLUBILITY IN WATER: SO APPEARANCE AND ODOR: WISECTION 1V- FIRE AND EXPLOSE FLASH POINT (METHOD USED):	WATER DLUBLE HITE SYRUP; SLI	NONE FOR DRIED ADHE	EVAPORATION RATE	Y VOLUME: APPROX, 40% WATER = 1); OF WATER		
SOLUBILITY IN WATER: SO APPEARANCE AND QUOR: WI SECTION 1V- FIRE AND EXPLOSE FLASH POINT (METHOD USED): EXTINGUISHING MEDIA:	WATER OLUBLE HITE SYRUP; SLI	NONE FOR DRIED ADHE	EVAPORATION RATE	Y VOLUME: APPROX. 40% WATER = 1); OF WATER HEMICAL FOAM		

PAGE 1 OF 3



Pioneer Adhesive Products of America Corporation

227 Thorn Ave. • Orchard Park, New York 14127

(716) 662-8100 FAX: (716) 662-6732

email: vinny@pioneeradhesive.com or rob@pioneeradhesive.com

SECTION		HEAL	YM.	447	A 196\	DATA
SECTION	V -	HEAL	.IH	MAZ	AIG.	WALA

THRESHOLD LIMIT YALUE:

SEE SECTION II

EFFECT OF OVEREXPOSURE:

VOLMITING, SKIN RASH

EYES:

SLIGHT IRRITATION; MAY CAUSE MINOR BURNS OR RASH

SKIN:

SLIGHT IRRITATION; MAY CAUSE MINOR BURNS OR RASH

INHALATION:

ESSENTIALLY NON-IRRITATING

INGESTION:

IRRITATING; MAY CAUSE SLIGHT BURNS AND VOLMITING

EMERGENCY/ FIRST AID PROCEDURES:

EYE8:

RINSE WITH LARGE QUANTITIES OF WATER FOR 20 MINUTES WHILE HOLDING EYELIDS APART.

NEVER INTRODUCE OILS OR OINTMENTS INTO EYES WITHOUT MEDICAL ADVICE.

SKIN:

REMOVE CONTAMINATED CLOTHING. LAUNDER BEFORE REUSE. RINSE AFFECTED AREA FOR

20 MINUTES WITH LARGE QUANTITIES OF WATER.

INHALATION:

INHALATION SHOULD NOT CAUSE PROBLEMS, BUT IF THEY DO OCCUR, REMOVE TO A WELL

VENTED AREA.

INGESTION:

SMALL INGESTED AMOUNTS ARE NOT BELIEVED TO PRODUCE ADVERSE HEALTH EFFECTS.

LARGER AMOUNTS (AT LEAST SEVERAL OUNCES) SHOULD BE REMOVED FROM THE STOMACH BY INDUCING VOLMITING OR ASPIRATION. NO ADVERSE HEALTH EFFECTS ARE ANTICIPATED. CALL

A PHYSICIAN.

PRIMARY ROUTE OF ENTRY: INHALATION? YES SKIN? YES INGESTION? YES CARCINOGENITY: NTP? NO IARC MONOGRAPHS? NO OSHA REG? NO MEDICAL CONDITIONS GENERALLY AGGRAYATED BY EXPOSURE: NONE

	ACTIVITY DATA	 		
STABLITY:	UNSTABLE	STABLE	_X	CONDITIONS TO AVOID: NONE

INCOMPATABILITY (MATERIALS TO AVOID):

DO NOT CONTACT STRONG ACIDS OR OXIDIZER.

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON DIOXIDE AND CARBON MONOXIDE

HAZARDOUS POLYMERIZATION:

MAY OCCUR_____ WILL NOT OCCUR____X_

CONDITIONS TO AVOID: N/A

SECTION VIL SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED: CONTAIN SPILL IN AS SMALL AN AREA AS POSSIBLE. SOAK UP ON NEUTRAL FLOOR ABSORBENT AND SHOVEL INTO A DRUM FOR DISPOSAL.

FOLLOW LOCAL DISPOSAL CODES FOR WASTE DISPOSAL.



Pioneer Adhesive Products of America Corporation

227 Thorn Ave. • Orchard Park, New York 14127

(716) 662-8100 FAX: (716) 662-6732

email: vinny@pioneeradhesive.com or rob@pioneeradhesive.com

SECTION VIII- SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE):

NONE

VENTILATION:

LOCAL EXHAUST: NECESSARY MECHANICAL (GEN.): NECESSARY

SPECIAL: NONE OTHER: NONE

PROTECTIVE GLOVES:

RUBBER OR BUNA-N

EYE PROTECTION:

GOGGLES OR SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT:

NONE

SECTION IX- SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

FOR INDUSTRIAL USE ONLY. STORE IN A COOL, DRY AREA. KEEP CONTAINERS CLOSED. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. CONTAINERS WHEN EMPTIED MAY BE HAZARDOUS. USE CAUTION; DO NOT REUSE.

OTHER PRECAUTIONS:

USE PROPER PERSONAL PROTECTIVE EQUIPMENT

RP2505-2500-2G PHB PAGE 3 OF 3