

MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name: premo! Sculpey® & premo! Sculpey® Accents

Product Use: Oven hardening modeling material for hobby use

Manufacturer:

Polyform Products Company 1901 Estes Avenue Elk Grove Village, IL 60007 USA Phone: 1-847-427-0020

info@polyformproducts.com www.sculpey.com Emergency Telephone Number: 1-847-427-0020

Only available during office hours Monday - Thursday 7 AM - 4 PM CST

Date of Preparation: 09/19/2012

SECTION 2: HAZARD IDENTIFICATION

Emergency Overview

Do not inhale fumes during baking. Overheating oven hardening polymer clays will result in blackening and release of irritating gases including hydrogen chloride vapor.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u> <u>CAS number</u> <u>Weight %</u>

Oven hardening modeling material composed of polyvinyl chloride, plasticizer, fillers and colorants. This material contains no dangerous substances to be declared.

SECTION 4: FIRST AID MEASURES

Eye Contact: Rinse eye thoroughly with plenty of water. If symptoms persist, seek medical attention.

Skin Contact: Wash with soap and water.

Ingestion: Wash out mouth with water. If symptoms persist, seek medical attention.

Inhalation: Seek fresh air after inhalation of fumes in the case of overheating material in oven.

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point: n/a
Autoignition Temperature: n/a

Explosion Limits in Air: Not explosive

Extinguishing Agents:

Hazardous Decomposition Products:

Use water spray jet, foam, carbon dioxide, dry chemical.

In the case of overheating in oven, carbon monoxide, carbon dioxide and noxious hydrochloric acid vapors.

Special Protective Equipment for Fire Fighters: Wear self-contained breathing apparatus with full face

piece and protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: None. In case of overheating material, turn off oven. Ventilate area by

opening nearest window. Seek fresh air, if fumes are inhaled.

Environmental Precautions: Contain spill.

Methods for Cleaning Up: Collect and reuse or dispose with domestic refuse.

SECTION 7: HANDLING AND STORAGE

Do not heat above 175°C (350°F), allow to come in contact with an open flame or use with a hot

knife or wire. Use oven thermometer when hardening material in oven. Do not use microwave oven for baking. Do not overbake. Do not exceed the recommended baking temperature or time.

Wash hands with soap and water after use.

Store unused material in a cool, dry place preferably in a sealed non-reactive container. Storage:

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: No threshold exposure limit values known.

Eye Protection: Skin and Body Protection: n/a **Respiratory Protection:**

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color: Various n/a

Appearance: Solid, malleable Solubility in Water: Not soluble Odor: Characteristic Reactivity in Water: Non-reactive

Boiling Point: n/a Specific Vapor Density (Air=1): n/a Melting Point: n/a Vapor Pressure:

SECTION 10: STABILITY AND REACTIVITY

Product is stable. Polymerization: Not known to occur. Hazardous Decomposition Products: Hydrochloric acid vapors

Materials to Avoid: None

Conditions to Avoid: None when used as intended.

SECTION 11: TOXICOLOGICAL INFORMATION

Effects and Symptoms of Acute Exposure: None expected. Effects and Symptoms of Chronic Exposure: None expected.

Carcinogen Listing

IARC: No OSHA: No NTP: No

SECTION 12: ECOLOGICAL INFORMATION

No harmful effects to the environment are known if material is used as intended and disposed of in the appropriate manner.

SECTION 13: DISPOSAL CONSIDERATIONS

If recycling is not available, dispose with domestic refuse. Observe all federal, state and local regulations.

SECTION 14: TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):
Proper Shipping Name: Not Regulated

SECTION 15: REGULATORY INFORMATION

This material is not classified as hazardous.

This material has been reviewed by a toxicologist in the US and carries the AP seal from the Art & Creative Materials Institute (ACMI). The labeling conforms to US 16 CFR 1500-14 and ASTM D-4236.

SECTION 16: OTHER INFORMATION

n/a: not applicable

5535 JUNGLE

5562 ULTRAMARINE BLUE HUE 5572 CADMIUM YELLOW HUE 5600 FLUORESCENT YELLOW

This MSDS applies to the following colors which are associated with non-hazardous ingredients.

premo! Sculpey® Products **5001 WHITE 5003 DENIM** 5007 SPANISH OLIVE **5010 NAVY BLUE 5020 BLUSH** 5022 WASABI **5026 POMEGRANATE** 5033 ORANGE 5042 BLACK **5053 BURNT UMBER 5063 COBALT BLUE HUE** 5072 ZINC YELLOW HUE **5092 BEIGE** 5093 ECRU **5317 FROST 5323 GREEN** 5382 CADMIUM RED HUE 5383 ALIZARIN CRIMSON HUE 5392 RAW SIENNA 5503 FLUORESCENT PINK 5504 FUCHSIA 5504 TURQUOISE 5513 PURPLE 5523 CANDY PINK 5525 SUNSHINE 5529 RHINO GRAY

5029 MAGENTA PEARL **5031 PURPLE PEARL** 5035 BRIGHT GREEN PEARL 5038 PEACOCK PEARL 5040 TRANSLUCENT BLUE **5044 TRANSLUCENT RED 5046 TRANSLUCENT YELLOW 5048 TRANSLUCENT GREEN 5049 BLUE GLITTER** 5051 RED GLITTER 5055 18K GOLD 5057 FROST WHITE GLITTER **5059 BLUE GRANITE 5061 WHITE GRANITE 5065 GRAY GRANITE** 5067 COPPER **5101 PEARL** 5129 SILVER **5289 BLUE PEARL** 5303 GOLD 5310 TRANSLUCENT 5317 ANTIQUE GOLD 5519 BRONZE 5527 WHITE TRANSLUCENT 5540 TWINKLE TWINKLE 5550 GREEN GLITTER

premo! Sculpey® Accents Products

The MSDS supersedes a previous MSDS dated: 05/11/2009 Prepared by: K. Rush 09/19/2012

The information contained herein is provided in good faith and is subject to change without notice. It is believed to be accurate and represents the best information currently available to us. However, we make no warranty, fitness for a particular purpose or of any other type, expressed or implied, with respect to products described or data or information provided. We assume no liability resulting from the use of such products, data or information. Users should determine the suitability of the information for their particular purpose. The user assumes all risk arising from their use of the material. The user is required to comply with all laws and regulations relating to the purchase, use, storage and disposal of the material and must be familiar with and follow generally accepted safe handling procedures.

Page 3 of 3