00423-1020

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name Mixture CAS No. Mixture

Trade Name GRUMBACHER VARNISH MATTE #533

Product Code 10-5350

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Coating Product - Arts & Crafts

Uses Advised Against None

Company Identification Chartpak, Inc.
One River Road

Leeds, MA 01053 (800) 628-1910

E-Mail (competent person) <u>INFO@CHARTPAK.COM</u>

Emergency telephone number

Emergency Phone No. Transportation Emergency: CHEMTREC 24 hr. 1-800-424-

9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Label elements

Telephone

Hazard Symbol

Flam. Aerosol 1; Liquefied gas; Skin Sens. 1; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; STOT RE 1; Asp. Tox. 1



Signal word(s)

Hazard Statement(s)

Precautionary Statement(s)

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

May cause damage to organs through prolonged or repeated exposure.

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Wash hands and exposed skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Use only outdoors or in a well-ventilated area.

Page: 1/9

Item Numbers: 00423-1020 Page 1 of 9

Avoid contact with skin and eyes. Avoid breathing vapors.

Protect from sunlight and do not expose to temperatures exceeding 50 $^{\circ}\text{C}/122~^{\circ}\text{F}.$

Other hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Acetone	20 - 30	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
VM&P Naphtha (Naphtha (petroleum), hydrotreated light)	20 - 30	64742-49-0	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Butane	10 - 15	106-97-8	Flam. Gas 1; H220 Liquefied gas; H280
Propane	10 - 15	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Turpentine	5 - 10	9005-90-7 / 8006-64-2	Flam. Liq. 2;H225 Acute Tox. 4; H302, H312, H332 Eye Irrit. 2; H319 Skin Irrit. 2; H315 Asp. Tox. 1; H304 Skin Sens. 1;H317 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Stoddard solvent	5 - 10	8052-41-3	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336 STOT RE 1; H372 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Solvent Naptha (Petroleum) Heavy Aromatic ^	< 1	64742-94-5	Flam. Liq. 4; H227 STOT SE 3; H336 Carc. 2; H351 Asp. Tox. 1; H304 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Acrylic polymers	5 - 10	Proprietary	Not classified as dangerous for supply/use.

^{*} The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

Additional Information Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.

^ Contains: Naphthalene (CAS No. 91-20-3); < = 0.7 % (< 0.01% in final formulation)

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Page: 2/9

Item Numbers: 00423-1020 Page 2 of 9

Inhalation Move person to fresh air. If breathing is labored, administer oxygen. If

symptoms develop, obtain medical attention. Get medical advice/attention

if you feel unwell.

Skin Contact Wash affected skin with soap and water. If irritation (redness, rash,

blistering) develops, get medical attention. Take off contaminated clothing

and wash it before reuse.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

Ingestion Do not induce vomiting. Do not give anything by mouth to an unconscious

person. Get immediate medical attention.

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways. Do NOT induce vomiting.

May cause an allergic skin reaction.

Indication of any immediate medical attention and

special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media
-Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.

Do not use water jet.

Special hazards arising from the substance or

mixture

Pressurised container: May burst if heated

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

emergency procedures

Eliminate sources of ignition. Avoid contact with skin and eyes. Avoid

breathing vapors.

Environmental precautions

Prevent liquid entering sewers, basements and work pits. Avoid

release to the environment. Collect spillage.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for

disposal or recovery.

Reference to other sections Additional Information None None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use product in a well-ventilated area only. Avoid contact

with skin and eyes. Avoid breathing vapors.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Store in a well-ventilated place. Protect from sunlight. Do not expose

to temperatures exceeding 50°C/ 122°F.

-Incompatible materials

This product should be stored away from sources of strong heat or

oxidizing chemicals.

Specific end use(s)

Coating Product - Arts & Crafts

Page: 3/9

Item Numbers: 00423-1020 Page 3 of 9

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

		(8hr	(8hr TWA)		(STEL)	
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
Acetone	67-64-1	1000 ppm	250 ppm		500 ppm	
Alkanes (C9-C15)			1200 mg/m3			
Propane	74-98-6	1000 ppm	Aspyx.#			#
n-Butane	106-97-8		250 ppm			
Aliphatic hydrocarbons (Stoddard Solvent)	8052-41-3	500 ppm	100 ppm			
Turpentine	8006-64-2/ 9005-90-7	100 ppm	20 ppm ^(S)			^(S) sensitization

^{*}Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1300 (Ketones I); NIOSH 1551 (Turpentine); NIOSH 1550

(Naphthas)

Exposure controls Appropriate engineering controls

Eye/face protection

Personal protection equipment

Ensure adequate ventilation.

Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely. Check with

protective equipment manufacturer's data.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with

protective equipment manufacturer's data.

Not normally required. Use gloves with insulation for thermal Thermal hazards

protection, when needed.

Environmental Exposure Controls Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Color. Odor

Odor Threshold (ppm)

pH (Value)

Melting Point (°C) / Freezing Point (°C)

Boiling point/boiling range (°C):

Flash Point (°C) **Evaporation Rate** Flammability (solid, gas) **Explosive Limit Ranges**

Aerosol spray

Petroleum spirit / Fuel oil-like

Not available Not available Not available Not available -104 (Propane) Not available Extremely flammable 2.1% - 9.5% v/v (Propane)

Page: 4/9

Page 4 of 9 Item Numbers: 00423-1020

Vapor pressure (Pascal)

Vapor Density (Air=1)

ca. 95 x 10⁴ (Propane)

ca. 1.56 @ 0°C (Propane)

Density (g/ml) Solubility (Water) Solubility (Other)

Partition Coefficient (n-Octanol/water) Auto Ignition Point (°C) Decomposition Temperature (°C)

Kinematic Viscosity Explosive properties Oxidizing properties Other information ca. 1.56 @ 0°C (Propane) Not available Not available Not available Not available

450 (Propane) Not available <20 cSt @ 40°C Not explosive. Not oxidizing. Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoid Avoid contact with heat and ignition sources.

Incompatible materials This product should be stored away from sources of strong heat or

oxidizing chemicals.

Hazardous decomposition product(s) Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Propane (CAS# 74-98-6):

Acute toxicity Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)

Irritation/Corrosivity No evidence of irritant effects from normal handling and use.

Sensitisation It is not a skin sensitiser.

Repeated dose toxicity NOAEC: ≥19678 mg/m3 (28-day, rat, Systemic effects)

LOAEC: 21641 mg/m3 (28-day, rat, effects: Body weight)

Carcinogenicity

No data. It is unlikely to present a carcinogenic hazard to man.

Mutagenicity There is no evidence of mutagenic potential.

Reproductive toxicity None anticipated

Acetone (CAS No. 67-64-1)

Acute toxicity Oral LD50 = 5800 mg/kg (rat)

Dermal LD50 >15800 mg/kg (rabbit)

Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness

and dizziness.

Irritation / Corrosivity Causes serious eye irritation. Repeated exposure may cause skin dryness or

cracking.

Sensitisation It is not a skin sensitiser.

Repeated dose toxicity

Oral NOAEL = 900 mg/kg/day (rat) (90-days)

Inhalation NOAEL ≥ 19,000 ppm (rat)

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

 Mutagenicity
 Negative

 Toxicity for reproduction
 Negative

Page: 5/9

Item Numbers: 00423-1020 Page 5 of 9

Other information None known.

Naphtha (petroleum) hydrotreated light (CAS No. 64742-49-0) - By analogy with similar materials:

Acute toxicity (calculated / estimated) Oral: LD50 >5000 mg/kg-bw

Dermal: LD50 >2000 mg/kg-bw

Inhalation: LC0 ≥7.6 mg/l (Vapor), 4-hr. rat - May cause drowsiness or

dizziness.

Irritation/Corrosivity Causes skin irritation. Repeated exposure may cause skin dryness or

cracking.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity Dermal: NOEAL >2000 mg/kg bw (systemic effects)

Inhalation: NOAEC = 1.4 mg/l (Vapor)

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

 Mutagenicity
 Not to be expected

 Reproductive toxicity
 Not to be expected.

Other information None

Solvent Naptha (Petroleum) Heavy Aromatic (CAS No. 64742-94-5)

Acute toxicity (calculated / estimated) Oral: LD50 >5 g/kg-bw

Dermal: LD50 >2 g/kg-bw

Inhalation: LC50 >20 mg/l (Vapor), 4-hr. rat - May cause drowsiness or

dizziness.

Irritation/Corrosivity Causes serious eye irritation. Causes skin irritation. Repeated exposure may

cause skin dryness or cracking.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity No data

Carcinogenicity Suspected of causing cancer. *Contains: Naphthalene (CAS No. 91-20-3)

*NTP	*IARC	*ACGIH	*OSHA	*NIOSH
Suspected Human	2B	A3	No.	No.

 Mutagenicity
 Not to be expected

 Reproductive toxicity
 Not to be expected

Turpentine (CAS No. 8006-64-2)

Acute toxicity Oral: LD50 =4.6 ml/kg-bw

Dermal: LD50 >2 g/kg-bw

Inhalation: LC50 =13.7 mg/l (Vapor), 4-hr. rat

Irritation/Corrosivity Causes serious eye irritation. Causes skin irritation. Repeated exposure may

cause skin dryness or cracking.

 Sensitization
 May cause sensitization by skin contact.

 Repeated dose toxicity
 Inhalation: NOAEL = 50 ppm (Vapor)

Carcinogenicity No evidence of carcinogenicity.

NTP	*IARC	*ACGIH	*OSHA	*NIOSH
No.	No.	No.	No.	No.

Mutagenicity There is evidence of mutagenic potential.

Reproductive toxicity Not to be expected

Page: 6/9

Item Numbers: 00423-1020 Page 6 of 9

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Naphtha (petroleum) hydrotreated light (CAS No. 64742-49-0) - By analogy with similar materials:

Long Term NOELR (21 days): 2.6 mg/L (crustacea; reproduction)

NOELR (72 hour): 0.5 mg/L (algae; growth rate)

Stoddard solvent (CAS# 8052-41-3) - By analogy with similar materials:

Short term LL50 (96 hour): 8.2 mg/L (Pimephales promelas)

EL50 (48 hour): 4.5 mg/l (Daphnia magna)

EL50 (72 hour): 3.1 mg/l (Pseudokirchnerella subcapitata)

Long Term EL50 (21 days): 10 mg/l (Daphnia magna)

EL50 (72 hour): 3.1 mg/l (Pseudokirchnerella subcapitata)

Persistence and degradability Biodegradable

Bioaccumulative potential The product has no potential for bioaccumulation.

Mobility in soil Not available.

Results of PBT and vPvB assessment Not classified as PBT or vPvB.

Other adverse effects None known.

Solvent Naptha (Petroleum) Heavy Aromatic (CAS No. 64742-94-5)

Short term LC50 (96 hour): 3 mg/L (Oncorhynchus mykiss)

EL50 (48 hour): 1.1 mg/L (Daphnia magna)

Long Term No data

Persistence and degradability

Part of the components are poorly biodegradable.

Bioaccumulative potential

The product has no potential for bioaccumulation.

Mobility in soil Not available.

Results of PBT and vPvB assessment Not classified as PBT or vPvB.

Other adverse effects None known.

Turpentine (CAS No. 8006-64-2)

Short term LC50 (96 hour): 29 mg/L (Zebrafish)
EL50 (48 hour): 6.4 mg/L (Daphnia magna)

EL50 (72 hour): 17.1 mg/L (Desmodesmus subspicatus)

Long Term No data

Persistence and degradability Readily biodegradable.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Results of PBT and vPvB assessment Not classified as PBT or vPvB.

Other adverse effects None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Disposal should be in accordance with local, state or national

legislation. Consult an accredited waste disposal contractor or the

local authority for advice.

SECTION 14: TRANSPORT INFORMATION

U.S. DOT
Sea transport
(IMDG)
(ICAO/IATA)

UN number195019501950Proper Shipping NameAerosols, flammableAerosols, flammableAerosols, flammable

Page: 7/9

Item Numbers: 00423-1020 Page 7 of 9

Transport hazard class(es) 2.1 2.1 Packing group Not applicable Not applicable Not applicable **Environmental hazards** None assigned None assigned None assigned Special precautions for user None assigned None assigned None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable Product may ship by ORM-D, LTD. QTY., CONSUMER COMMODITY, CLASS 9

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	5 - 10	5000

SARA 311/312 - Hazard Categories:

☐ Reactivity □ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

<u> </u>		
Chemical Name	CAS No.	Typical %wt.
None		

SARA 302 - Extremely Hazardous Substances (40 CFR 355):

	•	,	
Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
Ethylbenzene *	100-41-4	Cancer
Benzene *	71-43-2	Cancer/ Reproductive
Toluene *	108-88-3	Developmental
Naphthalene *	91-20-3	Reproductive
Cumene*	98-82-8	Cancer
Acetaldehyde*	75-07-0	Cancer

^{*} Trace

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: October 14,2016

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapour.
- H226: Flammable liquid and vapour.
- H280: Contains gas under pressure; may explode if heated.
- H302: Harmful if swallowed.H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation
- H332: Harmful if inhaled..
- H336: May cause drowsiness or dizziness
- H351: Suspected of causing cancer.
- H372: Causes damage to organs through prolonged or repeated exposure.
- H401: Toxic to aquatic life.
- H411: Toxic to aquatic life with long lasting effects.

Page: 8/9

Page 8 of 9 Item Numbers: 00423-1020

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Page: 9/9

Item Numbers: 00423-1020 Page 9 of 9