

Article No.: 111XXXXXX GEORGIAN OIL COLOURS
 Print date 16.09.2016 Revision date 16.09.2016 EN
 Version 1.0 Issue date 19.07.2016 Page 1 / 6

1. Identification of the substance/mixture and of the company/undertaking

- 1.1. **Product identifiers**
 Article No. (manufacturer/supplier): 111XXXXXX
 Identification of the substance or mixture: GEORGIAN OIL COLOURS (NON WHITE COLOURS)
- 1.2. **Relevant identified uses of the substance or mixture and uses advised against**
Relevant identified uses:
 Artists supply and hobby preparations
 Coatings and paints, thinners, paint removers
- 1.3. **Details of the supplier of the safety data sheet**
Supplier (manufacturer/importer/downstream user/distributor):
 Daler-Rowney Ltd
 Peacock Lane Telephone: +44 (0) 1344 461083
 Bracknell, RG12 8SS Telefax: +44 (0) 1344 486511
 ENGLAND
Dept. responsible for information:
 E-mail Philip.Gray@daler-rowney.com
- 1.4. **Emergency telephone number**
 Emergency telephone: +44 (0) 1344 461000

2. Hazards identification

- 2.1. **Classification of the substance or mixture**
Classification according to Regulation (EC) No. 1272/2008 [CLP]
 This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].
- 2.2. **Label elements**
 The product is classified and labelled according to EC directives or corresponding national laws.
Labelling according to Regulation (EC) No. 1272/2008 [CLP]
Hazard pictograms
Hazard statements
 n.a.
Precautionary statements
 P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
contains:
 n.a.
Supplemental Hazard information (EU)
 n.a.
- 2.3. **Other hazards**
 Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

3. Composition / Information on ingredients

3.2. **Mixtures**
Product description / chemical characterization
Description oil paint
Hazardous ingredients
Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No.	REACH No.	Wt %
CAS No.	Chemical name	Remark
INDEX No.	classification:	

Article No.: 111XXXXXX GEORGIAN OIL COLOURS
Print date 16.09.2016 Revision date 16.09.2016
Version 1.0 Issue date 19.07.2016

EN
Page 2 / 6

n.a.

Additional information

Full text of classification: see section 16

4. First-aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Vapours form explosive mixtures with air.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Vapours form explosive mixtures with air.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13).

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

7. Handling and storage

7.1. Precautions for safe handling

Item Numbers: 00485-1025, 00485-2023, 00485-2024, 00485-2025, 00485-2253, 00485-2254, 00485-2255, 00485-2563, 00485-2564, 00485-2565, 00485-3009, 00485-3063, 00485-3064, 00485-3065, 00485-3083, 00485-3084, 00485-3085, 00485-3093, 00485-3094, 00485-3095, 00485-3133, 00485-3134, 00485-3135, 00485-3203, 00485-3204, 00485-3205, 00485-3223, 00485-3224, 00485-3225, 00485-3253, 00485-3254, 00485-3255, 00485-3283, 00485-3284, 00485-3285, 00485-3333, 00485-3334, 00485-3335, 00485-3493, 00485-3494, 00485-3495, 00485-3503, 00485-3504, 00485-3505, 00485-3703, 00485-3725, 00485-3733, 00485-3734, 00485-3735, 00485-3843, 00485-3844, 00485-3845, 00485-4009, 00485-4043, 00485-4044, 00485-4045, 00485-4063, 00485-4064, 00485-4065, 00485-4123, 00485-4124, 00485-4125, 00485-4143, 00485-4144, 00485-4145, 00485-4153, 00485-4154, 00485-4155, 00485-4163, 00485-4203, 00485-4204, 00485-4205, 00485-4303, 00485-4304, 00485-4305, 00485-4533, 00485-4534, 00485-4535, 00485-4673, 00485-4674, 00485-4675, 00485-4753, 00485-4754, 00485-4755, 00485-5013, 00485-5014, 00485-5015, 00485-5023, 00485-5025, 00485-5163, 00485-5164, 00485-5165, 00485-5183, 00485-5184, 00485-5185, 00485-5223, 00485-5224, 00485-5225, 00485-5233, 00485-5234, 00485-5235, 00485-5783, 00485-5784, 00485-5785, 00485-5863, 00485-5865, 00485-6523, 00485-6524, 00485-6525, 00485-6683, 00485-6685, 00485-7053, 00485-7054, 00485-7055, 00485-7093, 00485-7094, 00485-7095, 00485-7103, 00485-7104, 00485-7105, 00485-7123, 00485-7124, 00485-7125, 00485-7133, 00485-7134, 00485-7135, 00485-7313, 00485-7314, 00485-7315, 00485-7803, 00485-7804, 00485-7805, 00485-8043, 00485-8044, 00485-8045, 00485-8053, 00485-8054, 00485-8055, 00485-8063, 00485-8064, 00485-8065, 00485-8073, 00485-8074, 00485-8075, 00485-8313, 00485-8314, 00485-8315, 00485-8623, 00485-8624, 00485-8625

Article No.:	111XXXXXX	GEORGIAN OIL COLOURS	EN
Print date	16.09.2016	Revision date 16.09.2016	Page 3 / 6
Version	1.0	Issue date 19.07.2016	

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSivO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

8. Exposure controls / Personal protection

8.1. Control parameters

Occupational exposure limit values:

n.a.

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

Article No.: 111XXXXXX GEORGIAN OIL COLOURS EN
 Print date 16.09.2016 Revision date 16.09.2016 Page 4 / 6
 Version 1.0 Issue date 19.07.2016

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: liquid
Physical state liquid
Colour refer to label
Odour characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	> 100 °C	DIN 53213	
Ignition temperature in °C:	300 °C		
Lower explosion limit	n.a.		
Upper explosion limit	n.a.		
Vapour pressure at 20 °C:	0,60 mbar		
Density at 20 °C:	1,00 g/cm³		
Water solubility (g/L)	insoluble		
pH at 20 °C:	-		
Viscosity at 20 °C	> 50 mPa·s		
Solvent separation test (%)	< 3 %		
boiling point in °C at 101,3 kPa	185 °C		

9.2. Other information:

10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. Vapours form explosive mixtures with air.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

11. Toxicological information

Classification according to Regulation (EC) No. 1272/2008 [CLP]
 No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Toxicological data are not available.

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are:

Article No.: 111XXXXXX GEORGIAN OIL COLOURS
 Print date 16.09.2016 Revision date 16.09.2016
 Version 1.0 Issue date 19.07.2016

EN
 Page 5 / 6

headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

12. Ecological information

overall evaluation

Classification according to Regulation (EC) No. 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 080111

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. Send to a collecting point for used paints.

14. Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

n.a.

14.2. UN proper shipping name

14.3. Transport hazard class(es)

n.a.

14.4. Packing group

n.a.

14.5. Environmental hazards

Land transport (ADR/RID)

n.a.

Marine pollutant

n.a.

14.6. Special precautions for user

Item Numbers: 00485-1025, 00485-2023, 00485-2024, 00485-2025, 00485-2253, 00485-2254, 00485-2255, 00485-2563, 00485-2564, 00485-2565, 00485-3009, 00485-3063, 00485-3064, 00485-3065, 00485-3083, 00485-3084, 00485-3085, 00485-3093, 00485-3094, 00485-3095, 00485-3133, 00485-3134, 00485-3135, 00485-3203, 00485-3204, 00485-3205, 00485-3223, 00485-3224, 00485-3225, 00485-3253, 00485-3254, 00485-3255, 00485-3283, 00485-3284, 00485-3285, 00485-3333, 00485-3334, 00485-3335, 00485-3493, 00485-3494, 00485-3495, 00485-3503, 00485-3504, 00485-3505, 00485-3703, 00485-3725, 00485-3733, 00485-3734, 00485-3735, 00485-3843, 00485-3844, 00485-3845, 00485-4009, 00485-4043, 00485-4044, 00485-4045, 00485-4063, 00485-4064, 00485-4065, 00485-4123, 00485-4124, 00485-4125, 00485-4143, 00485-4144, 00485-4145, 00485-4153, 00485-4154, 00485-4155, 00485-4163, 00485-4203, 00485-4204, 00485-4205, 00485-4303, 00485-4304, 00485-4305, 00485-4533, 00485-4534, 00485-4535, 00485-4673, 00485-4674, 00485-4675, 00485-4753, 00485-4754, 00485-4755, 00485-5013, 00485-5014, 00485-5015, 00485-5023, 00485-5025, 00485-5163, 00485-5164, 00485-5165, 00485-5183, 00485-5184, 00485-5185, 00485-5223, 00485-5224, 00485-5225, 00485-5233, 00485-5234, 00485-5235, 00485-5783, 00485-5784, 00485-5785, 00485-5863, 00485-5865, 00485-6523, 00485-6524, 00485-6525, 00485-6683, 00485-6685, 00485-7053, 00485-7054, 00485-7055, 00485-7093, 00485-7094, 00485-7095, 00485-7103, 00485-7104, 00485-7105, 00485-7123, 00485-7124, 00485-7125, 00485-7133, 00485-7134, 00485-7135, 00485-7313, 00485-7314, 00485-7315, 00485-7316, 00485-7317, 00485-7318, 00485-7319, 00485-7320, 00485-7321, 00485-7322, 00485-7323, 00485-7324, 00485-7325, 00485-7326, 00485-7327, 00485-7328, 00485-7329, 00485-7330, 00485-7331, 00485-7332, 00485-7333, 00485-7334, 00485-7335, 00485-7336, 00485-7337, 00485-7338, 00485-7339, 00485-7340, 00485-7341, 00485-7342, 00485-7343, 00485-7344, 00485-7345, 00485-7346, 00485-7347, 00485-7348, 00485-7349, 00485-7350, 00485-7351, 00485-7352, 00485-7353, 00485-7354, 00485-7355, 00485-7356, 00485-7357, 00485-7358, 00485-7359, 00485-7360, 00485-7361, 00485-7362, 00485-7363, 00485-7364, 00485-7365, 00485-7366, 00485-7367, 00485-7368, 00485-7369, 00485-7370, 00485-7371, 00485-7372, 00485-7373, 00485-7374, 00485-7375, 00485-7376, 00485-7377, 00485-7378, 00485-7379, 00485-7380, 00485-7381, 00485-7382, 00485-7383, 00485-7384, 00485-7385, 00485-7386, 00485-7387, 00485-7388, 00485-7389, 00485-7390, 00485-7391, 00485-7392, 00485-7393, 00485-7394, 00485-7395, 00485-7396, 00485-7397, 00485-7398, 00485-7399, 00485-7400, 00485-7401, 00485-7402, 00485-7403, 00485-7404, 00485-7405, 00485-7406, 00485-7407, 00485-7408, 00485-7409, 00485-7410, 00485-7411, 00485-7412, 00485-7413, 00485-7414, 00485-7415, 00485-7416, 00485-7417, 00485-7418, 00485-7419, 00485-7420, 00485-7421, 00485-7422, 00485-7423, 00485-7424, 00485-7425, 00485-7426, 00485-7427, 00485-7428, 00485-7429, 00485-7430, 00485-7431, 00485-7432, 00485-7433, 00485-7434, 00485-7435, 00485-7436, 00485-7437, 00485-7438, 00485-7439, 00485-7440, 00485-7441, 00485-7442, 00485-7443, 00485-7444, 00485-7445, 00485-7446, 00485-7447, 00485-7448, 00485-7449, 00485-7450, 00485-7451, 00485-7452, 00485-7453, 00485-7454, 00485-7455, 00485-7456, 00485-7457, 00485-7458, 00485-7459, 00485-7460, 00485-7461, 00485-7462, 00485-7463, 00485-7464, 00485-7465, 00485-7466, 00485-7467, 00485-7468, 00485-7469, 00485-7470, 00485-7471, 00485-7472, 00485-7473, 00485-7474, 00485-7475, 00485-7476, 00485-7477, 00485-7478, 00485-7479, 00485-7480, 00485-7481, 00485-7482, 00485-7483, 00485-7484, 00485-7485, 00485-7486, 00485-7487, 00485-7488, 00485-7489, 00485-7490, 00485-7491, 00485-7492, 00485-7493, 00485-7494, 00485-7495, 00485-7496, 00485-7497, 00485-7498, 00485-7499, 00485-7500, 00485-7501, 00485-7502, 00485-7503, 00485-7504, 00485-7505, 00485-7506, 00485-7507, 00485-7508, 00485-7509, 00485-7510, 00485-7511, 00485-7512, 00485-7513, 00485-7514, 00485-7515, 00485-7516, 00485-7517, 00485-7518, 00485-7519, 00485-7520, 00485-7521, 00485-7522, 00485-7523, 00485-7524, 00485-7525, 00485-7526, 00485-7527, 00485-7528, 00485-7529, 00485-7530, 00485-7531, 00485-7532, 00485-7533, 00485-7534, 00485-7535, 00485-7536, 00485-7537, 00485-7538, 00485-7539, 00485-7540, 00485-7541, 00485-7542, 00485-7543, 00485-7544, 00485-7545, 00485-7546, 00485-7547, 00485-7548, 00485-7549, 00485-7550, 00485-7551, 00485-7552, 00485-7553, 00485-7554, 00485-7555, 00485-7556, 00485-7557, 00485-7558, 00485-7559, 00485-7560, 00485-7561, 00485-7562, 00485-7563, 00485-7564, 00485-7565, 00485-7566, 00485-7567, 00485-7568, 00485-7569, 00485-7570, 00485-7571, 00485-7572, 00485-7573, 00485-7574, 00485-7575, 00485-7576, 00485-7577, 00485-7578, 00485-7579, 00485-7580, 00485-7581, 00485-7582, 00485-7583, 00485-7584, 00485-7585, 00485-7586, 00485-7587, 00485-7588, 00485-7589, 00485-7590, 00485-7591, 00485-7592, 00485-7593, 00485-7594, 00485-7595, 00485-7596, 00485-7597, 00485-7598, 00485-7599, 00485-7600, 00485-7601, 00485-7602, 00485-7603, 00485-7604, 00485-7605, 00485-7606, 00485-7607, 00485-7608, 00485-7609, 00485-7610, 00485-7611, 00485-7612, 00485-7613, 00485-7614, 00485-7615, 00485-7616, 00485-7617, 00485-7618, 00485-7619, 00485-7620, 00485-7621, 00485-7622, 00485-7623, 00485-7624, 00485-7625

