SAFETY DATA SHEET

LIQUITEX ARTISTS' ACRYLIC SOFT BODY LIQUITEX ARTISTS' ACRYLIC SOFT BODY

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification	
Product identifier	
Product name	LIQUITEX ARTISTS' ACRYLIC SOFT BODY LIQUITEX ARTISTS' ACRYLIC SOFT BODY
Recommended use of the che	emical and restrictions on use
Application	Fine Art Painting
Details of the supplier of the s	afety data sheet
Supplier	ColArt Americas Inc. 11 Constitution Avenue Piscataway New Jersey 08855 - 1396 USA 1-732-562-0770 R.Enquiries@colart.co.uk
Contact Person	Regulatory Manager
Manufacturer	
Emergency telephone numbe	<u>r</u>
Emergency telephone	For health information only call 1-800-628-3385 Piscataway NJ 08855.
2. Hazard(s) identification	
Classification of the substance	e or mixture
Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Not Classified
Label elements	
Hazard statements	NC Not Classified
3. Composition/information or	ningredients
Mixtures	
Polyethylene glycol octylphe CAS number: 9036-19-5	nyl ether 1-5%
Classification Aquatic Chronic 3 - H412	
The Full Text for all Hazard S	tatements are Displayed in Section 16.
Composition comments	-
4. First-aid measures	
Description of first aid measu	Tes
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.

1/5 them Numbers: 00616-3112, 00616-3184, 00616-3185, 00616-3223, 00616-3553, 00616-3555, 00616-4132, 00616-4132, 00616-4132, 00616-4192, 00616-4192, 00616-4192, 00616-4363, 00616-4365, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542,

Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.	
Skin Contact	Remove affected person from source of contamination. Get medical attention if irritation persists after washing.	
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.	
Most important symptoms and effects, both acute and delayed		
Inhalation	No specific symptoms known.	
Ingestion	No specific symptoms known.	
Skin contact	No specific symptoms known.	
Eye contact	May cause temporary eye irritation.	
5.Fire-fighting measures		
Extinguishing media		
Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.	
Advice for firefighters		
Protective actions during firefighting	No specific firefighting precautions known.	
6. Accidental release measure)S	
Environmental precautions		
Environmental precautions	Avoid discharge into drains or watercourses or onto the ground.	
Methods and material for containment and cleaning up		
Methods and material for cont	annient and ocaning up	
Methods for cleaning up	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.	
	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering	
Methods for cleaning up	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering	
Methods for cleaning up 7. Handling and storage	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering	
Methods for cleaning up 7. Handling and storage Precautions for safe handling	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.	
Methods for cleaning up 7. Handling and storage Precautions for safe handling Usage precautions	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.	
Methods for cleaning up 7. Handling and storage Precautions for safe handling Usage precautions Conditions for safe storage, in	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid spilling. Avoid contact with skin and eyes. Avoid spilling any incompatibilities Keep only in the original container. Store at moderate temperatures in dry, well ventilated	
Methods for cleaning up 7. Handling and storage Precautions for safe handling Usage precautions Conditions for safe storage, in Storage precautions	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid spilling. Avoid contact with skin and eyes. Avoid spilling any incompatibilities Keep only in the original container. Store at moderate temperatures in dry, well ventilated	
Methods for cleaning up 7. Handling and storage Precautions for safe handling Usage precautions Conditions for safe storage, in Storage precautions Specific end uses(s)	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid spilling. Avoid contact with skin and eyes. Including any incompatibilities Keep only in the original container. Store at moderate temperatures in dry, well ventilated area. The identified uses for this product are detailed in Section 1.2.	
Methods for cleaning up 7. Handling and storage Precautions for safe handling Usage precautions Conditions for safe storage, in Storage precautions Specific end uses(s) Specific end use(s)	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid spilling. Avoid contact with skin and eyes. Including any incompatibilities Keep only in the original container. Store at moderate temperatures in dry, well ventilated area. The identified uses for this product are detailed in Section 1.2.	

Item Numbers: 00616-3112, 00616-3184, 00616-3185, 00616-3223, 00616-3555, 00616-4132, 00616-4132, 00616-4132, 00616-4192, 00616-4192, 00616-4192, 00616-4282, 00616-4365, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 0061

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	No specific hand protection noted.
Other skin and body protection	No specific recommendations
Hygiene measures	Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9. Physical and Chemical Properties

Information on basic physical and chemical properties	
Appearance	Paste
Color	Various colors.
Odor	Characteristic.
рН	pH (concentrated solution): 9-10
Initial boiling point and range	> 100°C @ 760 mm Hg
Vapour density	> 1
Relative density	1.2 - 1.5 @ 20°C
Solubility(ies)	Miscible with water
Other information	Not available.
10. Stability and reactivity	
Stability	Stable at normal ambient temperatures.
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid freezing.
Hazardous decomposition products	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).
11. Toxicological information	
Information on toxicological ef	fects
<u>Acute toxicity - dermal</u> Notes (dermal LD∞)	Not determined.
Acute toxicity - inhalation Notes (inhalation LC ₅₀)	Not determined.
General information	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Ingestion	May cause discomfort if swallowed.
Skin Contact	Slightly irritating.
Eye contact	Irritating to eyes.

Item Numbers: 00616-3112, 00616-3184, 00616-3185, 00616-3223, 00616-3555, 00616-3555, 00616-4132, 00616-4132, 00616-4132, 00616-4192, 00616-4197, 00616-4282, 00616-4365, 00616-4365, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 0061

Acute and chronic health hazards	No specific health hazards known.
Route of entry	Inhalation Skin and/or eye contact.
Medical Symptoms	Irritation of eyes and mucous membranes.
12. Ecological Information	
Ecotoxicity	Not regarded as dangerous for the environment.
Toxicity	
Acute toxicity - fish	Not determined.
Acute toxicity - aquatic invertebrates	Not determined.
Acute toxicity - aquatic plants	Not determined.
Acute toxicity - microorganisms	Not determined.
Persistance and degradability	
Persistence and degradability	The degradability of the product is not known.
Mobility in soil	
Adsorption/desorption coefficient	Not determined.
13. Disposal considerations	
Waste treatment methods	
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
14. Transport information	
General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DoT).
UN Number	
Not relevant.	
UN proper shipping name	
Not relevant.	
Transport hazard class(es)	
Not relevant.	
Packing group	
Not relevant.	
Environmental hazards	
Environmentally Hazardous Su	ubstance
Environmentally Hazardous Si No.	ubstance
-	ubstance

Item Numbers: 00616-3112, 00616-3184, 00616-3185, 00616-3223, 00616-3553, 00616-3555, 00616-4132, 00616-4132, 00616-4132, 00616-4192, 00616-4197, 00616-4282, 00616-4365, 00616-4365, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 0061

Not relevant.

 hazards in accordance with the Labelling of Hazardous Art Materials Regulation and Federal Regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act. This product conform to ASTM D-4236 Standard Practice for Labelling Art Materials for Chronic Adverse health effects. The below applies to all colors except the Cadmium Colors. This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the AP (Approved Product) Seal, meaning this product bears no chronic or acute human health hazards. Cadmium Yellow Medium has been certified by ACMI (Artists Craft Material Institute, Inc.) 	Pogulatory Status	All Colors have been evaluated by a taxicologist and labelled for equite and shrenis beath
 Regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act. This product conform to ASTM D-4236 Standard Practice for Labelling Art Materials for Chronic Adverse health effects. The below applies to all colors except the Cadmium Colors. This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the AP (Approved Product) Seal, meaning this product bears no chronic or acute human health hazards. Cadmium Yellow Medium has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe us instructions should be observed. WARNING:EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS. Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385 	Regulatory Status	, .
to ASTM D-4236 Standard Practice for Labelling Art Materials for Chronic Adverse health effects. The below applies to all colors except the Cadmium Colors. This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the AP (Approved Product) Seal, meaning this product bears no chronic or acute human health hazards. Cadmium Yellow Medium has been certified by ACMI (Artists Craft Material Institute Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe us instructions should be observed. WARNING:EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS. Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385		
effects. The below applies to all colors except the Cadmium Colors. This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the AP (Approved Product) Seal, meaning this product bears no chronic or acute human health hazards. Cadmium Yellow Medium has been certified by ACMI (Artists Craft Material Institute Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe us instructions should be observed. WARNING:EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS. Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385		
 (Approved Product) Seal, meaning this product bears no chronic or acute human health hazards. Cadmium Yellow Medium has been certified by ACMI (Artists Craft Material Institute Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe us instructions should be observed. WARNING:EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS. Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385 		•
 hazards. Cadmium Yellow Medium has been certified by ACMI (Artists Craft Material Institute Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe us instructions should be observed. WARNING:EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS. Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385 		This product has been certified by ACMI (Artists Craft Material Institute, Inc.) to carry the AP
Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe us instructions should be observed. WARNING:EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS. Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385		(Approved Product) Seal, meaning this product bears no chronic or acute human health
instructions should be observed. WARNING:EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS. Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385		hazards. Cadmium Yellow Medium has been certified by ACMI (Artists Craft Material Institute,
WARNING:EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS. Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385		Inc.) to carry the CL (Cautionary Labelling) Seal, meaning the following warnings and safe use
Contains: CADMIUM PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385		instructions should be observed.
PRECAUTIONS:AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not for use by children. For further health information contact a poison control center or call 1-800-628-3385		WARNING: EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS.
for use by children. For further health information contact a poison control center or call 1-800-628-3385		Contains: CADMIUM
For further health information contact a poison control center or call 1-800-628-3385		PRECAUTIONS: AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. Not
		for use by children.
Piscataway NJ 08855.		·
		Piscataway NJ 08855.

California Proposition 65 Carcinogens and Reproductive Toxins

Applies to Cadmium Orange, Cadmium Yellow medium, Cadmium Yellow Light, Cadmium Red Medium and Cadmium Red Light only. WARNING: DO NOT SPRAY APPLY -- This product contains cadmium, a chemical known to the State of California to cause cancer by means of inhalation.

16. Other information	
Revision date	7/24/2015
Revision	9
Supersedes date	7/13/2015
Hazard statements in full	H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Item Numbers: 00616-3112, 00616-3184, 00616-3185, 00616-3223, 00616-3553, 00616-3555, 00616-4132, 00616-4132, 00616-4135, 00616-4192, 00616-4197, 00616-4282, 00616-4365, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 00616-4542, 0061