according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Lascaux Studio Bronze Original Aluminium (995)

Revision date : 03.09.2019 **Version (Revision) :** 6.0.1 (6.0.0)

Print date : 03.09.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Lascaux Studio Bronze Original Aluminium (995)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Artists' Acrylic Colour

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier : Lascaux Colours & Restauro, Barbara Diethelm AG

Street: Zürichstrasse 42

Postal code/city: CH-8306 Brüttisellen
Telephone: +41 44 807 41 41

Telefax: +41 44 807 41 40

Information contact: info@lascaux.ch

European address : Lascaux Colours & Restauro Europe GmbH

 Street :
 Turmstrasse 11

 Postal code/city :
 D-78467
 Konstanz

 Telephone :
 +49 7531
 911 3996

 Telefax :
 +49 7531
 911 3997

 Information contact :
 info@lascaux.de

1.4 Emergency telephone number

Tox Info Suisse, 24-h-emergency number 145, Tel. +41 44 251 51 51

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE; REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1).May produce an allergic

reaction.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY; EC No.: 265-150-3; CAS No.: 64742-48-9

Weight fraction : $\geq 1 - < 5 \%$ Classification 1272/2008 [CLP] : Asp. Tox. 1; H304

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.

Page: 1 / 6

(EN / CH)

Item Numbers: 00665-1000 Page 1 of 16

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Lascaux Studio Bronze Original Aluminium (995)

Revision date : 03.09.2019 **Version (Revision) :** 6.0.1 (6.0.0)

Print date : 03.09.2019

: 55965-84-9

Weight fraction : \geq 0,0005 - < 0,001 %

Classification 1272/2008 [CLP]: Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1;

1410

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Following inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

In case of skin contact

Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray.

Unsuitable extinguishing media

Waterjet.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

Appropriate breathing apparatus may be required.

5.4 Additional information

Do not allow the quenching water into the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources and provide for good ventilation. Refer to protective measures listed in sections 7 and 8.

Page: 2/6

(EN / CH)

Item Numbers: 00665-1000 Page 2 of 6

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Lascaux Studio Bronze Original Aluminium (995)

Revision date: 03.09.2019 **Version (Revision):** 6.0.1 (6.0.0)

Print date: 03.09.2019

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferabily with a detergent; avoid use of solvents.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Do not eat or drink during work - no smoking. Comply with the health and safety at work laws. For personal protection see Section 8.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No particular measures required.

Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (D): 12

Storage class (TRGS 510) (D): 12

Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep containers dry and cool. Comply with the health and saftey at work laws.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY; CAS No.: 64742-48-9

Limit value type (country of origin): MAK (CH)
Limit value: 50 ppm /

Limit value : 50 ppm / 300 mg/m³ Version : 01.01.2013

Version: 01.01.2013 Limit value type (country of origin): STEL (CH)

Limit value: 100 ppm / 600 mg/m³

Version: 01.01.2013

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Wear protective glasses in case of splashes.

Skin protection

Body protection

After skin contact wash thorougly with soap and water or use recognised skin cleanser. Do Not use solvents or thinners.

Page: 3 / 6

(EN / CH)

Item Numbers: 00665-1000 Page 3 of 6

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Lascaux Studio Bronze Original Aluminium (995)

Revision date : 03.09.2019 **Version (Revision) :** 6.0.1 (6.0.0)

Print date : 03.09.2019

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Liquid. Colour: Colourless.

Odour

Poor, characteristic.

Safety relevant basis data

Initial boiling point and boiling (1013 hPa) approx. 100 °C Flash point : not applicable Vapour pressure : (50 °C) 120 hPa approx. g/cm³ Density: (20 °C) approx. 1,3 pH: 7,5 approx. Viscosity: (20 °C) 4000 mPa.s approx.

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

No information available.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

Page: 4 / 6

(EN / CH)

Item Numbers: 00665-1000 Page 4 of 6

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Lascaux Studio Bronze Original Aluminium (995)

Revision date : 03.09.2019 **Version (Revision) :** 6.0.1 (6.0.0)

Print date : 03.09.2019

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

There are no data available on the product itself. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

08 01 11: waste paint and varnish containing organic solvents or other dangerous substances.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture $^{15.1}$

National regulations

U.S.A. Conforms to ASTM D-4236.

Technische Anleitung Luft (TA-Luft) (D):

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class (WGK)

Class (D): 1 (Slightly hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

Page: 5 / 6

(EN / CH)

Item Numbers: 00665-1000 Page 5. of 6

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Lascaux Studio Bronze Original Aluminium (995)

Revision date : 03.09.2019 **Version (Revision) :** 6.0.1 (6.0.0)

Print date : 03.09.2019

No information available.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H301 Toxic if swallowed. May be fatal if swallowed and enters airways. H304 H311 Toxic in contact with skin. H314 Causes severe skin burns and eve damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. Toxic if inhaled. H331 H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 6 / 6

(EN / CH)

Item Numbers: 00665-1000 Page 6 of 6