

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 1/10

Ceramic : all colours - FDS014

**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

>SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**> 1.1. Product identifier**

Product name : Ceramic : all colours

Product code : FDS014.

See list of references in appendix.

UFI : N7F0-20UJ-2008-TFSR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paints & Varnishes for artists

1.3. Details of the supplier of the safety data sheet

Registered company name : PEBEO SAS.

Address : CS 10106 .13881.GEMENOS CEDEX.FRANCE.

Telephone : 33 (0) 4.42.32.08.08. Fax : 33 (0) 4.42.32.01.70.

reglementation@pebeo.com

www.pebeo.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.**Other emergency numbers**

United Kingdom : 0870 600 6266 Ireland : 01 809 25 66

>SECTION 2 : HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture****> In compliance with EC regulation No. 1272/2008 and its amendments.**

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements**> In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS02

Signal Word :

WARNING

Hazard statements :

H226

Flammable liquid and vapour.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Precautionary statements - Storage :

P403 + P235

Store in a well-ventilated place. Keep cool.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 2/10

Ceramic : all colours - FDS014

Precautionary statements - Disposal :

P501

Dispose of contents/container in accordance with
local/regional/national/international regulation.**> 2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 649-327-00-6 CAS: 64742-48-9 EC: 265-150-3 REACH: 01-2119474196-32 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	GHS08 Dgr Asp. Tox. 1, H304	P [1]	25 \leq x % < 50
CAS: 64742-48-9 EC: 919-857-5 REACH: 01-2119463258-33 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	[1]	10 \leq x % < 25
CAS: 64216-15-5 EC: 264-731-9 CALCIUM 3,5,5-TRIMETHYLHEXANOATE	GHS07 Wng Acute Tox. 4, H302 Eye Irrit. 2, H319		0 \leq x % < 2.5
CAS: 22464-99-9 EC: 245-018-1 2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT	GHS08 Wng Repr. 2, H361d	[2]	0 \leq x % < 2.5

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 3/10

Ceramic : all colours - FDS014

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 4/10

Ceramic : all colours - FDS014

>SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

> 7.1. Precautions for safe handling

- Always wash hands after handling.
- Remove and wash contaminated clothing before re-using.
- Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

- Handle in well-ventilated areas.
- Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.
- Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.
- Prevent the accumulation of electrostatic charges with connections to earth.
- The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive
- Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.
- Keep packages tightly closed and away from sources of heat, sparks and naked flames.
- Do not use tools which may produce sparks. Do not smoke.
- Prevent access by unauthorised personnel.

Recommended equipment and procedures :

- For personal protection, see section 8.
- Observe precautions stated on label and also industrial safety regulations.
- Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

- No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

- Keep out of reach of children.
- Keep the container tightly closed in a dry, well-ventilated place.
- Keep away from all sources of ignition - do not smoke.
- Keep well away from all sources of ignition, heat and direct sunlight.
- Avoid accumulation of electrostatic charges.
- The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

>SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- Poland (Dz. U. z 2018 r. poz. 917, 1000 i 1076) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64742-48-9	300 mg/m ³	900 mg/m ³			
64742-48-9	300 mg/m ³	900 mg/m ³			

- Switzerland (SUVAPRO 2019) :

CAS	VME	VLE	Valeur plafond	Notations
64742-48-9	50 ppm 300 mg/m ³	100 mg/m ³ 600 fc/m ³		

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 5/10

Ceramic : all colours - FDS014

64742-48-9	50 ppm 300 mg/m ³	100 mg/m ³ 600 fc/m ³		
------------	---------------------------------	--	--	--

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

▷ - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

▷SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Fluid liquid.

▷ Colour

Unspecified

▷ Odour

Odour threshold : Not stated.

▷ Melting point

Melting point/melting range : Not relevant.

▷ Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : 210 °C.

▷ Flammability

Flammability (solid, gas) : Not stated.

▷ Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

Flash point

Flash Point : 35.00 °C.

Auto-ignition temperature

Self-ignition temperature : Not relevant.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 6/10

Ceramic : all colours - FDS014**Decomposition temperature**

Decomposition point/decomposition range : Not relevant.

▷ **pH**

pH : Not relevant.

pH (aqueous solution) : Not stated.

▷ **Kinematic viscosity**

Viscosity : Not stated.

▷ **Solubility**

Water solubility : Insoluble.

Fat solubility : Not stated.

▷ **Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

▷ **Density and/or relative density**

Density : 1.05

▷ **Relative vapour density**

Vapour density : Not stated.

▷ **9.2. Other information**

VOC (g/l) : 416.65

▷ **9.2.1. Information with regard to physical hazard classes**

No data available.

▷ **9.2.2. Other safety characteristics**

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 7/10

Ceramic : all colours - FDS014

>SECTION 11 : TOXICOLOGICAL INFORMATION**> 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances**Acute toxicity :**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Oral route :
LD50 > 5000 mg/kg
OECD Guideline 401 (Acute Oral Toxicity)
Species : Rat (recommended by the CLP)

Dermal route :
LD50 > 5000 mg/kg
OECD Guideline 402 (Acute Dermal Toxicity)
Species : Rabbit (recommended by the CLP)

Inhalation route (Vapours) :
LC50 > 4951 mg/m3
OECD Guideline 403 (Acute Inhalation Toxicity)
Species : Rat (recommended by the CLP)

Carcinogenicity :

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Carcinogenicity Test :
Negative.
No carcinogenic effect.
OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicant :

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

No toxic effect for reproduction
OECD Guideline 414 (Prenatal Developmental Toxicity Study)
OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Specific target organ systemic toxicity - repeated exposure :

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Oral route :
Duration of exposure : 90 days
C > 100 mg/kg body weight/day
Duration of exposure : 90 days
OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Species : Rat (recommended by CLP)

Inhalation route (Vapours) :
Duration of exposure : 90 days
C > 1 mg/l/6hrs/day
Duration of exposure : 90 days
OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

11.1.2. Mixture

No toxicological data available for the mixture.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 8/10

Ceramic : all colours - FDS014**► Monograph(s) from the IARC (International Agency for Research on Cancer) :**

- CAS 108-94-1 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
 CAS 7631-86-9 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
 CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION**12.1. Toxicity****12.1.1. Substances**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Fish toxicity : LC50 > 1000 mg/l
 Species : Oncorhynchus mykiss
 Duration of exposure : 96 h

Crustacean toxicity : EC50 = 1000 mg/l
 Species : Daphnia magna
 Duration of exposure : 48 h

Algae toxicity : ECr50 > 1000 mg/l
 Species : Pseudokirchnerella subcapitata
 Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances**

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 9/10

Ceramic : all colours - FDS014

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

- 20 01 27 * paint, inks, adhesives and resins containing dangerous substances
- 15 01 02 plastic packaging

>SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

14.1. UN number or ID number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or
PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel D/E
	3	F1	III	3	30	5 L	163 367 650	E1	3	
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	3	-	III	5 L	F-E. S-E	163 223 367 955	E1	Category A	-	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	III	355	60 L	366	220 L	A3 A72 A192	E1	
	3	-	III	Y344	10 L	-	-	A3 A72 A192	E1	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

>SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****> - Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

The mixture is contained in packaging that does not exceed 125 ml.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
PEBEO SAS

Version 8.1 (11/03/2022) - Page 10/10

Ceramic : all colours - FDS014**>SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.

> Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

CMR: Carcinogenic, mutagenic or reprotoxic.

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.

> Modification compared to the previous version

Références	Désignation Référence
756451	SET INITIATION CERAMIC 6 FLACONS ASSORTIS DE 20 ML
757451	SET EXPLORATION CERAMIC A LA CUVE 12 FLACONS ASSORTIS 20 ML
758451	COFFRET COLLECTION CERAMIC 10X45ML
758702	COFFRET ATELIER MIXED MEDIA 2
025037	CERAMIC 45 ML VERT
025036	CERAMIC 45 ML VIOLET CLAIR
025035	CERAMIC 45 ML BLEU
025034	CERAMIC 45 ML ROSE
025033	CERAMIC 45 ML JAUNE CLAIR
025032	CERAMIC 45 ML BLANC ANTIQUE
025031	CERAMIC 45 ML CYCLAMEN
025030	CERAMIC 45 ML NACRE
025029	CERAMIC 45 ML RUBIS
025028	CERAMIC 45 ML VERT VICTORIA
025027	CERAMIC 45 ML VERT FEUILLE
025026	CERAMIC 45 ML EMERAUDE
025025	CERAMIC 45 ML SEVRES
025024	CERAMIC 45 ML ROUGE CERISE
025023	CERAMIC 45 ML ORANGE
025022	CERAMIC 45 ML JAUNE ORANGE
025021	CERAMIC 45 ML JAUNE RICHE
025020	CERAMIC 45 ML GRENAT
025019	CERAMIC 45 ML CHAMOIS
025018	CERAMIC 45 ML BRUN ROUGE
025017	CERAMIC 45 ML BRUN ECAILLE CLAIR
025016	CERAMIC 45 ML TURQUOISE
025015	CERAMIC 45 ML OR RICHE
025014	CERAMIC 45 ML NOIR
025013	CERAMIC 45 ML METALLISE
025012	CERAMIC 45 ML MAUVE
025011	CERAMIC 45 ML LAVANDE
025010	CERAMIC 45 ML BLANC
754505	CERAMIC SET MIXED MEDIA 6 FLACONS ASSORTIS 20ML
764502	VITRAIL/ CERAMIC SET MIXED MEDIA 6 FLACONS ASSORTIS 20ML
764505	CERAMIC/ MOON SET MIXED MEDIA 6 FLACONS ASSORTIS 20ML