01463-2224

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Printing date 28.03.2017

Revision: 28.03.2017

· 1.1 Product identifier

- · Trade name: Aerosol Molotow "toast" signalschwarz (D)
- · Article number (product ID.): REZ619
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Tel.:+49 6269 95 20
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0001

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



 $GHS02\ flame$

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H336

May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms





- GHS02 GH
- · Signal word Danger
- · Hazard-determining components of labelling: acetone

n-butyl acetate

(Contd. on page 2)

B -

Page 1 of 10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.03.2017 Revision: 28.03.2017

Trade name: Aerosol Molotow "toast" signalschwarz (D)

(Contd. of page 1)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information: Without adequate ventilation, explosive atmosphere/gas mix may be created.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	ô Flam. Liq. 2, H225; 🚺 Eye Irrit. 2, H319; STOT SE 3, H336	ī.
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1, H220; Press. Gas C, H280	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane 🗞 Flam. Gas 1, H220; 🔷 Press. Gas C, H280	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226; � STOT SE 3, H336	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ♠ Flam. Gas 1, H220; ← Press. Gas C, H280	5-<10%
CAS: 9004-70-0	nitrocellulose with water(not less than 25% water, by mass) Unst. Expl., H200	5-<10%

Revision: 28.03.2017

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.03.2017

Trade name: Aerosol Molotow "toast" signalschwarz (D)

of page 2) -<10%
-<10%
5-<5%
5-<5%
5-<5%
<2.5%
<1%
5

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Cool container whit water

- $\cdot \textbf{\textit{For safety reasons unsuitable extinguishing agents:}} \ \textit{Water with full jet}$
- · 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 28.03.2017

Trade name: Aerosol Molotow ''toast'' signalschwarz (D)

(Contd. of page 3)

Revision: 28.03.2017

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

870	dients with limit values that require monitoring at the workplace:	
67-64	-1 acetone	
WEL	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm	
115-1	0-6 dimethyl ether	
WEL	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm	
123-8	6-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
106-9	7-8 butane (containing ≤0,1 % butadiene (203-450-8))	
WEL	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	
108-6	5-6 2-methoxy-1-methylethyl acetate	

(Contd. on page

according to 1907/2006/EC, Article 31

Printing date 28.03.2017

Trade name: Aerosol Molotow "toast" signalschwarz (D)

Revision: 28.03.2017

	Contd. of page 4)
1330-20-7 xylene	
WEL Short-term value: 441 mg/m³, 100 ppm	
Long-term value: 220 mg/m³, 50 ppm	
Sk; BMGV	
64-17-5 ethanol	
WEL Long-term value: 1920 mg/m³, 1000 ppm	
100-41-4 ethylbenzene	
WEL Short-term value: 552 mg/m³, 125 ppm	
Long-term value: 441 mg/m³, 100 ppm	
Sk Sk	
· Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV 650 mmol/mol creatinine	
Medium: urine	
Sampling time: post shift	
Parameter: methyl hippuric acid	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

Eye protection:



Tightly sealed goggles

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.03.2017

Trade name: Aerosol Molotow "toast" signalschwarz (D)

(Contd. of page 5)

Revision: 28.03.2017

0.1.7	1
9.1 Information on basic physical and c General Information	hemical properties
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: -44.5 °C
Flash point:	<0 °C
	Without propellant gas.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20 °C:	233 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	85.0 %
	With propellant gas. Content given by weight.
VOC (EU)	84.96 %
Solids content:	15.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- $\cdot \textbf{10.1 Reactivity} \ \textit{No further relevant information available}.$
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.03.2017 Revision: 28.03.2017

Trade name: Aerosol Molotow "toast" signalschwarz (D)

(Contd. of page 6)

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- $\cdot \textbf{12.4 Mobility in soil} \ No \ further \ relevant \ information \ available.$
- $\cdot \textit{Additional ecological information:}$
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

- · Uncleaned packaging:
- $\cdot \textit{Recommendation:} \ Disposal \ must \ be \ made \ according \ to \ official \ regulations.$

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA

UN1950

(Contd. on page 8)

GB -

Trade name: Aerosol Molotow ''toast'' signalschwarz (D)

according to 1907/2006/EC, Article 31

Printing date 28.03.2017

Revision: 28.03.2017

	(Contd. of pag
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1 Gases.
IMDG, IATA	
Class	2.1
Label	2.1
	μ.1
14.4 Packing group	
ADR, IMDG, IATA	Void
	not classified
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
	not classified
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category R. For WASTE AFROSOLS: Category C. Cler
	Category B. For WASTE AEROSOLS: Category C, Clear
Segregation Code	of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litr.
Segregation Code	Segregation as for class 9. Stow "separated from" class
	except for division 1.4. For AEROSOLS with a capaci
	above 1 litre: Segregation as for the appropriate
	subdivision of class 2. For WASTE AEROSOLS
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Anna	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
ADR Limited quantities (LQ)	IL
	IL Code: E0
Limited quantities (LQ)	
Limited quantities (LQ)	Code: E0

according to 1907/2006/EC, Article 31

Printing date 28.03.2017

Trade name: Aerosol Molotow "toast" signalschwarz (D)

(Contd. of page 8)

Revision: 28.03.2017

 \cdot IMDG

Limited quantities (LQ)

Code: E0

· Excepted quantities (EQ)

Not permitted as Excepted Quantity

UN 1950 AEROSOLS, 2.1 · UN ''Model Regulation'':

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H200 Unstable explosives.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department
- · Contact: Hr. Hamberger
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

(Contd. on page 10)

according to 1907/2006/EC, Article 31

Printing date 28.03.2017

Trade name: Aerosol Molotow "toast" signalschwarz (D)

(Contd. of page 9)

Revision: 28.03.2017

CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Unst. Expl.: Explosives - Unstable explosive Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols – Category 1
Press. Gas C: Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category I Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Eye Trin. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

GB

This safety data sheet is valid for the following item numbers / colors of BELTON MOLOTOW PREMIUM 400ml spraycans:

327.180 TOAST Signal Black