

**INDUSTRIA MAIMERI S.P.A.****CLASSICO OIL COLOURS****03131 Yellow Ochre**Revision nr.35  
Dated 10/7/2014  
Printed on 10/7/2014  
Page n. 1 / 7**Safety data sheet****SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**Code: **03131**  
Product name **CLASSICO OIL COLOURS 03131 Yellow Ochre****1.2. Relevant identified uses of the substance or mixture and uses advised against**Intended use **Oil colour.****1.3. Details of the supplier of the safety data sheet**Name **INDUSTRIA MAIMERI S.P.A.**  
Full address **Via Gianni Maimeri, 1**  
District and Country **20060 Mediglia (MI)**  
**Italia**  
Tel. **+39 02 906981**  
Fax **+39 02 90698999**e-mail address of the competent person responsible for the Safety Data Sheet **schedesicurezza@maimeri.it**Product distribution by **INDUSTRIA MAIMERI S.P.A. VIA G.MAIMERI 1 20060 BETTOLINO DI MEDIGLIA (MI) ITALY****1.4. Emergency telephone number**For urgent inquiries refer to **Australia : 131126**  
**USA: 1 800 222 1222**  
**Regno Unito NHS Direct (UK): +44 (0) 845 46 47****SECTION 2. Hazards identification.****2.1. Classification of the substance or mixture.**

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

**2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.**Hazard classification and indication:  
**Aquatic Chronic 3 H412****2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.**Danger Symbols: --  
R phrases: 52/53

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

**2.2. Label elements.**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:  
**H412** Harmful to aquatic life with long lasting effects.Precautionary statements:  
**P273** Avoid release to the environment.

<b>INDUSTRIA MAIMERI S.P.A.</b>		Revision nr.35 Dated 10/7/2014 Printed on 10/7/2014 Page n. 2 / 7
<b>CLASSICO OIL COLOURS</b>		<b>03131 Yellow Ochre</b>
<b>SECTION 2. Hazards identification. ... / &gt;&gt;</b>		
<p><b>P501</b> Dispose of contents / container to in accordance with local and national norms. . .</p> <p><b>2.3. Other hazards.</b></p> <p>Information not available.</p>		
<b>SECTION 3. Composition/information on ingredients.</b>		
<b>3.1. Substances.</b>		
Information not relevant.		
<b>3.2. Mixtures.</b>		
<b>Contains:</b>		
<b>Identification.</b>	<b>Conc. %.</b>	<b>Classification 67/548/EEC.</b>
<b>Zinc oxide</b>		
CAS. 1314-13-2	1,5 - 2	N R50/53
EC. 215-222-5		
INDEX. 030-013-00-7		
Reg. no. 01-2119463881-32-0000		
<b>ETHYLENE GLYCOL MONOBUTYL ETHER</b>		
CAS. 112-34-5	0 - 0,05	Xi R36
EC. 203-961-6		
INDEX. 603-096-00-8		
<p>Classification 1272/2008 (CLP).</p> <p>Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410</p> <p>Eye Irrit. 2 H319</p>		
<p>Note: Upper limit is not included into the range. The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.</p> <p>T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)</p>		
<b>SECTION 4. First aid measures.</b>		
<b>4.1. Description of first aid measures.</b>		
Not specifically necessary. Observance of good industrial hygiene is recommended.		
<b>4.2. Most important symptoms and effects, both acute and delayed.</b>		
No episodes of damage to health ascribable to the product have been reported.		
<b>4.3. Indication of any immediate medical attention and special treatment needed.</b>		
Information not available.		
<b>SECTION 5. Firefighting measures.</b>		
<b>5.1. Extinguishing media.</b>		
SUITABLE EXTINGUISHING EQUIPMENT		
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.		
UNSUITABLE EXTINGUISHING EQUIPMENT		
None in particular.		
<b>5.2. Special hazards arising from the substance or mixture.</b>		
HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE		
Do not breathe combustion products.		
<b>5.3. Advice for firefighters.</b>		
GENERAL INFORMATION		
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.		
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS		
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).		

<b>INDUSTRIA MAIMERI S.P.A.</b>		Revision nr.35 Dated 10/7/2014 Printed on 10/7/2014 Page n. 3 / 7
<b>CLASSICO OIL COLOURS</b>	<b>03131 Yellow Ochre</b>	

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

### 7.2. Conditions for safe storage, including any incompatibilities.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:  
United Kingdom

EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).

Éire  
OEL EU

Code of Practice Chemical Agent Regulations 2011.  
Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive

TLV-ACGIH

2000/39/EC.  
ACGIH 2012

#### Zinc oxide

#### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm
TLV-ACGIH		5		15	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration.

#### HAND PROTECTION

Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent.

The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

#### RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

**INDUSTRIA MAIMERI S.P.A.****CLASSICO OIL COLOURS****03131 Yellow Ochre**Revision nr.35  
Dated 10/7/2014  
Printed on 10/7/2014  
Page n. 4 / 7**SECTION 8. Exposure controls/personal protection. ... / >>**

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

**EYE PROTECTION**

Use of protective airtight goggles (ref. standard EN 166) recommended.

**ENVIRONMENTAL EXPOSURE CONTROLS.**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties.****9.1. Information on basic physical and chemical properties.**

Appearance		paste
Colour		ochre
Odour		characteristic
Odour threshold.		Not available.
pH.		
Melting point / freezing point.		Not available.
Initial boiling point.		Not available.
Boiling range.		Not available.
Flash point.	>	60 °C.
Evaporation Rate		Not available.
Flammability of solids and gases		Not available.
Lower inflammability limit.		Not available.
Upper inflammability limit.		Not available.
Lower explosive limit.		Not available.
Upper explosive limit.		Not available.
Vapour pressure.		Not available.
Vapour density		Not available.
Relative density.		0,2 Kg/l
Solubility		INSOLUBLE, DILUTE WITH WHITE SPIRIT
Partition coefficient: n-octanol/water		Not available.
Auto-ignition temperature.		Not available.
Decomposition temperature.		Not available.
Viscosity		Not available.
Explosive properties		Not available.
Oxidising properties		Not available.

**9.2. Other information.**

Solid content.	69,88 %	
VOC (Directive 1999/13/EC) :	0,05 % - 0,80	g/litre.
VOC (volatile carbon) :	0,04 % - 0,68	g/litre.

**SECTION 10. Stability and reactivity.****10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions.**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid.**

None in particular. However the usual precautions used for chemical products should be respected.

**10.5. Incompatible materials.**

Information not available.

**10.6. Hazardous decomposition products.**

Information not available.



**INDUSTRIA MAIMERI S.P.A.****CLASSICO OIL COLOURS****03131 Yellow Ochre**Revision nr.35  
Dated 10/7/2014  
Printed on 10/7/2014  
Page n. 6 / 7**SECTION 15. Regulatory information. ... / >>**

None.

Substances subject to authorisation (Annex XIV REACH).  
None.Substances subject to exportation reporting pursuant to (EC) Reg. 689/2008:  
None.Substances subject to the Rotterdam Convention:  
None.Substances subject to the Stockholm Convention:  
None.Healthcare controls.  
Information not available.**15.2. Chemical safety assessment.**

No chemical safety assessment has been processed for the mixture and the substances it contains.

**SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H319</b>	Causes serious eye irritation.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

<b>R36</b>	IRRITATING TO EYES.
<b>R50/53</b>	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
<b>R52/53</b>	HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value

**INDUSTRIA MAIMERI S.P.A.****CLASSICO OIL COLOURS****03131 Yellow Ochre**Revision nr.35  
Dated 10/7/2014  
Printed on 10/7/2014  
Page n. 7 / 7**SECTION 16. Other information. ... / >>**

- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

**GENERAL BIBLIOGRAPHY**

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. The Merck Index. - 10th Edition
9. Handling Chemical Safety
10. Niosh - Registry of Toxic Effects of Chemical Substances
11. INRS - Fiche Toxicologique (toxicological sheet)
12. Patty - Industrial Hygiene and Toxicology
13. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
14. ECHA website

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**Changes to previous review:**

The following sections were modified:

02 / 03 / 04 / 05 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.