

**INDUSTRIA MAIMERI S.P.A.****AUXILIARY PRODUCTS****58661 Strog solvent for restoration**Revision nr.6  
Dated 07/03/2017  
Printed on 07/03/2017  
Page n. 1 / 10

EN

**Safety data sheet****SECTION 1. Identification of the substance/mixture and of the company/undertaking.****1.1. Product identifier.**Code: **58661**  
Product name: **AUXILIARY PRODUCTS 58661 Strog solvent for restoration****1.2. Relevant identified uses of the substance or mixture and uses advised against.**Intended use: **Thinner.****1.3. Details of the supplier of the safety data sheet.**Name: **INDUSTRIA MAIMERI S.P.A.**  
Full address: **Via Gianni Maimeri, 1**  
District and Country: **20060 Mediglia (MI) Italia**  
Tel. **+39 02 906981**  
Fax. **+39 02 90698999**e-mail address of the competent person.  
responsible for the Safety Data Sheet. **schedesicurezza@maimeri.it**Product distribution by: **INDUSTRIA MAIMERI S.P.A. VIA G.MAIMERI 1 20060 BETTOLINO DI MEDIGLIA (MI) ITALY****1.4. Emergency telephone number.**For urgent inquiries refer to. **Australia : 131126**  
**USA: 1 800 222 1222**  
**Regno Unito NHS Direct (UK): +44 (0) 845 46 47****SECTION 2. Hazards identification.****2.1. Classification of the substance or mixture.**

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

## Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

**2.2. Label elements.**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words: **Danger**

Hazard statements:

**H225** Highly flammable liquid and vapour.  
**H373** May cause damage to organs through prolonged or repeated exposure.

**INDUSTRIA MAIMERI S.P.A.**
 Revision nr.6  
 Dated 07/03/2017  
 Printed on 07/03/2017  
 Page n. 2 / 10

EN

**AUXILIARY PRODUCTS 58661 Strog solvent for restoration****SECTION 2. Hazards identification. ... / >>**

**H412** Harmful to aquatic life with long lasting effects.  
**EUH066** Repeated exposure may cause skin dryness or cracking.

**Precautionary statements:**

**P101** If medical advice is needed, have product container or label at hand.  
**P102** Keep out of reach of children.  
**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P233** Keep container tightly closed.  
**P260** Do not breathe dust / fume / gas / mist / vapours / spray.  
**P280** Wear protective gloves / eye protection / face protection.  
**P314** Get medical advice / attention if you feel unwell.  
**P501** Dispose of contents / container to in accordance with local and national norms. . .

**Contains:** White Spirit

**2.3. Other hazards.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients.****3.1. Substances.**

Information not relevant.

**3.2. Mixtures.****Contains:**

Identification.	x = Conc. %.	Classification 1272/2008 (CLP).
<b>ISOAMYL ACETATE</b> CAS. 628-63-7 EC. 211-047-3 INDEX. 607-130-00-2 Reg. no. 01-2119491285-32	54 ≤ x < 58	Flam. Liq. 3 H226, EUH066, Note C
<b>2-methyl butyl acetate</b> CAS. 624-41-9 EC. 210-843-8 INDEX. 607-130-00-2	25,5 ≤ x < 27	Flam. Liq. 3 H226, EUH066, Note C
<b>White Spirit</b> CAS. 919-446-0 EC. 919-446-0 INDEX. 919-446-0 Reg. no. 01-2119458049-33	8,5 ≤ x < 10	Flam. Liq. 3 H226, STOT RE 1 H372, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Note P
<b>ISOAMYL ACETATE</b> CAS. 123-92-2 EC. 204-662-3 INDEX. 607-130-00-2	4 ≤ x < 4,5	Flam. Liq. 3 H226, EUH066, Note C

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures.****4.1. Description of first aid measures.**

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

<b>INDUSTRIA MAIMERI S.P.A.</b>	Revision nr.6 Dated 07/03/2017 Printed on 07/03/2017 Page n. 3 / 10
<b>AUXILIARY PRODUCTS</b> <b>58661 Strog solvent for restoration</b>	EN
<b>SECTION 4. First aid measures.</b> ... / >>	
<p><b>4.2. Most important symptoms and effects, both acute and delayed.</b> Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.</p> <p><b>4.3. Indication of any immediate medical attention and special treatment needed.</b> Information not available.</p>	
<b>SECTION 5. Firefighting measures.</b>	
<p><b>5.1. Extinguishing media.</b> SUITABLE EXTINGUISHING EQUIPMENT Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak. UNSUITABLE EXTINGUISHING EQUIPMENT Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.</p> <p><b>5.2. Special hazards arising from the substance or mixture.</b> HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.</p> <p><b>5.3. Advice for firefighters.</b> GENERAL INFORMATION Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).</p>	
<b>SECTION 6. Accidental release measures.</b>	
<p><b>6.1. Personal precautions, protective equipment and emergency procedures.</b> Block the leakage if there is no hazard. Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.  Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.</p> <p><b>6.2. Environmental precautions.</b> The product must not penetrate into the sewer system or come into contact with surface water or ground water.</p> <p><b>6.3. Methods and material for containment and cleaning up.</b> Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.</p> <p><b>6.4. Reference to other sections.</b> Any information on personal protection and disposal is given in sections 8 and 13.</p>	
<b>SECTION 7. Handling and storage.</b>	
<p><b>7.1. Precautions for safe handling.</b> Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.</p> <p><b>7.2. Conditions for safe storage, including any incompatibilities.</b> Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from</p>	

**INDUSTRIA MAIMERI S.P.A.**Revision nr.6  
Dated 07/03/2017  
Printed on 07/03/2017  
Page n. 4 / 10

EN

**AUXILIARY PRODUCTS 58661 Strog solvent for restoration****SECTION 7. Handling and storage. ... / >>**

any incompatible materials, see section 10 for details.

**7.3. Specific end use(s).**

Information not available.

**SECTION 8. Exposure controls/personal protection.****8.1. Control parameters.**

Regulatory References:

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

**ISOAMYL ACETATE****Threshold Limit Value.**

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm
VLEP	ITA		100		150

**2-methyl butyl acetate****Threshold Limit Value.**

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm
VLEP	ITA		100		150

**ISOAMYL ACETATE****Threshold Limit Value.**

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm
VLEP	ITA	532	100		150

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**8.2. Exposure controls.**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS.**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

EPY 9.3.0 - SDS 1003

<b>INDUSTRIA MAIMERI S.P.A.</b>		Revision nr.6 Dated 07/03/2017 Printed on 07/03/2017 Page n. 5 / 10	EN
<b>AUXILIARY PRODUCTS</b>	<b>58661 Strog solvent for restoration</b>		

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance		liquid
Colour		colourless
Odour		characteristic
Odour threshold.		Not available.
pH.		
Melting point / freezing point.		Not available.
Initial boiling point.	>	35 °C.
Boiling range.		Not available.
Flash point.	<	23 °C.
Evaporation Rate		Not available.
Flammability of solids and gases		Not available.
Lower inflammability limit.		Not available.
Upper inflammability limit.		Not available.
Lower explosive limit.		Not available.
Upper explosive limit.		Not available.
Vapour pressure.		Not available.
Vapour density		Not available.
Relative density.		0,1
Solubility		Not available.
Partition coefficient: n-octanol/water		Not available.
Auto-ignition temperature.		Not available.
Decomposition temperature.		Not available.
Viscosity		80 cps
Explosive properties		Not available.
Oxidising properties		Not available.

### 9.2. Other information.

Total solids {0}.		85,10 %
-------------------	--	---------

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

#### ETHANOL

Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.

### 10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

#### ETHANOL

Avoid exposure to: sources of heat,naked flames.

### 10.5. Incompatible materials.

Information not available.

### 10.6. Hazardous decomposition products.

**INDUSTRIA MAIMERI S.P.A.****AUXILIARY PRODUCTS****58661 Strog solvent for restoration**Revision nr.6  
Dated 07/03/2017  
Printed on 07/03/2017  
Page n. 6 / 10

EN

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

**SECTION 11. Toxicological information.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects.**ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:	Not classified (no significant component).
LC50 (Inhalation - mists / powders) of the mixture:	Not classified (no significant component).
LD50 (Oral) of the mixture:	Not classified (no significant component).
LD50 (Dermal) of the mixture:	Not classified (no significant component).

White Spirit	
LD50 (Oral).	> 5000 mg/kg
LD50 (Dermal).	> 4

ETHANOL	
LD50 (Oral).	> 5000 mg/kg Rat
LC50 (Inhalation).	120 mg/l/4h Pimephales promelas

SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION.

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

May cause damage to organs.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

**SECTION 12. Ecological information.**

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on aquatic environment.

**12.1. Toxicity.**

White Spirit	
LC50 - for Fish.	< 30 mg/l/96h
EC50 - for Crustacea.	< 22 mg/l/48h
EC50 - for Algae / Aquatic Plants.	< 10 mg/l/72h

**INDUSTRIA MAIMERI S.P.A.**
 Revision nr.6  
 Dated 07/03/2017  
 Printed on 07/03/2017  
 Page n. 7 / 10

EN

**AUXILIARY PRODUCTS 58661 Strog solvent for restoration****SECTION 12. Ecological information. ... / >>**

ETHANOL  
 LC50 - for Fish. 2029 mg/l/96h Alga ( BUTANONE; Nr. CAS 78-93-3 )  
 EC50 - for Crustacea. 2993 mg/l/48h pesce ( BUTANONE;Nr.CAS 78-93-3 )

**12.2. Persistence and degradability.**

ETHANOL  
 Solubility in water. 1000 - 10000 mg/l  
 Rapidly biodegradable.

**12.3. Bioaccumulative potential.**

ETHANOL  
 Partition coefficient: n-octanol/water. -0,35

**12.4. Mobility in soil.**

Information not available.

**12.5. Results of PBT and vPvB assessment.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects.**

Information not available.

**SECTION 13. Disposal considerations.****13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information.****14.1. UN number.**

ADR / RID, IMDG, IATA: 1263

**14.2. UN proper shipping name.**

ADR / RID: PAINT or PAINT RELATED MATERIAL  
 IMDG: PAINT or PAINT RELATED MATERIAL  
 IATA: PAINT or PAINT RELATED MATERIAL

**14.3. Transport hazard class(es).**

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3

**14.4. Packing group.**

ADR / RID, IMDG, IATA: II

**INDUSTRIA MAIMERI S.P.A.**Revision nr.6  
Dated 07/03/2017  
Printed on 07/03/2017  
Page n. 8 / 10

EN

**AUXILIARY PRODUCTS 58661 Strog solvent for restoration****SECTION 14. Transport information. ... / >>****14.5. Environmental hazards.**ADR / RID: NO  
IMDG: NO  
IATA: NO**14.6. Special precautions for user.**

ADR / RID:	HIN - Kemler: 33 Special Provision: 640C	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo: Pass.: Special Instructions:	Maximum quantity: 60 L Maximum quantity: 5 L A3, A72, A192	Packaging instructions: 364 Packaging instructions: 353

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.**

Information not relevant.

**SECTION 15. Regulatory information.****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product Point: 3 - 40

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment.**

No chemical safety assessment has been processed for the mixture and the substances it contains.

**SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.



**INDUSTRIA MAIMERI S.P.A.**
 Revision nr.6  
 Dated 07/03/2017  
 Printed on 07/03/2017  
 Page n. 9 / 10

EN

**AUXILIARY PRODUCTS****58661 Strog solvent for restoration****SECTION 16. Other information. ... / >>**

<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

**INDUSTRIA MAIMERI S.P.A.**Revision nr.6  
Dated 07/03/2017  
Printed on 07/03/2017  
Page n. 10 / 10

EN

**AUXILIARY PRODUCTS      58661 Strog solvent for restoration****SECTION 16. Other information. ... / >>**

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.  
Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:  
The following sections were modified:  
03 / 09 / 15.