

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 24-10-21 Revision date: 20-09-21 Supersedes version of: 28-06-18 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Retouching Varnish

Product code : 1109

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use

Use of the substance/mixture : Varnish

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Old Holland Classic Colours Since 1664 Nijendal 36

3972 KC Driebergen Rijsenburg

Nederland

T 0031 343 518 224 - F 0031 343 516 342 info@oldholland.com - www.oldholland.com

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
Netherlands	Nationaal Vergiftigingen Informatie Centrum	Huispostnummer B.00.118 Postbus 85500 3508 GA Utrecht		Only for the purpose of informing medical personnel in cases of acute intoxications

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225 H315 Skin corrosion/irritation, Category 2 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336 H372 Specific target organ toxicity — Repeated exposure, Category 1 Aspiration hazard, Category 1 H304 H411 Hazardous to the aquatic environment — Chronic Hazard, Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects. May be fatal if swallowed and enters airways. Highly flammable liquid and vapour. Causes skin irritation. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)









20-09-21 (Revision date) EN (English)

Page 1 of 17 Item Numbers: 01750-1101, 01750-1105

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP) : Danger

Contains : Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%),

Hydrocarbons, C9, aromatics

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H372 - Causes damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing vapours, mist, spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P273 - Avoid release to the environment.

P301+P310+P331 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do

NOT induce vomiting. P391 - Collect spillage.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) substance with a Community workplace exposure limit	CAS-No.: 64742-82-1 EC-No.: 265-185-4 EC Index-No.: 649-330-00-2 REACH-no: 01-2119458049- 33	< 70	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Muta. Not classified Carc. Not classified STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C9, aromatics	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851- 35	15 – 20	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (NL)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-	1 – 2	Flam. Liq. 2, H225

20-09-21 (Revision date) EN (English) 2/17

Item Numbers: 01750-1101, 01750-1105 Page 2 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone; propan-2-one; propanone substance with national workplace exposure limit(s) (NL); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	0,01 – 0,25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
methanol substance with national workplace exposure limit(s) (NL); substance with a Community workplace exposure limit	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-	0,01 - 0,25	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Specific concentration limits:			
Name	Product identifier	Specific concentration limits	
methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-	(3 ≤C < 10) STOT SE 2, H371 (10 ≤C < 100) STOT SE 1, H370	

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If medical advice is needed, have

product container or label at hand. Call a physician immediately. First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

Gently wash with plenty of soap and water. Take off immediately all contaminated clothing. First-aid measures after skin contact

If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Sand. Foam. Dry powder. Carbon dioxide. Water spray.

Unsuitable extinguishing media Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

: Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire : For further information, refer to section 10 : "Stability and Reactivity".

20-09-21 (Revision date) EN (English)

Page 3 of 17 Item Numbers: 01750-1101, 01750-1105



Other information

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Prevent fire fighting water from entering the environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe vapours, mist, spray.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. For further information refer to section 8:

"Exposure controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Sweep or shovel spills into appropriate container

for disposal. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Concerning personal protective equipment to use, see item 8. Provide good ventilation in

process area to prevent formation of vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Do not

breathe vapours, mist, spray. Use only outdoors or in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Explosion-free electrical equipment and lighting with earth. Ground/bond container and

receiving equipment.

Storage conditions : Keep only in the original container in a cool well ventilated place. Keep container closed when not in use. Store locked up. Store in a well-ventilated place. Keep cool. Keep

container tightly closed

container tightly closed.

Incompatible products : Strong bases. Strong acids. Strong oxidation agent.

Heat and ignition sources : Keep away from heat and direct sunlight. ignition sources.

7.3. Specific end use(s)

Solvent.

20-09-21 (Revision date) EN (English) 4/17

Item Numbers: 01750-1101, 01750-1105 Page 4 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Mile spirit Type 1 OEL TWA 116 mg/m² OEL TWA (ppm) 20 ppm OEL STEL 200 mg/m² OEL STEL 500 mg/m² Semark Skin. (Year of adoption 2007) Sequalatory reference Sequence (67-64-1) EU - Indicative Occupational Exposure Limit (IOEL 700 mg/m² Gellatory reference Aceton	Hydrocarbons, C9-C12, n-alkanes, iso-alkanes	s, cyclic, aromatic compounds (16.3%) (64742-82-1)		
OEL TWA [ppm] 20 ppm OEL STEL 290 mg/m² OEL STEL [ppm] 50 ppm Remark Skin, (Year of adoption 2007) Regulatory reference SCOEL Recommendations accetone; propan-2-one; propanone (67-68-1) EU - Indicative Occupational Exposure Limit (IOEL) OEL TWA [ppm] 500 ppm Acquiatory reference CoMMISSION DIRECTIVE 2000/39/EC Netherlands - Occupational Exposure Limit (IOEL) Regulatory reference Arbeitomic (67-68-1) Regulatory reference Del Company (100 ppm) Acceton (100 ppm	EU - Indicative Occupational Exposure Limit (IOEL)			
OEL TWA [ppm] 20 ppm OEL STEL (ppm] 50 ppm OEL STEL (ppm] 50 ppm Asmark Six, (Year of adoption 2007) Regulatory reference SCOEL Recommendations Sectione; propan-2-one; propanone (67-64-1) Total control of the co	Local name	White spirit Type 1		
OEL STEL 290 mg/m³ 50 ppm	IOEL TWA	116 mg/m³		
OEL STEL (ppm) 50 ppm Remark Skin. (Year of adoption 2007) Remark ScoEL Recommendations acetone; propan-2-one; propanone (67-64-1) EU - Indicative Occupational Exposure Limit (IOEL) ocal name Acetone OEL TWA (ppm) 500 ppm Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Netherlands - Occupational Exposure Limits ocal name Aceton GG-15min (OEL STEL) 2420 mg/m² Regulatory reference Arbitological Exposure Limits ocal name Aceton GG-35min (OEL STEL) 2420 mg/m² Regulatory reference Arbitological Exposure Limits ocal name Financial Exposure Limits ocal name Aceton GG-35min (OEL STEL) 2420 mg/m² Regulatory reference Arbitological Exposure Limits ocal name Financial Exposure Limits GG-35min (OEL STEL) 1900 mg/m² GG-35min (OEL STEL) 1900 mg/m² GG-36min (OEL STEL) 1900 mg/m² GG-36	IOEL TWA [ppm]	20 ppm		
Regulatory reference SCOEL Recommendations Begulatory reference SCOEL Recommendations Begulatory reference SCOEL Recommendations Begulatory reference SCOEL Recommendations Begulatory reference Acetone OEL TWA Acetone OEL TWA 1210 mg/m³ Begulatory reference COMMISSION DIRECTIVE 2000/39/EC Notherlands - Occupational Exposure Limits Cocal name Aceton Aceton Cocal name Arbeidsomstandighedenregeling 2021 Begulatory reference Arbeidsomstandighedenregeling 2021 Begulatory reference Arbeidsomstandighedenregeling 2021 Bethanol: ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Cocal name Ethanol Cocal name Ethanol Cocal name Aceton Cocal name Aceton Cocal name Aceton Cocal name Arbeidsomstandighedenregeling 2021 Bethanol: Arbeidsomstandighedenregeling 2021 Bethanol Cocal name Aceton Cocal name Arbeidsomstandighedenregeling 2021 Bethanol Cocal name Aceton Cocal name Aceton Mothanol OEL TWA (ppm) Cocal name Methanol OEL TWA (ppm)	IOEL STEL	290 mg/m³		
Regulatory reference SCOEL Recommendations acetone; propan-2-one; propanone (67-64-1) EU - Indicative Occupational Exposure Limit (IOEL) .ocal name Acetone OEL TWA 1210 mg/m³ OEL TWA [ppm] 500 ppm Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Netherlands - Occupational Exposure Limits .ocal name Aceton IGG-8u (OEL TWA) 1210 mg/m³ Regulatory reference Arbeitandighedenregeling 2021 Setherlands - Occupational Exposure Limits .ocal name Aceton IGG-8u (OEL TWA) 2420 mg/m³ Regulatory reference Arbeitandighedenregeling 2021 Setherlands - Occupational Exposure Limits .ocal name Ethanol IGG-8u (OEL TWA) 260 mg/m³ IGG-15min (OEL STEL) 1900 mg/m³ Regulatory IGE STEL) 1900 mg/m³ Regulatory reference Arbeitandighedenregeling Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen indeming ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) .ocal name Methanol OEL TWA (ppm) 200 ppm	IOEL STEL [ppm]	50 ppm		
acetone; propan-2-one; propanone (67-64-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Acetone OEL TWA OEL TWA [ppm] 500 ppm Regulatory reference CoMMISSION DIRECTIVE 2000/39/EC Netherlands - Occupational Exposure Limits Local name Aceton IGG-8u (OEL TWA) 1210 mg/m³ IGG-15min (OEL STEL) 2420 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethenoit ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol IGG-8u (OEL TWA) 260 mg/m³ IGG-15min (OEL STEL) 1900 mg/m³ IGG-15min (OEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limits Local name Ethanol IGG-8u (OEL TWA) 260 mg/m³ IGG-15min (OEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethendaria - Occupational Exposure Limit (IOEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021	Remark	Skin. (Year of adoption 2007)		
EU - Indicative Occupational Exposure Limit (IOEL) Local name Acetone OEL TWA 1210 mg/m³ OEL TWA (ppm) 500 ppm Regulatory reference COMMISSION DIRECTIVE 2000/39/ECN Netherlands - Occupational Exposure Limits Local name Aceton TGG-8u (OEL TWA) 1210 mg/m³ TGG-15min (OEL STEL) 2420 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol TGG-8u (OEL TWA) 260 mg/m³ TGG-15min (OEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Eu - Indicative Occupational Exposure Limit (IOEL) Local name Methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA (ppm) 200 ppm	Regulatory reference	SCOEL Recommendations		
Acetone OEL TWA OEL TWA [ppm] S00 ppm Regulatory reference OEL TWA) Aceton Aceton Aceton Aceton Aceton Aceton Aceton IGG-8u (OEL TWA) Regulatory reference Arbeidsomstandighedenregeling 2021 Standard Aceton IGG-8u (OEL TWA) Regulatory reference Arbeidsomstandighedenregeling 2021 Standard Aceton IGG-8u (OEL TWA) Arbeidsomstandighedenregeling 2021 Standard Aceton IGG-8u (OEL STEL) Arbeidsomstandighedenregeling 2021 Standard Aceton IGG-8u (OEL TWA) Arbeidsomstandighedenregeling 2021 Standard IGG-15min (OEL STEL) Iggor my ^{m3} I	acetone; propan-2-one; propanone (67-64-1)			
OEL TWA OEL TWA [ppm] 500 ppm Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Netherlands - Occupational Exposure Limits Local name Aceton Regulatory reference Arbeidsomstandighedenregeling 2021 Netherlands - Occupational Exposure Limits Regulatory reference Arbeidsomstandighedenregeling 2021 Netherlands - Occupational Exposure Limits Local name Ethanol Ethanol Regulatory reference Ethanol Regulatory reference Arbeidsomstandighedenregeling 2021 Netherlands - Occupational Exposure Limits Local name Ethanol Regulatory reference Ethanol Regulatory reference Arbeidsomstandighedenregeling 2021 Semark Limit (OEL STEL) 1900 mg/m³ Regulatory reference Arbeidsomstandighedenregeling een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA (ppm] 200 ppm	EU - Indicative Occupational Exposure Limit (IOEL)			
OEL TWA [ppm] 500 ppm Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Netherlands - Occupational Exposure Limits Local name Aceton IGG-8u (OEL TWA) 1210 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol IGG-15min (OEL STEL) 2420 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sethanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol IGG-8u (OEL TWA) 260 mg/m³ Regulatory (OEL STEL) 1900 mg/m³ Remark R	Local name	Acetone		
Regulatory reference COMMISSION DIRECTIVE 2000/39/EC Netherlands - Occupational Exposure Limits Local name Aceton GG-8u (OEL TWA) 1210 mg/m³ GG-15min (OEL STEL) 2420 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sthanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol GG-9u (OEL TWA) 260 mg/m³ GG-15min (OEL STEL) 1900 mg/m³ Remark Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA 260 mg/m³ OEL TWA [ppm] 200 ppm	IOEL TWA	1210 mg/m³		
Netherlands - Occupational Exposure Limits Local name Aceton 1210 mg/m³ 126G-8u (OEL TWA) Arbeidsomstandighedenregeling 2021 Sethanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol 1260 mg/m³ Edenark Ethanol 1290 mg/m³ Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidoontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA Depm 200 ppm	IOEL TWA [ppm]	500 ppm		
Aceton TGG-8u (OEL TWA) TGG-15min (OEL STEL) Arbeidsomstandighedenregelling 2021 Sethanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol TGG-15min (OEL STEL) 260 mg/m³ TGG-9u (OEL TWA) TGG-15min (OEL STEL) TGG-15	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
TGG-8u (OEL TWA) 1210 mg/m³ Regulatory reference Arbeidsomstandighedenregeling 2021 Sthanol; ethyl alcohol (64-17-5) Stetherlands - Occupational Exposure Limits Local name Ethanol 1900 mg/m³ Remark Remark Resulatory reference Regulatory reference Arbeidsomstandighedenregeling 2021 Ethanol 1900 mg/m³ Remark Remark Remark Resulatory reference Arbeidsomstandighedenregeling 2021 EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA ODE TWA ODE DYM 200 ppm	Netherlands - Occupational Exposure Limits			
TGG-15min (OEL STEL) Regulatory reference Arbeidsomstandighedenregeling 2021 Sthanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol GG-8u (OEL TWA) Remark Remark Remark Remark Remark Remark Remark Remark Respulatory reference Arbeidsomstandighedenregeling 2021 Standard Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 Methanol GEU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA 260 mg/m³ OEL TWA [ppm] 200 ppm	Local name	Aceton		
Regulatory reference Arbeidsomstandighedenregeling 2021 Sethanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol TGG-8u (OEL TWA) 260 mg/m³ TGG-15min (OEL STEL) 1900 mg/m³ Remark Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA 260 mg/m³ OEL TWA [ppm] 200 ppm	TGG-8u (OEL TWA)	1210 mg/m³		
Sethanol; ethyl alcohol (64-17-5) Netherlands - Occupational Exposure Limits Local name Ethanol EGG-8u (OEL TWA) EGG-15min (OEL STEL) Remark Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA OEL TWA [ppm] EU - 100 mg/m³ 200 ppm	TGG-15min (OEL STEL)	2420 mg/m³		
Netherlands - Occupational Exposure Limits Local name Ethanol TGG-8u (OEL TWA) 260 mg/m³ TGG-15min (OEL STEL) 1900 mg/m³ Remark Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA 260 mg/m³ OEL TWA [ppm] 200 ppm	Regulatory reference	Arbeidsomstandighedenregeling 2021		
Ethanol TGG-8u (OEL TWA) 260 mg/m³ TGG-15min (OEL STEL) 1900 mg/m³ Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA OEL TWA [ppm] 200 ppm	ethanol; ethyl alcohol (64-17-5)			
TGG-8u (OEL TWA) 260 mg/m³ TGG-15min (OEL STEL) Remark Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA [ppm] 200 ppm	Netherlands - Occupational Exposure Limits			
TGG-15min (OEL STEL) 1900 mg/m³ Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA 260 mg/m³ OOEL TWA [ppm] 200 ppm	Local name	Ethanol		
Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeter naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA OEL TWA [ppm] Z00 ppm	TGG-8u (OEL TWA)	260 mg/m³		
kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen. Regulatory reference Arbeidsomstandighedenregeling 2021 EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA 260 mg/m³ 200 ppm	TGG-15min (OEL STEL)	1900 mg/m³		
methanol (67-56-1) EU - Indicative Occupational Exposure Limit (IOEL) Local name Methanol OEL TWA [ppm] 200 ppm	Remark	kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van		
Local name Methanol OEL TWA [ppm] 200 ppm	Regulatory reference	Arbeidsomstandighedenregeling 2021		
Local name Methanol OEL TWA 260 mg/m³ OEL TWA [ppm] 200 ppm	methanol (67-56-1)			
OEL TWA 260 mg/m³ OEL TWA [ppm] 200 ppm	EU - Indicative Occupational Exposure Limit (IOEL)			
OEL TWA [ppm] 200 ppm	Local name	Methanol		
Fig. 7	IOEL TWA	260 mg/m³		
Remark Skin	IOEL TWA [ppm]	200 ppm		
	Remark	Skin		

20-09-21 (Revision date) EN (English) 5/17

Item Numbers: 01750-1101, 01750-1105 Page 5 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

methanol (67-56-1)		
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
Netherlands - Occupational Exposure Limits		
Local name	Methanol	
TGG-8u (OEL TWA)	133 mg/m³	
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.	
Regulatory reference	Arbeidsomstandighedenregeling 2021	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Approved respirator.

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. CEN: EN 340; EN 369; EN 465

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF EN 374 or equivalent)

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Polyvinylchloride (PVC), Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.11		EN ISO 374

20-09-21 (Revision date) EN (English) 6/17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.3. Respiratory protection

Respiratory protection:

Wear respiratory protection. EN 143

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask	Type A - High-boiling (>65 °C) organic compounds	If conc. in air > exposure limit	EN 143

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product. Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour Colourless. Odour characteristic. Odour threshold Not available Melting point Not available Freezing point Not available Boiling point Not available Not available Flammability Explosive limits Not available Lower explosive limit (LEL) Not available Upper explosive limit (UEL) Not available Flash point Not available Auto-ignition temperature Not available Not available Decomposition temperature рΗ Not available Viscosity, kinematic Not available Solubility Not available Partition coefficient n-octanol/water (Log Kow) Not available Not available Vapour pressure Vapour pressure at 50 °C Not available Density Not available Relative density Not available Relative vapour density at 20 °C Not available Particle size Not applicable Particle size distribution Not applicable Particle shape Not applicable Particle aspect ratio Not applicable Not applicable Particle aggregation state Particle agglomeration state Not applicable Particle specific surface area : Not applicable : Not applicable Particle dustiness

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

20-09-21 (Revision date) EN (English) 7/17

Item Numbers: 01750-1101, 01750-1105 Page 7 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use. Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Keep away from heat and direct sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong bases. Strong acids. Strong oxidizing agents. Strong oxidation agent.

10.6. Hazardous decomposition products

Combustion generates: Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

, , , , , , , , , , , , , , , , , , , ,	, ,		
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
ethanol; ethyl alcohol (64-17-5)			
LD50 oral rat	6200 mg/kg		
LD50 dermal rabbit	20000 mg/kg		
LC50 Inhalation - Rat (Vapours)	95,6 mg/l/4h		
Hydrocarbons, C9, aromatics (64742-95-6)			
LD50 oral rat	3592 mg/kg		

LD50 dermal rabbit > 3160 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified STOT-single exposure : May cause drowsiness or dizziness.

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)	
STOT-single exposure	May cause drowsiness or dizziness.

20-09-21 (Revision date) EN (English) 8/17

Item Numbers: 01750-1101, 01750-1105 Page 8 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetone; propan-2-one; propanone (67-64-1)		
STOT-single exposure	May cause drowsiness or dizziness.	
methanol (67-56-1)		
STOT-single exposure	Causes damage to organs.	
Hydrocarbons, C9, aromatics (64742-95-6)		
STOT-single exposure May cause drowsiness or dizziness. May cause respiratory irritation.		
STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.		

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)		
· · · · · · · · · · · · · · · · · · ·	Causes damage to organs (central nervous system) through prolonged or repeated exposure.	

Aspiration hazard : May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Other information : Risk of aspiration pneumonia

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

. Not classified

Hazardous to the aquatic environment, long-term

: Toxic to aquatic life with long lasting effects.

(chronic)

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)		
EC50 - Crustacea [1]	7,8 g/l	
EC50 - Other aquatic organisms [1]	3,59 g/l	
ethanol; ethyl alcohol (64-17-5)		
LC50 - Fish [1]	8140 mg/l 48 h	
EC50 - Crustacea [1]	9268 – 14221 mg/l 48 h	
EC50 - Crustacea [2]	65 mg/l 72 h	
ErC50 algae	1450 mg/l 8 d	
Hydrocarbons, C9, aromatics (64742-95-6)		
LC50 - Fish [1]	9,2 mg/l	
EC50 - Crustacea [1]	3,2 mg/l	
ErC50 algae	2,6 – 2,9 mg/l	
NOEC chronic fish	1,23 mg/l	

12.2. Persistence and degradability

Retouching Varnish	
Persistence and degradability	Not established.

20-09-21 (Revision date) EN (English) 9/17

Item Numbers: 01750-1101, 01750-1105 Page 9 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethanol; ethyl alcohol (64-17-5)		
Biochemical oxygen demand (BOD)	0,9 - 1,67 g O ₂ /g substance	
BOD (% of ThOD)	94 % ThOD	

12.3. Bioaccumulative potential

Retouching Varnish	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Retouching Varnish

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

Additional information

- : Dispose in a safe manner in accordance with local/national regulations.
- : Handle empty containers with care because residual vapours are flammable. Empty containers should be taken for recycle, recovery or waste in accordance with local regulation. Flammable vapours may accumulate in the container.
- Ecology waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID		
14.1. UN number or ID n	14.1. UN number or ID number					
UN 1263 UN 1263		UN 1263	UN 1263	UN 1263		
14.2. UN proper shippin	14.2. UN proper shipping name					
PAINT / PAINT RELATED MATERIAL (CONTAINS; Hydrocarbons, C9-C12, n- alkanes, iso-alkanes, cyclic, aromatic compounds (2- 25%))	PAINT RELATED MATERIAL (CONTAINS; Hydrocarbons, C9-C12, n- alkanes, iso-alkanes, cyclic, aromatic compounds (2- 25%))	PAINT (CONTAINS; HYDROCARBONS, C9- C12, N-ALKANES, ISO- ALKANES, CYCLIC, AROMATIC COMPOUNDS (2-25%))	PAINT RELATED MATERIAL (CONTAINS; Hydrocarbons, C9-C12, n- alkanes, iso-alkanes, cyclic, aromatic compounds (2- 25%))	PAINT RELATED MATERIAL (CONTAINS; Hydrocarbons, C9-C12, n- alkanes, iso-alkanes, cyclic, aromatic compounds (2- 25%))		

20-09-21 (Revision date) EN (English) 10/17

Page 10 of 17 Item Numbers: 01750-1101, 01750-1105

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID	
Transport document description					
UN 1263 PAINT / PAINT RELATED MATERIAL (CONTAINS; Hydrocarbons, C9-C12, n- alkanes, iso-alkanes, cyclic, aromatic compounds (2- 25%)), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS UN 1263 PAINT RELATED MATERIAL (CONTAINS; Hydrocarbons, C9-C12, n- alkanes, iso-alkanes, cyclic, aromatic compounds (2- 25%)), 3, II 25%)), 3, II		UN 1263 PAINT (CONTAINS; HYDROCARBONS, C9- C12, N-ALKANES, ISO- ALKANES, CYCLIC, AROMATIC COMPOUNDS (2-25%)), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (CONTAINS; Hydrocarbons, C9-C12, n- alkanes, iso-alkanes, cyclic, aromatic compounds (2- 25%)), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (CONTAINS; Hydrocarbons, C9-C12, n- alkanes, iso-alkanes, cyclic, aromatic compounds (2- 25%)), 3, II, ENVIRONMENTALLY HAZARDOUS	
14.3. Transport hazard	class(es)				
3	3	3	3	3	
1 1 1 1 1 1 1 1 1 1	3	1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1	1	
14.4. Packing group	14.4. Packing group				
II	II	II	II	II	
14.5. Environmental hazards					
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: No	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	
No supplementary information	No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)

Special provisions (ADR) : 163, 367, 640D, 650

Limited quantities (ADR) : 51 Excepted quantities (ADR) : E2

: P001, IBC02, R001 Packing instructions (ADR)

Special packing provisions (ADR) : PP1 : MP19 Mixed packing provisions (ADR) : T4 Portable tank and bulk container instructions (ADR)

Portable tank and bulk container special provisions

(ADR)

: LGBF Tank code (ADR) Vehicle for tank carriage : FL : 2 Transport category (ADR) Special provisions for carriage - Operation (ADR) S2, S20

Hazard identification number (Kemler No.) 33 Orange plates

Transport by sea

Tunnel restriction code (ADR)

Special provisions (IMDG) : 163, 367 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E2 Packing instructions (IMDG) : P001 : PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC02

20-09-21 (Revision date) EN (English)

: TP1, TP8, TP28

33 **1263**

: D/E

Page 11 of 17 Item Numbers: 01750-1101, 01750-1105

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP8, TP28

EmS-No. (Fire): F-EEmS-No. (Spillage): S-EStowage category (IMDG): B

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

MFAG-No : 127;128

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 163, 367, 640C, 650

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E2

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1

Special provisions (RID) : 163, 367, 640C, 650

Excepted quantities (RID) : E2
Packing instructions (RID) : P001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4

Portable tank and bulk container instructions (TIB) : T4

Portable tank and bulk container special provisions : TP1, TP8, TP28

(RID)

Tank codes for RID tanks (RID) : L1.5BN
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code Applicable on		
3(a)	Retouching Varnish; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%); acetone; propan-2-one; propanone; ethanol; ethyl alcohol; methanol; Hydrocarbons, C9, aromatics	
3(b) Retouching Varnish; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%); propan-2-one; propanone; methanol; Hydrocarbons, C9, aromatics		

20-09-21 (Revision date) EN (English) 12/17

Item Numbers: 01750-1101, 01750-1105 Page 12 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code Applicable on		
3(c)	Retouching Varnish; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%); Hydrocarbons, C9, aromatics	
40.	Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%); acetone; propan-2-one; propanone; ethanol; ethyl alcohol; methanol; Hydrocarbons, C9, aromatics	
69. methanol		

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name		Nomenclature	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-05/list_of_competent_authorities_and_national_contact_points_en.pdf

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5a FLAMMABLE LIQUIDS — Flammable liquids, Category 1, or — Flammable liquids Category 2 or 3 maintained at a temperature above their boiling point, or — Other liquids with a flash point ≤ 60 °C, maintained at a temperature above their boiling point	10	50
P5b FLAMMABLE LIQUIDS — Flammable liquids Category 2 or 3 where particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, or — Other liquids with a flash point ≤ 60 °C where particular processing conditions, such as high pressure or high temperature, may create major-accident hazards	50	200
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

SZW-lijst van kankerverwekkende stoffen : Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds

(16.3%), ethanol; ethyl alcohol are listed

SZW-lijst van mutagene stoffen : Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) is

SZW-lijst van reprotoxische stoffen - Borstvoeding

: ethanol; ethyl alcohol is listed

SZW-lijst van reprotoxische stoffen -

: ethanol; ethyl alcohol is listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling : ethanol; ethyl alcohol is listed

20-09-21 (Revision date) EN (English) 13/17

Page 13 of 17 Item Numbers: 01750-1101, 01750-1105

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes				
Section	Changed item	Change	Comments	
	Supersedes	Modified		
	Revision date	Modified		
	SDS EU format	Modified		
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified		
2.1	Adverse physicochemical, human health and environmental effects	Modified		
2.2	Hazard statements (CLP)	Modified		
2.2	Precautionary statements (CLP)	Modified		
4.1	First-aid measures general	Modified		
4.1	First-aid measures after skin contact	Modified		
4.1	First-aid measures after eye contact	Modified		
4.2	Symptoms/effects after skin contact	Modified		
5.1	Suitable extinguishing media	Modified		
5.2	Hazardous decomposition products in case of fire	Modified		
5.3	Protection during firefighting	Modified		
5.3	Firefighting instructions	Added		
6.1	Protective equipment	Modified		
6.1	Emergency procedures	Modified		
6.1	Emergency procedures	Added		
6.2	Environmental precautions	Modified		
6.3	Methods for cleaning up	Modified		
6.4	Reference to other sections (8, 13)	Modified		
7.1	Hygiene measures	Modified		
7.1	Precautions for safe handling	Modified		
7.2	Storage conditions	Modified		
8.2	Skin and body protection	Modified		
8.2	Respiratory protection	Modified		
8.2	Personal protective equipment	Modified		
8.2	Other information	Modified		
10.1	Reactivity	Modified		
10.3	Possibility of hazardous reactions	Modified		
10.4	Conditions to avoid	Modified		
10.5	Incompatible materials	Modified		

20-09-21 (Revision date) EN (English) 14/17

Item Numbers: 01750-1101, 01750-1105 Page 14 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes				
Section	Changed item	Change	Comments	
12.2	Persistence and degradability Added			
12.3	Bioaccumulative potential	Added		
13.1	Additional information	Modified		
13.1	Waste disposal recommendations	Added		
15.1	REACH Annex XVII	Added		
16	Data sources	Modified		
16	Abbreviations and acronyms			

Abbreviations and acronyms:			
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
CAS	CAS (Chemical Abstracts Service) number		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
	CMR: Carcinogeen, Mutageen, Reprotoxisch		
	CSA: Chemical Safety Assessment		
	CSR: Chemical Safety Report		
DNEL	Derived-No Effect Level		
	EC50: Median Effective Concentration (required to induce a 50% effect)		
	EINECS: European Inventory of Existing Commercial Chemical Substances		
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals		
	IATA: International Air Transport Association		
	IMDG: International Maritime Code for Dangerous Goods		
	LC50: Lethal concentration, 50 percent		
	LD50: Lethal dose, 50 percent		
PBT	Persistent Bioaccumulative Toxic		
	PNEC: Predicted No Effect Concentration (for environment)		
	REACH: Registration, Evaluation and Authorisation of Chemical substances		
	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)		
	SVHC: Substances of Very High Concern		
vPvB	Very Persistent and Very Bioaccumulative		
SDS	Safety Data Sheet		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006		
PBT	Persistent Bioaccumulative Toxic		
vPvB	Very Persistent and Very Bioaccumulative		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		

20-09-21 (Revision date) EN (English) 15/17

Item Numbers: 01750-1101, 01750-1105 Page 15 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:			
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
LC50	Median lethal concentration		
LD50	Median lethal dose		
CAS	CAS (Chemical Abstracts Service) number		
	EG-nr.: EINECS- en ELINCS-number		
	EINECS: European Inventory of Existing Commercial Substances		
	OEL: Occupational Exposure Limit		

Data sources

Other information

- : ECHA (European Chemicals Agency). according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878.
- DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number).

Full text of H- and EUH-statements:			
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3		
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3		
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3		
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2		
Asp. Tox. 1	Aspiration hazard, Category 1		
Carc. Not classified	Carcinogenicity Not classified		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H301	Toxic if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H311	Toxic in contact with skin.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H335	May cause respiratory irritation.		

20-09-21 (Revision date) EN (English) 16/17

Item Numbers: 01750-1101, 01750-1105 Page 16 of 17

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:			
H336	May cause drowsiness or dizziness.		
H370	Causes damage to organs.		
H371	May cause damage to organs.		
H372	Causes damage to organs through prolonged or repeated exposure.		
H411	Toxic to aquatic life with long lasting effects.		
Muta. Not classified	Germ cell mutagenicity Not classified		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1		
STOT SE 1	Specific target organ toxicity — single exposure, Category 1		
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2		
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:				
Flam. Liq. 2	H225	Calculation method		
Skin Irrit. 2	H315	Calculation method		
STOT SE 3	H336	Calculation method		
STOT RE 1	H372	Calculation method		
Asp. Tox. 1	H304	Expert judgment		
Aquatic Chronic 2	H411	Calculation method		

The classification complies with

: ATP 12

This Safety Data Sheet is compiled by: ChemPros B.V. | +31(0)797676006 | info@chemprosbv.nl

20-09-21 (Revision date) EN (English) 17/17

Item Numbers: 01750-1101, 01750-1105 Page 17 of 17