

02007-1095

**SAFETY DATA SHEET**MATERIAL NAME: **ATELIER UNLOCKING FORMULA**LAST REVISION: **3/08/2021****SECTION 1 – IDENTIFICATION****Material Name**

ATELIER UNLOCKING FORMULA

**Product Number**

Various

**Manufacturer Information**

Chroma, Inc.

Airport Industrial Park

205 Bucky Drive

Lititz, Pennsylvania 17543

U.S.A.

Phone: 717-626-8866; 1-800-257-8278

Fax: 717-626-9292

Email: jhirneisen@chromaonline.com; infousa@chromaonline.com

For Health Emergencies Call the Poison Control Center: 1-888-516-2502

Seek medical assistance for further treatment, observation and support, if necessary.

**SECTION 2 – HAZARDS IDENTIFICATION****Physical Hazards**

Flammable Liquids

Category 2

**Health Hazards**

Serious eye damage / eye irritation

Category 2A

Specific target organ toxicity, single exposure

Category 3 narcotic effects

**Environmental Hazards**

Not classified.

**OSHA Defined Hazards**

Not classified.

**Label Elements****Signal Word**

Danger

**Hazard Statement**Highly flammable liquid and vapor. Causes serious eye irritation.  
May cause drowsiness or dizziness.

All Sizes – Atelier Unlocking Formula

Page 1 of 12 SDS Date 03/21

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

**Precautionary Statement**

- Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear protective gloves/eye protection/face protection.
- Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
- Storage** Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
- Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**Supplemental Information**

None.

**SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Ingredient</b>	<b>CAS #</b>	<b>PEL/TLV (MG/M#)</b>	<b>Max % Weight</b>	<b>NTP</b>	<b>IARC</b>
PROPAN-2-OL	67-63-0		Proprietary		

**SECTION 4 – FIRST AID MEASURES**

- Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor / physician if you feel unwell.
- Skin Contact** Take off immediately all contaminated clothing. Rinse skin with water / shower. Get medical attention if irritation develops and persists.
- Eye Contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
- Ingestion** Rinse mouth. Get medical attention if symptoms occur.

**Most important symptoms / effects, acute and delayed**

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

All Sizes – Atelier Unlocking Formula

Page 2 of 12 SDS Date 03/21

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

**Indication of immediate medical attention and special treatment needed**

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General Information**

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Wash contaminated clothing before reuse.

**SECTION 5 – FIRE FIGHTING MEASURES****Suitable Extinguishing Media**

Alcohol resistant foam. Water fog. Carbon dioxide (CO<sub>2</sub>). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

**Unsuitable Extinguishing Media**

Do not use water jet as an extinguisher, as this will spread the fire.

**Specific Hazards arising from the Chemical**

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

**Special Protective Equipment and Precautions for Firefighters**

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire Fighting Equipment / Instructions**

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**Specific Methods**

Use standard firefighting procedures and consider the hazards of other involved materials.

**General Fire Hazards**

Highly flammable liquid and vapor.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

All Sizes – Atelier Unlocking Formula

Page 3 of 12 SDS Date 03/21

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

**Large Spills:** Stop the flow of material if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

**Small Spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g., cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

**SECTION 7 – HANDLING AND STORAGE****Precautions for Safe Handling**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to – mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

**Conditions for safe storage, including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Material	Type	Value
PROPAN-2-OL (CAS 67-63-0)	PEL	980 mg/m <sup>3</sup> 400 ppm

**US. ACGIH Threshold Limit Values**

Material	Type	Value
PROPAN-2-OL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Material	Type	Value
PROPAN-2-OL (CAS 67-63-0)	STEL	1225 mg/m <sup>3</sup> 500 ppm
	TWA	980 mg/m <sup>3</sup> 400 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Material	Value	Determinant	Specimen	Sampling Time
PROPAN-2-OL (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

**Individual protection measures, such as personal protective equipment****Eye / Face Protection**

Chemical respirator with organic vapor cartridge and full facepiece.

**Skin Protection / Hand Protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other**

Wear suitable protective clothing.

**Respirator Protection**

Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal Hazards**

Wear appropriate thermal protective clothing, when necessary.

All Sizes – Atelier Unlocking Formula

Page 5 of 12 SDS Date 03/21

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

**General Hygiene Considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES****Appearance**

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Colorless
<b>Odor</b>	ALCOHOL
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-127.3 °F (-88.5 °C) 999 °F (537.22 °C)
<b>Initial boiling point and boiling range</b>	180.5 °F (82.5 °C) 101.325 kPa
<b>Flash point</b>	53.6 °F (12.0 °C) Closed Cup 75.0 °F (23.9 °C) Open Cup 59.0 °F (15.0 °C)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	2.5 %
<b>Flammability limit - upper (%)</b>	12 %
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	6.05 kPa at 25 °C 6.05 kPa at 25 °C
<b>Vapor density</b>	2.1
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Miscible

<b>Partition coefficient (n-octanol/water)</b>	0.05
<b>Auto-ignition temperature</b>	750.2 °F (399 °C)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	6.55 lbs/gal estimated
<b>Dynamic viscosity</b>	2.1 mPa.s
<b>Dynamic viscosity temperature</b>	77 °F (25 °C)
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Flammable IB estimated
<b>Heat of combustion (NFPA 30B)</b>	27.4 kJ/g
<b>Molecular formula</b>	C3-H8-O
<b>Molecular weight</b>	60.1 g/mol
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	100 %
<b>Specific gravity</b>	0.79 at 20 °C
<b>VOC (Weight %)</b>	100 % 100 % EPA estimated

## SECTION 10 – STABILITY AND REACTIVITY

### Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

### Chemical Stability

Material is stable under normal conditions.

### Possibility of Hazardous Reactions

Hazardous polymerization does not occur.

### Conditions to Avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

### Incompatible Materials

Acids. Strong oxidizing agents. Isocyanates. Chlorine.

### Hazardous Decomposition Products

No hazardous decomposition products are known.

All Sizes – Atelier Unlocking Formula

Page 7 of 12 SDS Date 03/21

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

**SECTION 11 – TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

- Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting.
- Skin Contact** No adverse effects due to skin contact are expected.
- Eye Contact** Causes serious eye irritation.
- Ingestion** Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics**

Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Information on Toxicological Effects**

<b>Acute toxicity</b>	<b>Narcotic effects.</b>	
<b>Product</b>	<b>Species</b>	<b>Test Results</b>
PROPAN-2-OL (CAS 67-63-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	12800 mg/kg
<b>Oral</b>		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg
	Rabbit	5 03 g/kg
<b>Product</b>	<b>Species</b>	<b>Test Results</b>
	Rat	4.7 g/kg

\* Estimates for product may be based on additional component data not shown.

- Skin Corrosion / Irritation** Prolonged skin contact may cause temporary irritation.
- Serious Eye Damage / Eye Irritation** Causes serious eye irritation.

**Respiratory or Skin Sensitization**

- Respiratory Sensitization** Not a respiratory sensitizer.
- Skin Sensitization** This product is not expected to cause skin sensitization.

- Germ Cell Mutagenicity** No data available to indicate product or any components present at greater than 0.1 % are mutagenic or genotoxic.

- Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**  
Not Listed.

**Reproductive Toxicity**

This product is not expected to cause reproductive or developmental effects.

All Sizes – Atelier Unlocking Formula

Page 8 of 12 SDS Date 03/21

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.



**Specific Target Organ Toxicity – Single Exposure**

May cause drowsiness and dizziness.

**Specific Target Organ Toxicity – Repeated Exposure**

Not Classified.

**Aspiration Hazard**

Not an aspiration hazard.

**SECTION 12 – ECOLOGICAL INFORMATION****Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species	Test Results
PROPAN-2-OL (CAS 67-63-0)		
<b>Aquatic</b>		
Fish	LC50 Bluegill ( <i>Lepomis macrochirus</i> )	> 1 400 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistent and Degradability**

No data is available on the degradability of this product.

**Bioaccumulative Potential****Partition coefficient n-octanol / water (log Know)**

0.05

**Mobility in Soil**

No data is available.

**Other Adverse Effects**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**SECTION 13 – DISPOSAL CONSIDERATIONS****Disposal Instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local Disposal Regulation**

Dispose in accordance with all applicable regulations.

**Hazardous Waste Code**

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from Residues / Unused Products**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated Packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

All Sizes – Atelier Unlocking Formula

Page 9 of 12 SDS Date 03/21

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

**SECTION 14 – TRANSPORT INFORMATION****DOT**

**UN Number** UN1219  
**UN Proper Shipping Name** ISOPROPANOL

**Transport Hazard Class(es)**

**Class** 3

**Subsidiary Risk** -

**Packaging Group**

II

**Special precautions for User** Read safety instructions, SDS and emergency procedures before handling.

**ERG Number** 129

DOT information on packaging may be different from that listed.

**DOT****SECTION 15 – REGULATORY INFORMATION****US Federal Regulation**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**SARA 304 Emergency Release Notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard Categories** Immediate Hazard – Yes  
 Delayed Hazard – No  
 Fire Hazard – Yes  
 Pressure Hazard – No  
 Reactivity Hazard – No

**SARA 302 Extremely Hazardous Substance**

Not listed.

**SARA 311 / 312 Hazardous Chemical**

Yes

All Sizes – Atelier Unlocking Formula

Page 10 of 12 SDS Date 03/21

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

**SARA 313 (TRI reporting)**

Not regulated.

**Other Federal Regulation****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112® Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)**

Not regulated

**US State Regulation****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs. Tit. 22, 69502.3, subd. (a))**

PROPAN-2-OL (CAS 67-63-0)

**US. Massachusetts RTK - Substance List**

PROPAN-2-OL (CAS 67-63-0)

**US. New Jersey Worker and Community Right-to-Know Act**

PROPAN-2-OL (CAS 67-63-0)

**US. Pennsylvania Worker and Community Right-to-Know Law**

PROPAN-2-OL (CAS 67-63-0)

**US. Rhode Island RTK**

PROPAN-2-OL (CAS 67-63-0)

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**SECTION 16 – OTHER INFORMATION**

**HMIS Ratings**           Health: 2  
                                   Flammability: 3  
                                   Physical hazard: 0

**NFPA Ratings**           Health: 2  
                                   Flammability: 3  
                                   Instability: 0

All information the same for all sizes.

This product does not contain egg, dairy, wheat, gluten, soy or peanut products, by-products or derivatives.

This product does not contain latex materials or animal derived ingredients.