

21733-1002

SAFETY DATA SHEET.

Issuing date 20-Jul-2021

Revision Date 22-Jun-2022

Version 1.02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product identifier****Product name** TEXTURED FIXATIVE**Recommended use of the chemical and restrictions on use****Product code** F04391**Product Type** Extremely Flammable Aerosol
Synonyms None**Supplier's details****Recommended Use** Color Pencil Fixative.**Uses advised against** No information available**Manufactured For:**
Brush And Pencil, LLC
526 Kingwood Drive, #193
Kingwood, TX 77339
www.BrushAndPencil.com**Manufacturer**
American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126
Phone:(734) 721-5930**Emergency telephone number**
Chemical Emergency Phone Number CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

2. HAZARDS IDENTIFICATION**Classification**

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Serious eye damage/eye irritation	Category 2B
Skin Sensitization	Category 1
Reproductive Toxicity	Category 2
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements**Emergency Overview****DANGER****Hazard Statements**

Causes eye irritation.
 May cause an allergic skin reaction.
 Suspected of damaging fertility or the unborn child
 Extremely Flammable Aerosol
 Contains gas under pressure; may explode if heated

**Appearance** Hazy**Physical state** Aerosol**Odor** Mild**Precautionary Statements - Prevention**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Wear protective gloves, protective clothing, eye protection, face protection.
 Wash face, hands and any exposed skin thoroughly after handling.
 Avoid breathing fumes, gas, mist, vapors, spray.
 Contaminated work clothing must not be allowed out of the workplace
 Keep away from heat, sparks, open flames, hot surfaces - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

If exposed or concerned: Call a poison center, doctor.
 Specific treatment (see first aid on this label).
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice, attention
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical advice, attention
 Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up.
 Protect from sunlight. Store in a well-ventilated place

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
DIMETHYLETHER	115-10-6	30-40
ETHANOL	64-17-5	10-20
"TETRAMETHYL-5-DECYNE-4	126-86-3	0.1-1.0
HYDROXYPHENYL-BENZOTRIAZOLE	104810-47-1	0.1-1.0
HYDROXYPHENYL-BENZOTRIAZOLE	104810-48-2	0.1-1.0

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. Call a physician if irritation persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes eye irritation. May cause an allergic skin reaction if in direct contact with skin. May cause respiratory irritation. Harmful and may be fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data**Sensitivity to Mechanical Impact** none.**Sensitivity to Static Discharge** Yes.**Protective Equipment and Precautions for Firefighters**

In the event of fire and/or explosion do not breathe fumes. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal precautions** Use with adequate ventilation to keep the exposure levels below the OELS.**Environmental precautions****Environmental precautions** Vapors can accumulate in low areas. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Report spills as required by local and federal regulations.**Methods and materials for containment and cleaning up****Methods for Containment** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.**Methods for cleaning up** Pick up and transfer to properly labeled containers. Soak up with inert absorbant material. Clean contaminated surfact thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against atatic discharges.**7. HANDLING AND STORAGE****Precautions for safe handling****Advice on safe handling** Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.**Conditions for safe storage, including any incompatibilities****Technical measures/Storage conditions** Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.**Incompatible products** Strong acids, alkalis, oxidizing agents.**Aerosol Level** 1**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Guidelines** .

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
DIMETHYLETHER 115-10-6	STEL: 500 PPM TWA: 400PPM	TWX: 400 PPM TWA: 1200 mg/m ³	IDLH: 1900 PPM (10 % LEL)
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
ISOPROPYL ALCOHOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
SODIUM TETRABORATE DECAHYDRATE 1303-96-4	STEL: 6 mg/m ³ inhalable particulate matter TWA: 2 mg/m ³ inhalable particulate matter	(vacated) TWA: 10 mg/m ³	TWA: 5 mg/m ³
AMORPHOUS SILICA 7631-86-9	-	TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
ETHYLENE GLYCOL 107-21-1	STEL: 50 ppm vapor fraction STEL: 10 mg/m ³ inhalable particulate matter, aerosol only TWA: 25 ppm vapor fraction	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls**Engineering Measures**

Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Physical and chemical properties****Physical state**
Appearance
ColorAerosol
Hazy
Tan**Odor**
Odor Threshold

Mild

Property**pH**
Melting/freezing point**Values**
7.56
No information available**Remarks • Methods**
+/- 0.5

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

Boiling point/boiling range		
Flash Point	-41.1 °C / -42 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	0.854	
Water solubility	Soluble in Water	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

Other information

VOC Content(%)	54.02
MIR Value	0.56
MIR Coating Category	Art Fixative or Sealant (AFS) MIR MAX 1.75

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

Inhalation	Avoid inhaling vapors or mists. Harmful if inhaled. May cause irritation to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	May cause an allergic skin reaction.
Ingestion	Harmful and may be fatal if swallowed and enters airways and lungs.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIMETHYLETHER	-	-	= 164000 ppm (Rat) 4 h

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

115-10-6 ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
TETRAMETHYL-5-DECYNE-4 126-86-3	> 500 mg/kg (Rat)	> 1000 mg/kg (Rabbit)	> 20 mg/L (Rat) 1 h

Information on toxicological effects

Symptoms Causes eye irritation. May cause an allergic skin reaction if in direct contact with skin. May cause respiratory irritation. Harmful and may be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Eye damage/irritation Causes eye irritation.
Sensitization Known skin sensitizer.
Germ cell mutagenicity Not a germ cell mutagen.
Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.
Specific target organ systemic toxicity (single exposure) No information available.
Specific target organ systemic toxicity (repeated exposure) No information available.
Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects Eyes, Skin, Respiratory system, Central Nervous System, Liver, Blood, and Reproductive System.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 24161 mg/kg

ATEmix (dermal) 14904 mg/kg

ATEmix (inhalation-gas) 87069 mg/l

ATEmix (inhalation-dust/mist) 68.2 mg/l

ATEmix (inhalation-vapor) 637 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
DIMETHYLETHER 115-10-6	-	4.1 g/L LC50 Poecilia reticulata 96h semi-static	-	-
ETHANOL 64-17-5	-	12.0 - 16.0 mL/L LC50 Oncorhynchus mykiss 96h static 13400 - 15100 mg/L LC50 Pimephales promelas	-	9268 - 14221 mg/L LC50 Daphnia magna 48h 2 mg/L EC50 Daphnia magna 48h Static

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

		96h flow-through 100 mg/L LC50 Pimephales promelas 96h static		
--	--	---	--	--

Persistence and degradability**Bioaccumulation**

Chemical Name	log Pow
DIMETHYLETHER 115-10-6	-0.18
ETHANOL 64-17-5	-0.32

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment****Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Pressurized container: Do not pierce or burn, even after use. Do not re-use empty containers.

14. TRANSPORT INFORMATION**DOT Ground**

LIMITED QUANTITY

IATA

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD .QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD.QTY

15. REGULATORY INFORMATION**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
DIMETHYLETHER	X	X	X	X	X	X	X	X
ETHANOL	X	X	X	X	X	X	X	X
"TETRAMETHYL-5-D ECYNE-4	X	X	X	X	X	X	X	X
HYDROXYPHENYL-B ENZOTRIAZOLE	X	X	Not listed	X	X	X	X	X
HYDROXYPHENYL-B ENZOTRIAZOLE	X	X	Not listed	X	X	X	X	X

Legend:

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
CHINA - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
ISOPROPYL ALCOHOL - 67-63-0	67-63-0	0.1-1.0	1.0
ETHYLENE GLYCOL - 107-21-1	107-21-1	0.1-1.0	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Ethanol is ONLY considered a Proposition 65 chemical if ingested as an alcoholic beverage.

NO Warning required.

Ethylene Glycol CAS # 107-21-1) is considered a Proposition 65 chemical for developmental only when ingested. The purpose of this product is not for ingestion. There is no Proposition 65 warning required for Ethylene Glycol. It is in the product at <0.1%.

This product as supplied does not contain respirable particles of amorphous silica, (CAS# 7631-86-9). Such bound and non-respirable particles are not considered to be hazardous under Proposition 65. NO warning is required.



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65
ETHANOL - 64-17-5	*Ethyl alcohol in alcoholic beverages -For this application is not apply or

F04391 - TEXTURED FIXATIVE

Revision Date 22-Jun-2022

	considered a Proposition 65 chemical / Developmental / 0.1-1.0%
AMORPHOUS SILICA - 7631-86-9	Carcinogen (respirable particles / 0.1-1.0%
ETHYLENE GLYCOL - 107-21-1	Developmental (ingested)/<0.1%

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
DIMETHYLETHER 115-10-6	X	X	X
DEIONIZED WATER 7732-18-5			X
ETHANOL 64-17-5	X	X	X
ISOPROPYL ALCOHOL 67-63-0	X	X	X
SODIUM TETRABORATE DECAHYDRATE 1303-96-4	X	X	X
AMORPHOUS SILICA 7631-86-9		X	X
ETHYLENE GLYCOL 107-21-1	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B

Prepared By American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126

Issuing date 20-Jul-2021
Revision Date 22-Jun-2022
Revision Note

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet