

22383-XXXX



SAFETY DATA SHEET

Issuing Date 20-Mar-2018

Revision Date

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product identifier**Product Name **Dry Erase Marker****Other means of identification**Synonyms **Dry Erase Marker****Recommended use of the chemical and restrictions on use**

Recommended Use Dry Erase Boards

Uses advised against Dry Erase Boards

Details of the supplier of the safety data sheetSupplier Address **Tyne Mills Industrial Estate, Hexham,
Northumberland, NE46 1XL, ENGLAND****Emergency telephone number**Company Emergency Phone Number For Medical Emergencies call: +44 7887 612787
Transportation Emergencies,

Page Header

Revision Date

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Non under normal use conditions	

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Non under normal use conditions	Danger
Hazard statements Non under normal use conditions	
Appearance: Colored	Physical State: Stable
	Odor: Mild

Precautionary Statements - Prevention

Non under normal use conditions

Precautionary Statements - Response

Non under normal use conditions

Eyes

Non under normal use conditions

Skin

Non under normal use conditions

Precautionary Statements - Storage

N/A

Precautionary Statements - Disposal

N/A

Hazards not otherwise classified (HNOC)

N/A

Unknown Toxicity

N/A

Other information

N/A

Interactions with Other Chemicals

.N/A

Page Header

Revision Date

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade Secret
De-Natured Ethanol - inks	64-17-5	>7%	*
Iso-Propanol (Propan-2-ol) - inks	67-63-0	<1.5%	*
Pigments, Resins, Release Agents, Surfactants – inks		0.1-0.2% 1.5-3.0%	*
Plastic Materials (PP) – Marker Body	9003-07-0	90%	*
Polyester – Marker Tip	80595-68-2	1%	*

* The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Non under normal use conditions

Eye Contact Non under normal use conditions

Skin Contact Non under normal use conditions

Inhalation Non under normal use conditions

Ingestion Non under normal use conditions

Protection of First-aiders Non under normal use conditions

Most important symptoms and effects, both acute and delayed

Most Important Symptoms/Effects Non under normal use conditions

Indication of any immediate medical attention and special treatment needed

Notes to Physician Non under normal use conditions

Page Header

Revision Date

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

.Not Flammable

Unsuitable Extinguishing Media

.N/A

Specific Hazards Arising from the Chemical

.N/A

Uniform Fire Code	N/A
-------------------	-----

Hazardous Combustion Products

.Not Combustion Products

Explosion Data

Sensitivity to Mechanical Impact	N/A
----------------------------------	-----

Sensitivity to Static Discharge	N/A
---------------------------------	-----

Protective Equipment and Precautions for Firefighters

.N/A

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Non under normal use conditions
----------------------	---------------------------------

Other Information

Environmental precautions

Environmental Precautions	Non under normal use conditions
---------------------------	---------------------------------

Methods and material for containment and cleaning up

Methods for Containment	N/A
-------------------------	-----

Methods for Cleaning Up	N/A
-------------------------	-----

7. HANDLING AND STORAGE

Precautions for safe handling

Handling	N/A
----------	-----

Conditions for safe storage, including any incompatibilities

Storage	Keep in normal warehouse / storage condition.
---------	---

Incompatible Products	.N/A
-----------------------	------

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines	N/A
---------------------	-----

Page Header

Revision Date

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines N/A

Appropriate engineering controls

Engineering Measures N/A

Individual protection measures, such as personal protective equipment

Eye/Face Protection Non under normal use conditions

Skin and Body Protection Non under normal use conditions

Respiratory Protection Non under normal use conditions

Hygiene Measures Non under normal use conditions

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Solid (Marker body) / Liquid (inks)		
Appearance	Marker	Odor	Characteristic odour of low alcohol solvent
Color	Color coded	Odor Threshold	N/A
<u>Property</u>	<u>Values</u>	<u>Remarks/ Method</u>	
pH	4.0 to 12.0	None known	
Melting/freezing point	No data available	None known	
Boiling Point/Range	No data available	None known	
Flash Point	No data available	None known	
Evaporation rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	5.81 kPa at 20 degrees C	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Soluble in water.	None known	
Solubility in other solvents	Yes	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive Properties	No data available	None known	
Oxidizing Properties	No data available		
<u>Other Information</u>			
Softening Point	No data available		
VOC Content (%)	No data available		
Particle Size	No data available		

Page Header

Revision Date

9. PHYSICAL AND CHEMICAL PROPERTIES**Particle Size Distribution** No data available**10. STABILITY AND REACTIVITY****Reactivity**

N/A

Chemical stability

Yes

Possibility of Hazardous Reactions

N/A

Hazardous Polymerization

N/A

Conditions to avoid

N/A

Incompatible materials

N/A

Hazardous Decomposition Products

N/A

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information****Inhalation** Non under normal use conditions**Eye Contact** Non under normal use conditions**Skin Contact** Non under normal use conditions**Ingestion** Non under normal use conditions**Component Information** Plastic, Polyester, Liquid

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation

Information on toxicological effects**Symptoms** Non under normal use conditions**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Sensitization** Non under normal use conditions**Mutagenic Effects** N/A

Page Header

Revision Date

Carcinogenicity

N/A

Chemical Name	ACGIH	IARC	NTP	OSHA

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive Toxicity

N/A

STOT - single exposure

N/A

STOT - repeated exposure

N/A

Chronic Toxicity

N/A

Target Organ Effects

N/A

Aspiration Hazard

N/A

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

6,565.00 mg/kg

ATEmix (dermal)

50,000.00 mg/kg (ATE)

ATEmix (inhalation-dust/mist)

50.00 mg/L

ATEmix (inhalation-vapor)

275.00ATEmix

12. ECOLOGICAL INFORMATION**Ecotoxicity**

N/A

Persistence and Degradability

Marker are readily biodegradable

N/A

Bioaccumulation**Other Adverse Effects**

Page Header

Revision Date

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods	Consider recycling
Contaminated Packaging	N/A

Chemical Name	California Hazardous Waste

14. TRANSPORT INFORMATION

<u>DOT</u>		
Proper Shipping Name	Non	
Hazard Class	Non	

<u>TDG</u>	N/A
-------------------	-----

<u>MEX</u>	N/A
-------------------	-----

<u>ICAO</u>	N/a
--------------------	-----

<u>IATA</u>		
Proper Shipping Name	Non	
Hazard Class	Non	

<u>IMDG/IMO</u>	
Hazard Class	Non

<u>RID</u>	N/A
-------------------	-----

<u>ADR</u>	N/A
-------------------	-----

<u>ADN</u>	N/A
-------------------	-----

15. REGULATORY INFORMATION

International Inventories

TSCA	Available
DSL	N/A

TSCA -
DSL/NDSL -

U.S. Federal Regulations**SARA 313**

Page Header

Revision Date

SARA 311/312 Hazard Categories

Acute Health Hazard	N/A
Chronic Health Hazard	N/A
Fire Hazard	N/A
Sudden Release of Pressure Hazard	N/A
Reactive Hazard	N/A

Clean Water Act

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
N/A				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
N/A			

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
N/A					

International Regulations**Mexico****National occupational exposure limits**

Chemical Name	Carcinogen Status	Exposure Limits
N/A		

Mexico - Occupational Exposure Limits - Carcinogens
A3 - Confirmed Animal Carcinogen

Canada

N/A

WHMIS Hazard Class

R11

16. OTHER INFORMATION

Page Header

Revision Date

16. OTHER INFORMATION

NFPA	Health Hazard	Flammability	Instability 0	Physical and Chemical Hazards -
N/A	N/A	N/A	N/A	N/A
HMIS	Health Hazard	Flammability	Physical Hazard 0	Personal Protection
N/A	N/A	N/A	N/A	N/A

Prepared By Michael Nelson

Issuing Date 20-Mar-2018

Revision Date 20-Mar-2018

Revision Note

General Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 1

1.0 – Identification of the substance/mixture and of the company/undertaking

1.1 – Product Identification

Trade name: Fluorescent Dry Erase, Fluorescent Paint Marker
 Substance name: n/a
 Index No: n/a
 CAS-No: n/a
 EC-No: n/a

1.2 – Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: Preparation for use in writing instruments
 Recommended restrictions on use: No information available

1.3 – Details of the supplier of the safety data sheet





Company: Multichem Limited, Tyne Mills Industrial Estate, Hexham, Northumberland NE46 1XL, UK
 Telephone: +44 1434 606 085
 Fax: +44 1434 601 804
 e-mail: mail@multichem.net

1.4 – Emergency telephone number

+44 7887 612 787

2.0 - Hazards Identification

2.1 – Classification of the substance or mixture

Regulation (EC) No. 1272/2008			
Hazard class	Hazard category	Target organs	Hazard statements
Flammable liquids	2	n/a	H225 
Skin sensitization	1	skin	H317 
Serious eye damage/eye irritation	2	eyes	H319 
Aquatic chronic	3	n/a	H412 

For the full text of the H-Statements mentioned in this Section, see Section 16.

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 2

Most important adverse effects: Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2 – Label Elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard Symbols:



Signal word:

DANGER

Hazard statements:

H225 Highly flammable liquid and vapour
 H317 May cause an allergic skin reaction
 H319 Causes serious eye irritation
 H412 Harmful to aquatic life with long lasting effects

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
 P233 Keep container tightly closed
 P240 Ground/bond container and receiving equipment
 P243 Take precautionary measures against static discharge
 P273 Avoid release to the environment
 P280 Wear protective gloves/protective clothing/eye protection
 P302/P352 IF ON SKIN: wash with plenty of soap and water
 P305/P351/P338 IF IN EYES: rinse cautiously with water for several minutes
 Remove contact lenses, if present and easy to do. Continue rinsing
 P337/P313 If eye irritation persists: get medical advice/attention
 P403/P235 Store in a well-ventilated place. Keep cool.

2.3 – Other hazards

No other information available.

3.0 - Composition / information on ingredients

3.1 – Substances

Chemical nature: mixture

Chemical name	REACH Reg. No.	CAS No.	EC No.	Amount (%)
Ethanol	01-2119457610-43	64-17-5	200-578-6	<75%
Propan-2-ol	01-2119457558-25	67-63-0	200-661-7	10%
Fluorescent pigment				15%

Chemical name	Classification according to Regulation (EC) No. 1272/2008
Ethanol	H225 (2), H319 (2)
Propan-2-ol	H225 (2), H319 (2), H336 (3)
Fluorescent pigment	H317 (1), H319 (2), H411 (2)

For the full text of the H-Statements mentioned in this Section, see Section 16.

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 3

4.0 - Description of first aid measures

4.1 – Description of first aid measures

General advice:	Take off all contaminated clothing immediately
In case of inhalation:	Remove to fresh air. If symptoms persist, seek medical advice. If unconscious place in recovery position
In case of skin contact:	Wash off with plenty of water. If skin irritation persists, seek medical advice
In case of eye contact:	Rinse thoroughly with plenty of water, also under the eyelids. Consult an eye specialist immediately

4.2 – Most important symptoms and effects, both acute and delayed

No information available

4.3 - Indication of immediate medical attention and special treatment needed

Treat symptomatically. No further information available

5.0 – Firefighting measures

5.1 – Extinguishing media

Suitable extinguishing media:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide
Unsuitable extinguishing media:	High volume water jet

5.2 – Special hazards arising from the substance or mixture

Specific hazards during fire-fighting:	Highly flammable. Vapours may form explosive mixtures with air. In case of fire hazardous decomposition products may be produced, such as carbon monoxide (CO) and carbon dioxide (CO ₂).
--	---

5.3 - Advice for firefighter

Special protective equipment for firefighters:	In the event of fire, wear self-contained breathing apparatus. Wear appropriate body protection (full protective suit)
Further information:	Cool closed containers exposed to fire with water spray. Heating will cause a pressure rise – with risk of bursting. Collect contaminated fire extinguishing water separately. This must not be discharged into drains

6.0 – Accidental release measures

6.1 – Personal precautions, protective equipment and emergency procedures

Personal precautions:	Use personal protective equipment. Provide adequate ventilation. Keep away from heat and sources of ignition. Avoid contact with skin and eyes. Do not breathe vapours.
-----------------------	---

6.2 – Environmental precautions

Environmental precautions:	Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration
----------------------------	---

6.3 – Methods and materials for containment and cleaning up

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 4

Procedure: Contain spillage, and then collect with non-combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see Section 13)

Further information: Treat recovered material as described in Section 13

6.4 – Reference to other sections

For personal protection see Section 8

7.0 – Handling and storage

7.1 – Precautions for safe handling

Advice on safe handling: Keep container tightly closed. Ensure adequate ventilation. Avoid contact with skin and eyes. Do not breathe vapours. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity

Hygiene measures: Keep away from food, drink and animal feeding stuffs. Smoking, eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of the working day. Take off all contaminated clothing immediately. Avoid contact with skin and eyes. Do not breathe vapours of spray mist

7.2 – Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers: Keep in an area equipped with solvent resistant flooring. Store in original container

Advice on protection against fire and explosion: Combustible liquid. Keep away from sources of ignition – no smoking. Take measures to prevent the build-up of electrostatic charge. Vapours may form explosive mixtures in air. Use only in an area containing explosion proof equipment

Further information on storage conditions: Keep tightly closed in a dry and cool place. Keep in a well-ventilated place. Keep away from heat. Keep away from direct sunlight

Advice on common storage: Incompatible with oxidizing agents. Keep away from food, drink and animal feeding stuffs

7.3 – Specific end uses

Specific uses(s): No information available

8.0 – Exposure controls/personal protection

8.1 – Control parameters

Ethanol (CAS No. 64-17-5)

ACGIH TLV (US, 4/2014) : STEL: 1000 ppm 15 minutes.
OSHA PEL (US, 2/2013) : TWA: 1000 ppm 8hours.
TWA: 1900 mg.m-3 8 hours.
NIOSH REL (US, 10/2013) : TWA: 1000 ppm 10 hours.
TWA: 1900 mg.m-3 10 hours.
OSHA PEL 1989 (US, 3/1989): TWA: 1000 ppm 8 hours.
TWA: 1900 mg.m-3 8 hours.

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 5

	TWA: 980 mg.m-3 8 hours
Propan-2-ol (CAS No. 67-63-0)	
ACGIH TLV (US, 3/2012) :	TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.
OSHA PEL 1989 (US, 3/1989) :	TWA: 400 ppm 8 hours. TWA: 980 mg.m-3 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg.m-3 15 minutes.
NIOSH REL (US, 1/2013) :	TWA: 400 ppm 10 hours. TWA: 980 mg.m-3 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg.m-3 15 minutes.
OSHA PEL (US, 6/2010) :	TWA: 400 ppm 8 hours.

8.2 – Exposure controls

Engineering measures:	Refer to protective measures listed in Sections 7 and 8
Respiratory protection :	Required, if exposure limit is exceeded (e.g. OEL). Respirator with a gas filter. Recommended filter type: A
Hand protection:	Wear suitable gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Protective gloves should be replaced at first signs of wear Butyl rubber, 0.5 mm, Fluorocarbon rubber, 0.4 mm
Eye protection:	Tight fitting safety goggles
Skin and body protection:	Wear suitable protective clothing
Environmental protection:	Do not let product enter drains. If the product contaminates rivers and lakes or drains inform respective authorities

9.0 – Physical and chemical properties

9.1 – Information on basic physical and chemical properties

Appearance:	Various colours, liquid
Odour:	Alcohol-like
Odour threshold:	No data available
pH:	No data available
Melting point / freezing point:	-114.5°C
Initial boiling point/boiling range:	78.3°C
Flash point:	12°C
Evaporation rate:	No data available
Flammability:	No data available
Upper/lower flammability or explosive limits:	15% (V), 3.5% (V)
Vapour pressure:	No data available
Vapour density:	No data available

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 6

Relative density:	No data available
Solubility:	Miscible in water, readily miscible with solvents
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	425°C
Decomposition temperature:	No data available
Viscosity:	No data available
Explosive properties:	No data available
Oxidising properties:	No data available

9.2 – Other information

No further information available

10.0 – Stability and reactivity

10.1 – Reactivity

Advice: Stable under recommended storage conditions

10.2 – Chemical Stability

Advice: Stable under normal conditions

10.3 – Possibility of hazardous reactions

Hazardous reactions: No information available

10.4 – Conditions to avoid

Conditions to avoid: Heat, flames and sparks

10.5 – Incompatible materials

Materials to avoid: Alkali metals, alkaline earth metals, strong oxidizing agents, nitric acid, sulphuric acid, peroxides (e.g. hydrogen peroxide)

10.6 – Hazardous decomposition products

Hazardous decomposition: Under fire conditions: carbon monoxide (CO), carbon dioxide (CO₂)

11.0 – Toxicological information

11.1 – Information on toxicological effects

Ethanol (CAS No. 64-17-5)

Oral

Value type: LD50
Value: >2000 mg/Kg
Species: rat

Inhalation

Value type: LC50
Value: >20 mg/L
Exposure time: 4 h
Species: mouse

Dermal

Value type: LD50
Value: >2000 mg/Kg

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 7

Species: rabbit

Propan-2-ol (CAS No. 67-63-0)

Oral

Value type: LD50

Value: 5840 mg/Kg

Species: rat

Inhalation

Value type: LC50

Value: >25 mg/L

Exposure time: 6 h

Species: rat

Dermal

Value type: LD50

Value: >13900 mg/Kg

Species: rabbit

12.0 – Ecological information

12.1 – Toxicity

Ethanol (CAS No 64-17-5)

Fish

Species: Pimephales Promelas (Fathead Minnow)

Value type: LC50

Value: 15300 mg/L

Exposure time: 96 h

Daphnia and other aquatic invertebrates

Species: daphnia magna

Value type: EC50

Value: 12340 mg/L

Exposure time: 48 h

Algae

Species: Chlorella vulgaris (Fresh water algae)

Value type: EC50

Value: 275 mg/L

Exposure time: 72 h

Bacteria

Species: Paramecium caudatum

Value type: EC50

Value: 5800 mg/L

Exposure time: 4 h

Propan-2-ol (CAS No 67-63-0)

Fish

Species: Pimephales promelas (fathead minnow)

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 8

Value type:	LC50
Value:	9640 mg/L
Exposure time:	96 h
Daphnia and other aquatic invertebrates	
Species:	daphnia magna
Value type:	EC50
Value:	9714 mg/L
Exposure time:	24 h
Algae	
Species:	Scenedesmus subspicatus
Value type:	EC50
Value:	>100 mg/L
Exposure time:	72 h
Bacteria	
Value type:	EC50
Value:	>100 mg/L, no harming action

12.2 – Persistence and biodegradability

No data available

12.3 – Bioaccumulative potential

No data available

12.4 – Mobility in soil

Mobile in water environment

12.5 – Results of PBT and vPvB assessment

No data available

12.6 – Other adverse effects

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

13.0 – Disposal considerations

13.1 – Waste treatment methods

Product:	Disposal together with normal waste is not allowed. Special disposal required according to local regulations. Do not empty into drains. Contact waste disposal services
Contaminated packaging:	Empty contaminated packaging thoroughly. They can be recycled after thorough and proper cleaning. Packaging that cannot be cleaned is to be disposed of in the same manner as the product. Do not burn, or use a cutting torch on the empty drum. Risk of explosion

14.0 – Transport Information

14.1 – UN Number

1993

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 9

14.2 – UN proper shipping name

ADR: Flammable Liquid n.o.s (contains ethanol)
RID: Flammable Liquid n.o.s (contains ethanol)
IMDG: Flammable Liquid n.o.s (contains ethanol)

14.3 – Transport hazardous class(es)

Labels/classification code/ hazard identification number /tunnel restriction code

ADR: 3; F1 ; 33 : (D/E)
RID: 3 ; F1 ; 33
IMDG : 3 ; (F-E, S-E)

14.4 – Packing group

ADR: II
RID: II
IMDG: II

14.5 – Environmental hazards

Labelling according to 5.2.1.8 ADR: No
Labelling according to 5.2.1.8 RID: No
Labelling according to 5.2.1.6.3 IMDG: No
Classification as environmentally hazardous according to 2.9.3 IMDG: No
Classified as 'P' according to 2.10 IMDG: No

14.6 – Special precautions for user

Not applicable

14.7 – Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG: Not applicable

15.0 – Regulatory Information

15.1 – Safety, health and environmental regulations/legislation specific for the substance or mixture

All components are REACH registered or are exempt from REACH registration
Our inks do not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57)
All components are listed on TSCA list of active substances

15.2 – Chemical safety assessment

No information available

16.0 – Other Information

Date of preparation: 05 November 2018

16.1 – Full text of H-Statements referred to under Sections 2 and 3

H225: Highly flammable liquid and vapour
H317: May cause an allergic skin reaction
H319: Causes serious eye irritation
H336: May cause drowsiness or dizziness

Safety Data Sheet according to the OSHA Hazard Communication Standard 29 CFR 1910. 1200

Fluorescent Dry Erase, Fluorescent Paint Marker

Data Sheet No: DS526

Version No: 001

Issue Date: 5th November 2018

Page 10

H411: Toxic to aquatic life with long lasting effects
H412: Harmful to aquatic life with long lasting effects

16.2 – Further information

Other: The information provided in this safety data sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship. The information contained in this safety data sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text

HS Tariff code: 32159070