

Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

| | |
|--|---|
| Identity (As used on Label and List) Orton Pyrometric Cones / Bars / TempCheks / Cone Plaques/Kiln wash | Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that. |
|--|---|

Section 1 – Product Identification

| | |
|--|---|
| Manufacturer's Name The Edward Orton Jr. Ceramic Foundation | Emergency Telephone Number (614) 895-2663 |
| Address (Number, Street, City, State, & Zip Code) 6991 Old 3C Highway, P.O. Box 2760, Westerville OH 43086 – 2760 | Telephone Number for Information (614) 895-2663 |
| Date Prepared 11-17-15 | Signature of Preparer (Optional) |

Section 2 – Hazardous Ingredients/Identity Information

| Hazardous Components (Specific Chemical Identity: Common Name(s)) | OSHA PEL | ACGIH TLV | Other Limits Recommended | (%) (Optional) |
|---|----------|----------------------|-----------------------------|-------------------|
| Plaques, TempCheks, TempTAB, Pyrometric Cone and Bar Numbers | | | | |
| 022, 021, 020, 019, 018, 017, 016, 015, 014, 013, 012, 011, 010, 09, 08, 07, 06, 05½, 05, 04, 03, 02, 01, 1, 2, 3, 4, 5, 5½, 6, 7, 8, 9, 10, 11, 12, 12½, 13, 13½, 14, 14½, 15, 15½, 16, 17, 18, 19, 20, 21, 23, 26, 27, 28, 29, 30, 31, 31½, 32, 32½, 33, 34, 35, 36 37, 38, 39, 40, 41 (Contain 2-65% Silica) | | | | |
| Silica as dust | | 10 mg/m ³ | | |

Section 3 – Physical/Chemical Characteristics

| | | | |
|---|-----|--|-----------|
| Boiling Point | N/A | Specific Gravity (H ₂ O = 1) | 1.8 – 2.0 |
| Vapor Pressure (mmHg) | N/A | Melting Point | N/A |
| Vapor Density (Air = 1) | N/A | Evaporation Rate (Butyl Acetate = 1) | N/A |
| Solubility in Water Nil | | | |
| Appearance and Color Solid-Shape of pyramid or rectangular shape – some products contain organic colors for aid in identification | | | |

Section 4 – Fire And Explosion Hazard Data

| | | | |
|---|--------------------------------|-------------------|-------------------|
| Flash Point (Method Used) N/A | Flammable Limits N/A | LEL N/A | UEL N/A |
| Extinguishing Media N/A | | | |
| Special Fire Fighting Procedures All products except those labeled Fast Fire or PCE contain 4-6% organic material that will oxidize above 300°F | | | |
| Unusual Fire and Explosion Hazards N/A | | | |

Section 5 – Reactivity Data

| | | | |
|---|-----------------------|---|----------------------------|
| Stability | Unstable | | Conditions to Avoid |
| | Stable | X | |
| Incompatibility (Materials to Avoid) N/A | | | |
| Hazardous Decomposition or Byproducts N/A | | | |
| Hazardous Polymerization | May Occur | | Conditions to Avoid |
| | Will not Occur | X | |

Section 6 – Health Hazard Data

| | | | |
|--|---------------------------|----------------------------------|---------------------------------------|
| Route(s) of Entry: | Inhalation? N/A | Skin? None Anticipated | Ingestion? None Anticipated |
| Health Hazards (Acute and Chronic) Product is non-hazardous when used as intended. Product should not be ground into dust or ingested. Product may contain crystalline silica, which may cause cancer, when inhaled, based on animal testing. | | | |
| Carcinogenicity: | NTP? No | IARC Monographs? No | OSHA Regulated? No |
| Signs and Symptoms of Exposure N/A | | | |
| Medical Conditions Generally Aggravated by Exposure N/A | | | |
| Emergency and First Aid Procedures If swallowed, get professional medical help | | | |

Section 7 – Precautions for Safe Handling and Use

| |
|--|
| Steps to be taken in Case Material is Released or Spilled No specific precautions |
| Waste Disposal Method Disposal must meet existing federal, state, and local environmental control for low soluble glass frit - titanium dioxide – silica |
| Precautions to Be Taken in Handling and Storing Keep out of reach of children. Wash hands after handling. |
| Other Precautions Organic components may produce harmful gases during firing, if not fully oxidized. Also other gases may be produced during firing, therefore, provide adequate ventilation to kiln or kiln area. |

Section 8 – Control Measures

| | | |
|--|------------------------------------|-----------------------|
| Respiratory Protection (Specify Type) N/A | | |
| Ventilation | Local Exhaust N/A | Special N/A |
| | Mechanical (General) N/A | Other N/A |
| Protective Gloves N/A | Eye Protection N/A | |
| Other Protective Clothing or Equipment No special requirements | | |
| Work/Hygienic Practices Wash hands after handling | | |

Section 9 - Physical and Chemical Properties

Appearance: Pyrometric Cones are three sided elongated pyramids 1" to 2" long. Cone plaques are rectangular clay forms ranging in Length, width, and height between 3"-4"x1"x1/2". TempCheks and TempTABS are ceramic disks 1 1/8" in diameter by 1/4" thick.

Odor: none

Vapor Pressure: none

PH: neutral

Melting point: above 1000°F

Freezing point: none

Flammability: none

Section 10 – Stability and Reactivity

Reactivity: None

Chemical Stability: Stable

Section 11 – Toxicological Information

Not toxic

Section 12 – Ecological Information

None available

Section 13 – Disposal Considerations

No precautions known

Section 14 – Transport Information

Non-hazardous

Section 15 – Regulatory Information

none

Section 16 – Other Information

Rev. 11-17-15

Product resources found at www.ortoceramic.com