




SAFETY DATA SHEET

1. Identification

Product identifier	42A PLASTERS	
Other means of identification		
SDS number	GP-42A	
Product code	GP-42A	
Synonyms	See Product List found in Section 16	
Recommended use	Industrial Plasters	
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	Specialized Building Products LLC	
Address	145 W. Meats Ave. Orange, CA 92865	
Telephone	Technical Information	714 279 1042
	(M)SDS Request	714 279 1042
E-mail	Not available.	
Emergency phone number	Chemtrec - Emergency	800.424.9300

2. Hazard(s) identification

Emergency overview	WARNING	
	Harmful if swallowed. Causes eye irritation. A natural chemical reaction during hardening (rehydration) develops sufficient heat that may cause severe burns in the event of contact with skin. These burns may possibly result in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Crushing, mixing, sanding, or otherwise working with this product may generate large amounts of dust. Dust can be irritating to the eyes.	
Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Category 4
	Serious eye damage/eye irritation	Category 2B
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Warning	
Hazard statement	Harmful if swallowed. Causes eye irritation.	
Precautionary statement		
Prevention	Wash thoroughly after handling. Do not eat, drink or smoke when using this product. After mixing with water, do not allow prolonged contact with skin until the product has completely hardened and cooled.	
Response	If swallowed: Rinse mouth. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
Storage	Store away from acids, phosphorus, diazomethane, and aluminum (at high temperatures). Protect from moisture.	
Disposal	Dispose of contents/container in accordance with applicable regulations.	

Material name: 42A PLASTERS

SDS US

GP-42A, Version #: 02, Revision date: 04-Mar-2015, Issue date: March-03-2015

Item Numbers: 33537-1008, 33537-1025

Page 1 of 9

Hazard(s) not otherwise classified (HNOC)	Heat develops as product hardens. May cause serious burns during hardening (rehydration) resulting in possible permanent injury.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM SULFATE HEMIHYDRATE		10034-76-1	60 - 100
CRYSTALLINE SILICA (QUARTZ)*		14808-60-7	1 - 5

Composition comments Gypsum (calcium sulfate) contains naturally occurring crystalline silica (quartz) which is listed as a lung carcinogen. See Section 8 for exposure information.

*The weight percent for crystalline silica represents total crystalline silica and not the respirable fraction. Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

4. First-aid measures

Inhalation	Remove to fresh air. If symptoms persist, get medical attention.
Skin contact	For skin contact, wash immediately with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. May result in obstruction and irritation if ingested. Get medical attention.
Most important symptoms/effects, acute and delayed	Causes eye irritation. Exposed individuals may experience eye tearing, redness, and discomfort. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Firefighters should wear full protective clothing including self contained breathing apparatus. Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep upwind. Keep unnecessary personnel away from the release. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust from the spilled material. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Use personal protection recommended in Section 8.
Methods and materials for containment and cleaning up	Sweep up or gather material and place in appropriate container for disposal. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Contain the spill, then place in a suitable container. Minimize dust generation. For waste disposal, see section 13 of the SDS.

Material name: 42A PLASTERS

SDS US

GP-42A Version #: 02 Revision date: 04-Mar-2015 Issue date: March-03-2015

Item Numbers: 33537-1008, 33537-1025

2 / 9
Page 2 of 9

Environmental precautions Keep out of drains, sewers, ditches, and waterways.

7. Handling and storage

Precautions for safe handling

Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Do not breathe dust. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. Do not taste or swallow. Use only in well-ventilated areas. Handle and open container with care. Wear appropriate NIOSH approved dust mask or filtering facepiece if dust is generated. Do not eat or drink while using the product. Wash hands before eating, drinking, or smoking.

Conditions for safe storage, including any incompatibilities

Keep the container tightly closed and dry. Store in a covered, dry, climate controlled area, away from incompatibles.

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table Z-3: Calculated Time Weighted Average (TWA) (mg/m3)

Components	Type	Value	Form
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	4.3 mg/m3	Total dust.
		1.4 mg/m3	Respirable.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
CALCIUM SULFATE HEMIHYDRATE (CAS 10034-76-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3, non-standard units

Components	Type	Value	Form
CALCIUM SULFATE HEMIHYDRATE (CAS 10034-76-1)	TWA	10 mg/m3	Inhalable fraction.
		0.025 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Exposure limits for CRYSTALLINE SILICA - The US OSHA exposure limits 8 hour TWA for CRYSTALLINE SILICA (QUARTZ) are calculated from the following equations: $30/(\%SiO_2+2)$ mg/m3 for total dust; and $10/(\%SiO_2+2)$ mg/m3 for the respirable fraction.

*Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

Appropriate engineering controls

When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses or goggles are recommended when using this product. Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection. Safety shower/eye wash fountain must be readily available in the workplace area (29 CFR 1910.151(c)).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other	Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151 (c)).
Respiratory protection	A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Powder
Physical state	Solid.
Form	Powder.
Color	Light grey to white
Odor	Low odor
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	2642 °F (1450 °C) estimated Not applicable
Initial boiling point and boiling range	Not applicable
Flash point	Not applicable
Evaporation rate	Not available
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable
Flammability limit - upper (%)	Not applicable
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	2.3 - 2.7
Solubility(ies)	
Solubility (water)	0.2 - 1 % at 22°C
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
Viscosity	Not available.
Other information	
Flash point class	Not flammable

10. Stability and reactivity

Reactivity	Reacts with water (normal condition of use).
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

Conditions to avoid	Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Exposure to moisture.
Incompatible materials	Acids. Phosphorus. Diazomethane. Aluminum (at high temperatures).
Hazardous decomposition products	May include and are not limited to: calcium oxide and sulfur dioxide.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Harmful if swallowed.
Inhalation	Prolonged inhalation may be harmful. Inhalation of dusts may cause respiratory irritation.
Skin contact	Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Eye contact	Causes eye irritation. Dust in the eyes will cause irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Upper respiratory tract irritation. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Product	Species	Test Results
42A PLASTERS (CAS Mixture)		
Acute		
<i>Oral</i>		
LD50	Rat	1664.2106 mg/kg estimated
Components	Species	Test Results
CALCIUM SULFATE HEMIHYDRATE (CAS 10034-76-1)		
Acute		
<i>Oral</i>		
LD50	Rat	> 1581 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Serious eye damage/eye irritation	Dust in the eyes will cause irritation. Causes eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not classified.
Skin sensitization	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	Not expected to be hazardous by OSHA criteria.

Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not classified.

Material name: 42A PLASTERS

SDS US

GP-42A Version #: 02 Revision date: 04-Mar-2015 Issue date: March-03-2015
Item Numbers: 33537-1008, 33537-1025

5 / 9
Page 5 of 9

Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Not hazardous under normal conditions of use.
Further information	*Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

12. Ecological information

Ecotoxicity Not considered to be harmful to aquatic life.

Product	Species	Test Results
42A PLASTERS (CAS Mixture)		
Aquatic		
Fish	LC50	Fish
		3137 mg/L, 96 Hours
Components	Species	Test Results
CALCIUM SULFATE HEMIHYDRATE (CAS 10034-76-1)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)
		> 1970 mg/l, 96 hours
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Zebra danio (<i>Danio rerio</i>)
		> 10000 mg/l, 96 Hours OECD SIDS

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
General information	This product is not regulated as a hazardous material by the United States (DOT) transportation regulations.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
-------------------------------	--

Material name: 42A PLASTERS

SDS US

GP-42A Version #: 02 Revision date: 04-Mar-2015 Issue date: March-03-2015

Item Numbers: 33537-1008, 33537-1025

6 / 9
Page 6 of 9

16. Other information, including date of preparation or last revision

Product list	BASECOAT PLASTER BR-170 DENSCAL® BASE BR-700 DENSCAL® BLEND BR-707 DENSCAL® IC LOW EXPANSION BR-704 DENSCAL® IC REGULAR BR-703 DENSCAL® OIL WELL BR-735, 736, 835 DENSCAL® SLOW SET BR-706 DENSCAL® WH BR-705 DENSITE® BASE BR-800 DENSITE® BASE - FINE GRIND BR-850 DENSITE® HL BR-853, NV-853 DENSITE® HS BR-854 DENSITE® K-11 BR-811 DENSITE® K-16 BR-816 DENSITE® K-4 BR-864 DENSITE® K-4 LE BR-865, NV-872 DENSITE® K-5 BR-805 DENSITE® K-6 BR-806 DENSITE® K-7 BR-807 DENSITE® K-7 WHITE BR-810 DENSITE® K-8 YELLOW BR-808 DENSITE® K-9 BR-809 DENSITE® MEDIUM LOW EXPANSION BR-815 DENSITE® RA BR-868 DENSITE® STATUARY PLASTER BR-856, NV-856 DRYCAST BR-863 GAUGING PLASTER - QUICK SET BR-155 GAUGING PLASTER - SLOW SET BR-158 GAUGING PLASTER - STABILIZED SET BR-231 IMPRESSION PLASTER BR-265 INDUSTRIAL MOLDING PLASTER BR-232 INDUSTRIAL MOLDING PLASTER - MEDIUM SET NV-233 LABORATORY PLASTER BR-264 MANUFACTURERS STUCCO - TUBED BR-244 MANUFACTURERS STUCCO - UNTUBED BR-240 MOLDING PLASTER - FAST SET NV-234 MOLDING PLASTER - SLOW SET BR-230, CNJ-230, NV-230 NOVEX #3 PLASTER BR-171 NS GROUT STATUARY BR-624 OIL WELL ULTRA DENSITE® BR-861 POTTERY PLASTER BR-251 POTTERY PLASTER K-55 BR-255 POTTERY PLASTER K-58 BR-658 POTTERY PLASTER K-59 BR-659 POTTERY PLASTER K-60 BR-660 POTTERY PLASTER K-62 BR-662 POTTERY PLASTER K-63 BR-663 PREMIX PLASTER BR-822 SAFE FILLER BR-241 STATUARY CASTING PLASTER BR-252, 646, 648, 649 STUCCO BR/CNJ/NV - 35, 46, 48, 53 SUPER ANHYDRITE BR-400 ULTRA DENSITE® BASE BR-860 ULTRA RH BR-862 WHITE MOLDING PLASTER BR-236, NV-236 WHITE MOLDING PLASTER (90 MINUTE MOLDING) NV-237 SUNFLOWER MOLDING PLASTER BR-233
Issue date	March-03-2015
Revision date	04-Mar-2015
Version #	02
HMIS® ratings	Health: 1 Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 1 Flammability: 0 Instability: 0

Material name: 42A PLASTERS

SDS US

GP-42A Version #: 02 Revision date: 04-Mar-2015 Issue date: March-03-2015

Item Numbers: 33537-1008, 33537-1025

Page 8 of 9

Disclaimer

This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.