
34130-1003(4)

Page 1 of 8



Glazing resin : part A resin - FDS011

Version 3.1 (03/05/2018) - Page 1/8

# pebeo

fabricant de couleurs SAFETY DATA SHEET (REACH regulation (EC) n° 1907/2006 - n° 2015/830) SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1.1. Product identifier Product name : Glazing resin : part A resin Product code : FDS011. 1.2. Relevant identified uses of the substance or mixture and uses advised against Paints & Varnishes for artists 1.3. Details of the supplier of the safety data sheet Registered company name : PEBEO SAS. Address : CS 10106.13881.GEMENOS CEDEX.FRANCE. Telephone : 33 (0) 4.42.32.08.08. Fax : 33 (0) 4.42.32.01.70. cdedeyne@pebeo.com www.pebeo.com 1.4. Emergency telephone number : 33 (0) 1.45.42.59.59. Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net . **SECTION 2 : HAZARDS IDENTIFICATION** 2.1. Classification of the substance or mixture In compliance with EC regulation No. 1272/2008 and its amendments. Skin irritation, Category 2 (Skin Irrit. 2, H315). Eye irritation, Category 2 (Eye Irrit. 2, H319). Skin sensitisation, Category 1 (Skin Sens. 1, H317). Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411). This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site. 2.2. Label elements In compliance with EC regulation No. 1272/2008 and its amendments. Hazard pictograms : GHS07 GHS09 Signal Word : WARNING Product identifiers : REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE 603-074-00-8 MOLECULAR WEIGHT < 700) TRIMETHYLOLPROPANE TRIGLYCIDYLETHER EC 608-489-8 Additional labeling : EUH205 Contains epoxy constituents. May produce an allergic reaction. Hazard statements : H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. Precautionary statements - General : P101 If medical advice is needed, have product container or label at hand. Page 1 of 8 Item Numbers: 34130-1004, 34130-1003 - Made under licence of European Label System® MSDS software from InfoDyne - http://www.infodyne.fr -

Page 2 of 8	3
-------------	---

Version 3.1 (03/05/2018) - Page 2/8

Name : %s -	%s	
PEBEO SAS		

## Glazing resin : part A resin - FDS011

## P102

Keep out of reach of children.

Precautionary statements - Prevention :

P280

Wear protective gloves/protective clothing/eye protection/face protection.

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

## **Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 603-074-00-8	GHS07, GHS09		50 <= x % < 100
CAS: 25068-38-6	Wng		
EC: 500-033-5	Eye Irrit. 2, H319		
REACH: 01-2119456619-26-0018	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
REACTION PRODUCT:	Aquatic Chronic 2, H411		
BISPHENOL-A-(EPICHLORHYDRIN) EPOXY			
RESIN (NUMBER AVERAGE MOLECULAR			
WEIGHT $< 700$ )			
CAS: 30499-70-8	GHS07		25 <= x % < 50
EC: 608-489-8	Wng		
	Skin Irrit. 2, H315		
TRIMETHYLOLPROPANE	Skin Sens. 1, H317		
TRIGLYCIDYLETHER	Eye Irrit. 2, H319		
	Aquatic Chronic 3, H412		

(Full text of H-phrases: see section 16)

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

## 4.1. Description of first aid measures

## In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

## In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

## In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed** No data available.

Name : %s -%s PEBEO SAS

Version 3.1 (03/05/2018) - Page 3/8

Glazing resin : part A resin - FDS011

CTION 5 : FIREFIGHTING MEASURES
Non-flammable.
1. Extinguishing media
uitable methods of extinction
In the event of a fire, use :
- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)
nsuitable methods of extinction
In the event of a fire, do not use :
- water jet
2. Special hazards arising from the substance or mixture
A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to l
Do not breathe in smoke.
In the event of a fire, the following may be formed :
- carbon monoxide (CO)
- carbon dioxide (CO2)
3. Advice for firefighters
No data available.
CTION 6 : ACCIDENTAL RELEASE MEASURES
1. Personal precautions, protective equipment and emergency procedures
Consult the safety measures listed under headings 7 and 8.

## For non first aid worker

Avoid any contact with the skin and eyes.

## For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

## **6.2.** Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

## 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

## **Fire prevention :**

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid skin and eye contact with this mixture.

Name : 9	‰s -	%
PEBEO	SAS	

## Glazing resin : part A resin - FDS011

Version 3.1 (03/05/2018) - Page 4/8

## Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

## 7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

## Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

## No data available.

## 8.2. Exposure controls

## Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

## - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Recommended properties : - Impervious gloves in accordance with standard EN374

## - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Name : %s -	%s
PEBEO SAS	

## Glazing resin : part A resin - FDS011

<b>&gt;SECTION 9 : PHYSICAL AND CHEMICAL PROP</b>	PERTIES	
9.1. Information on basic physical and chemical pr	operties	
General information :		
Physical state :	Viscous liquid.	
> Important health, safety and environmental inform	nation	
pH :	Not relevant.	
Boiling point/boiling range :	Not relevant.	
Flash point interval :	Not relevant.	
Vapour pressure (50°C) :	Not relevant.	
Density :	1.17	
Water solubility :	Insoluble.	
Melting point/melting range :	Not relevant.	

Not relevant.

Not relevant.

9.2. Other information

Self-ignition temperature :

## No data available.

## SECTION 10 : STABILITY AND REACTIVITY

Decomposition point/decomposition range :

10.1. Reactivity

No data available.

## 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

10.5. Incompatible materials

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

## SECTION 11 : TOXICOLOGICAL INFORMATION

## 11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

May cause an allergic reaction by skin contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and a respiratory tract sensitiser as well as an irritant.

Constituents with a low molecular weight irritate the eyes, mucous membranes and the skin

Repeated contact with the skin may cause irritation and hypersensitisation, possibly in combination with other epoxide compounds.

## 11.1.1. Substances

No toxicological data available for the substances.

## 11.1.2. Mixture

## **Respiratory or skin sensitisation :**

Contains epoxy compounds. May cause an allergic reaction.

Version 3.1 (03/05/2018) - Page 5/8

Name : %s -%s PEBEO SAS

## Glazing resin : part A resin - FDS011

Version 3.1 (03/05/2018) - Page 6/8

## SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

## 12.1. Toxicity

## 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

## No data available.

- 12.3. Bioaccumulative potential
- No data available.

12.4. Mobility in soil

No data available.

## 12.5. Results of PBT and vPvB assessment

## No data available.

12.6. Other adverse effects

No data available.

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

## 13.1. Waste treatment methods

Do not pour into drains or waterways.

## Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

## Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

20 01 27 \* paint, inks, adhesives and resins containing dangerous substances

15 01 02 plastic packaging

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

## 14.1. UN number

3082

## 14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(reaction product: bisphenol-a-(epichlorhydrin) epoxy resin (number average molecular weight < 700))

## 14.3. Transport hazard class(es)

- Classification :



Name : %s - %s PEBEO SAS Version 3.1 (03/05/2018) - Page 7/8

Glazing resin : part A resin - FDS011

## 14.4. Packing group

#### Ш

## 14.5. Environmental hazards

- Environmentally hazardous material :



## 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M6	III	9	90	5 L	274 335 375 601	E1	3	-
Not subject to this regulation if $Q \le 51/5 \text{ kg} (\text{ADR } 3.3.1 - \text{DS } 375)$										

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	9	-	III	5 L	F-A,S-F	274 335 969	E1
Not subject to this regulation if $Q \le 51/5$ kg (IMDG 3.3.1 - 2.10.2.7)							

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	9	-	III	964	450 L	964	450 L	A97	E1
								A158	
								A197	
	9	-	III	Y964	30 kg G	-	-	A97	E1
					-			A158	
								A197	

Not subject to this regulation if  $Q \le 51/5 \text{ kg}$  (IATA 4.4.4 - DS A197)

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

## **>SECTION 15 : REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

|> - Classification and labelling information included in section 2:

The following regulations have been used:


- EU Regulation No. 1272/2008 amended by EU Regulation No. 2017/776 (ATP 10)

- Container information:
- No data available.

- Particular provisions : No data available.

# - Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=2 Inflammability=3 Instability/Reactivity=1 Specific Risk=none



**15.2.** Chemical safety assessment No data available.

Version 3.1 (03/05/2018) - Page 8/8

Name : %s - %s PEBEO SAS

## Glazing resin : part A resin - FDS011

## **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

## Wording of the phrases mentioned in section 3 :

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

## Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.