43212-4712



SAFETY DATA SHEET

Published Date Revision Date Revision Number Nov-13-2023 Nov-13-2023

1. IDENTIFICATION

Product identifier

Product code 5561

Product name Brilliant Pale Gold

Product category 5500 Series SV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Industrial Printing Operations Recommended use

Details of the supplier of the safety data sheet

UNITED STATES UNITED KINGDOM Nazdar Company Nazdar Limited 8501 Hedge Lane Terrace Barton Road Shawnee, KS 66227 Tel: +001-913-422-1888 **Heaton Mersey**

Stockport, England SK4 3EG Tel: +44 161 442 2111 Tel: +001-800-677-4657

Fax: +001-913-422-2294

www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)
Carcinogenicity	Category 1B - (H350)
Aspiration hazard	Category 1 - (H304)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

Label elements



Hazard statements

H226 - Flammable liquid and vapor

Danger

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H350 - May cause cancer

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P201 - Obtain special instructions before use

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P403 + P235 - Store in a well-ventilated place. Keep cool

Hazards not otherwise classified (HNOC)

Toxic to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No.	Weight-%	Trade secret	Note
Solvent naphtha, petroleum, light aromatic	64742-95-6	10 - 30	*	
Petroleum distillates, hydrotreated light	64742-47-8	10 - 30	*	
Copper	7440-50-8	10 - 30	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	10 - 30	*	1
Ethylene glycol monopropyl ether	2807-30-9	5 - 10	*	
Resin	Not Available	5 - 10	*	
Naphtha, petroleum, hydrotreated heavy	64742-48-9	1 - 5	*	
1,3,5-Trimethylbenzene (constituent)	108-67-8	1 - 5	*	1
Zinc powder (stabilized)	7440-66-6	1 - 5	*	
Cumene (constituent)	98-82-8	1 - 5	*	1
Silicon dioxide, amorphous	7631-86-9	1 - 5	*	
1,2,3-Trimethylbenzene (constituent)	526-73-8	1 - 5	*	1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Note

4. FIRST-AID MEASURES

Description of first aid measures

General Advice Eye Contact

Show this safety data sheet to the doctor in attendance.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Inhalation Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

^{1.} Hazardous Constituent contained in Complex Substance(s) required for disclosure

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open

flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep

out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Page 3 / 12

Item Numbers: 43212-4712 Page 3 of 12

Exposure limits

Chemical name	ACGIH TLV	
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume	
1,2,4-Trimethylbenzene (constituent)	TWA: 10 ppm	
95-63-6 1,3,5-Trimethylbenzene (constituent)	TWA: 10 ppm	
108-67-8		
Cumene (constituent) 98-82-8	TWA: 5 ppm	
1,2,3-Trimethylbenzene (constituent) 526-73-8	TWA: 10 ppm	

Chemical name	OSHA PEL
Copper	TWA: 0.1 mg/m³ fume
7440-50-8	TWA: 1 mg/m³ dust and mist
Cumene (constituent)	TWA: 50 ppm
98-82-8	TWA: 245 mg/m ³
	Skin

Chemical name	OSHA PEL (vacated)
Copper 7440-50-8	TWA: 0.1 mg/m³ dust, fume, mist
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m³ Skin
Silicon dioxide, amorphous 7631-86-9	TWA: 6 mg/m ³

Chemical name	Ontario TWAEV
Copper	TWA: 0.2 mg/m³ fume
7440-50-8	TWA: 1 mg/m³ dust and mist
Ethylene glycol monopropyl ether	TWA: 25 ppm
2807-30-9	TWA: 110 mg/m ³
	Skin
Cumene (constituent)	TWA: 50 ppm
98-82-8	

Chemical name	Mexico OEL (TWA)
Copper	TWA/VLE-PPT: 0.2 mg/m³ fume
7440-50-8	TWA/VLE-PPT: 1 mg/m³ dust and mist
Cumene (constituent)	TWA/VLE-PPT: 50 ppm
98-82-8	

Appropriate engineering controls

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear safety glasses with s	side shields (or goggles	s). If splashes are likel	y to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as

appropriate, to prevent skin contact.

Hand Protection Chemical resistant protective gloves.

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6,

Item Numbers: 43212-4712 Page 4 of 12

> corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Appearance Colored Characteristic Odor Threshold No information available Odor

Values Remarks • Method **Property** No data available Melting Point / Freezing Point No information available No data available **Boiling Point / Boiling Range** 149 °C / 300

Flash Point °C / 102 Pensky Martens Closed Cup (PMCC)

No data available **Evaporation rate** Flammability Limit in Air

Upper flammability limit No data available Lower flammability limit No data available Vapor Pressure No data available Vapor Density No data available **Specific Gravity** 1.11

Water Solubility No data available Solubility in other solvents No data available

No data available Partition coefficient: n-octanol/water No information available **Autoignition Temperature** No data available Hyphen No data available

No data available Kinematic viscosity No data available Dynamic viscosity

Explosive Properties No data available **Oxidizing Properties** No data available

Other information

Photochemically Reactive Yes Weight Per Gallon (lbs/gal) 9.26

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
61.82	79.15	5.73	

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

InhalationSpecific test data for the substance or mixture is not available.Eye ContactSpecific test data for the substance or mixture is not available.Skin ContactSpecific test data for the substance or mixture is not available.IngestionSpecific test data for the substance or mixture is not available.

Chemical name	Oral LD50
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg (Rat)
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 3280 mg/kg (Rat)
Ethylene glycol monopropyl ether 2807-30-9	= 3089 mg/kg (Rat)
Naphtha, petroleum, hydrotreated heavy 64742-48-9	> 6000 mg/kg (Rat)
Zinc powder (stabilized) 7440-66-6	= 630 mg/kg (Rat)
Cumene (constituent) 98-82-8	= 1400 mg/kg (Rat)
Silicon dioxide, amorphous 7631-86-9	= 7900 mg/kg (Rat)

Chemical name	Dermal LD50
Solvent naphtha, petroleum, light aromatic	> 2000 mg/kg (Rabbit)
64742-95-6	
Petroleum distillates, hydrotreated light	> 2000 mg/kg (Rabbit)
64742-47-8	
1,2,4-Trimethylbenzene (constituent)	> 3160 mg/kg (Rabbit)
95-63-6	
Ethylene glycol monopropyl ether	= 870 mg/kg (Rabbit)
2807-30-9	
Naphtha, petroleum, hydrotreated heavy	> 5000 mg/kg (Rabbit)
64742-48-9	
Cumene (constituent)	= 12300 μL/kg (Rabbit)
98-82-8	
Silicon dioxide, amorphous	> 5000 mg/kg (Rabbit)
7631-86-9	

Chemical name	Inhalation LC50	
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 3400 ppm (Rat) 4 h	
Petroleum distillates, hydrotreated light 64742-47-8	> 5.2 mg/L (Rat)4 h	
Copper 7440-50-8	> 5.11 mg/L (Rat) 4 h	
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 18 g/m³ (Rat)4 h	
Ethylene glycol monopropyl ether 2807-30-9	= 1530 ppm (Rat) 7 h	
Naphtha, petroleum, hydrotreated heavy 64742-48-9	> 8500 mg/m³(Rat)4 h	
1,3,5-Trimethylbenzene (constituent) 108-67-8	= 24 g/m³ (Rat)4 h	
Cumene (constituent) 98-82-8	> 3577 ppm (Rat)6 h	
Silicon dioxide, amorphous 7631-86-9	> 58.8 mg/L (Rat)4 h	

Symptoms related to the physical, chemical and toxicological characteristics

Specific test data for the substance or mixture is not available. **Symptoms**

Delayed and immediate effects	as well as chronic effects from short and long-term exposure	
Skin corrosion/irritation	Specific test data for the substance or mixture is not available. Causes skin irritation (pain, redness and swelling). (based on components).	
Eye damage/irritation	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components).	
Irritation	Specific test data for the substance or mixture is not available.	
Corrosivity	Specific test data for the substance or mixture is not available.	
Sensitization	Specific test data for the substance or mixture is not available. May cause an allergic skin reaction. (based on components).	
Mutagenic Effects	Specific test data for the substance or mixture is not available.	
Carcinogenic effects	Specific test data for the substance or mixture is not available. May cause cancer. (based on components).	
Reproductive Effects	Specific test data for the substance or mixture is not available.	
STOT - single exposure	Specific test data for the substance or mixture is not available.	
STOT - repeated exposure	Specific test data for the substance or mixture is not available.	
Chronic Toxicity	Specific test data for the substance or mixture is not available	
Aspiration hazard	Specific test data for the substance or mixture is not available. May be fatal if swallowed and enters airways. (based on components).	
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.	
Chemical name	ACGIH	
Cumene (constituent) 98-82-8	A3	
Chemical name	IARC	
Cumene (constituent) 98-82-8	Group 2B	
Chemical name	NTP	

Numerical measures of toxicity - Product Information

Cumene (constituent) 98-82-8

Chemical name Cumene (constituent) 98-82-8 Reasonably Anticipated

OSHA

Page 7 of 12 Item Numbers: 43212-4712

0 % of the mixture consists of ingredient(s) of unknown toxicity Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 99,999.00 mg/kg ATEmix (dermal) 12,444.80 mg/kg ATEmix (inhalation-gas) 99,999.00 ATEmix (inhalation-dust/mist) 12.40 mg/l ATEmix (inhalation-vapor) 91.30

12. ECOLOGICAL INFORMATION

EcotoxicitySpecific test data for the substance or mixture is not available. Toxic to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants
Copper	96h EC50 Pseudokirchneriella subcapitata: 0.031 - 0.054 mg/L
7440-50-8	static
	72h EC50 Pseudokirchneriella subcapitata: 0.0426 - 0.0535 mg/L
	static
Zinc powder (stabilized)	96h EC50 Pseudokirchneriella subcapitata: 0.11 - 0.271 mg/L
7440-66-6	static
	72h EC50 Pseudokirchneriella subcapitata: 0.09 - 0.125 mg/L
	static
Cumene (constituent)	72h EC50 Pseudokirchneriella subcapitata: = 2.6 mg/L
98-82-8	
Silicon dioxide, amorphous	72h EC50 Pseudokirchneriella subcapitata: = 440 mg/L
7631-86-9	

Chemical name	Fish
Solvent naphtha, petroleum, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: = 9.22 mg/L
Petroleum distillates, hydrotreated light 64742-47-8	96h LC50 Pimephales promelas: = 45 mg/L (flow-through) 96h LC50 Lepomis macrochirus: = 2.2 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 2.4 mg/L (static)
Copper 7440-50-8	96h LC50 Oncorhynchus mykiss: = 0.052 mg/L (flow-through) 96h LC50 Lepomis macrochirus: = 1.25 mg/L (static) 96h LC50 Cyprinus carpio: = 0.3 mg/L (semi-static) 96h LC50 Cyprinus carpio: = 0.8 mg/L (static) 96h LC50 Poecilia reticulata: = 0.112 mg/L (flow-through) 96h LC50 Pimephales promelas: 0.0068 - 0.0156 mg/L 96h LC50 Pimephales promelas: < 0.3 mg/L (static) 96h LC50 Pimephales promelas: = 0.2 mg/L (flow-through)
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L (flow-through)
Ethylene glycol monopropyl ether 2807-30-9	96h LC50 Pimephales promelas: > 5000 mg/L (static)
Naphtha, petroleum, hydrotreated heavy 64742-48-9	96h LC50 Pimephales promelas: = 2200 mg/L
1,3,5-Trimethylbenzene (constituent) 108-67-8	96h LC50 Pimephales promelas: = 3.48 mg/L
Zinc powder (stabilized) 7440-66-6	96h LC50 Pimephales promelas: 2.16 - 3.05 mg/L (flow-through) 96h LC50 Pimephales promelas: 0.211 - 0.269 mg/L (semi-static) 96h LC50 Pimephales promelas: 2.66 mg/L (static) 96h LC50 Cyprinus carpio: = 30 mg/L 96h LC50 Cyprinus carpio: = 0.45 mg/L (semi-static) 96h LC50 Cyprinus carpio: = 7.8 mg/L (static) 96h LC50 Cyprinus carpio: = 3.5 mg/L (static) 96h LC50 Lepomis macrochirus: = 3.5 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 0.24 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: = 0.59 mg/L (semi-static)

Page 8 of 12 Item Numbers: 43212-4712

	96h LC50 Oncorhynchus mykiss: = 0.41 mg/L (static)
Cumene (constituent)	96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L (flow-through)
98-82-8	96h LC50 Oncorhynchus mykiss: = 4.8 mg/L (flow-through)
	96h LC50 Oncorhynchus mykiss: = 2.7 mg/L (semi-static)
	96h LC50 Poecilia reticulata: = 5.1 mg/L (semi-static)
Silicon dioxide, amorphous	96h LC50 Brachydanio rerio: = 5000 mg/L (static)
7631-86-9	

Chemical name	Crustacea
Solvent naphtha, petroleum, light aromatic 64742-95-6	48h EC50 Daphnia magna: = 6.14 mg/L
Copper 7440-50-8	48h EC50 Daphnia magna: = 0.03 mg/L Static
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: = 6.14 mg/L
Zinc powder (stabilized) 7440-66-6	48h EC50 Daphnia magna: 0.139 - 0.908 mg/L Static
Cumene (constituent) 98-82-8	48h EC50 Daphnia magna: 7.9 - 14.1 mg/L Static 48h EC50 Daphnia magna: = 0.6 mg/L
Silicon dioxide, amorphous 7631-86-9	48h EC50 Ceriodaphnia dubia: = 7600 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Partition coefficient
1,2,4-Trimethylbenzene (constituent)	3.63
95-63-6	
Cumene (constituent)	3.7
98-82-8	

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Empty containers should be taken to an approved waste handling site for recycling or **Contaminated Packaging**

disposal.

14. TRANSPORT INFORMATION

This information is not intended to convey all specific transportation requirements relating to Note:

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not DOT regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49

CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part

1.33]. UN/ID no UN1210 **Proper Shipping Name** Printing Ink

Transport hazard class(es) **Packing Group**

Page 9 of 12 Item Numbers: 43212-4712

ICAO / IATA / IMDG / IMO

VN/ID no UN1210
Proper Shipping Name Printing Ink
Transport hazard class(es) 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

All substances are listed as ACTIVE on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold
			Values %
Copper	7440-50-8	10 - 30	1.0
1,2,4-Trimethylbenzene (constituent)	95-63-6	10 - 30	1.0
Ethylene glycol monopropyl ether	2807-30-9	5 - 10	1.0
Zinc powder (stabilized)	7440-66-6	1 - 5	1.0
Cumene (constituent)	98-82-8	1 - 5	0.1

Zinc is reportable under SARA313 ONLY if it is a fume or dust form. Fume or dust refers to dry forms but does not refer to "wet" forms such as use in a solution or slurry.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Chemical name	CAS No.	Weight-%
Ethylene glycol monopropyl ether	2807-30-9	5 - 10
Cumene (constituent)	98-82-8	1 - 5
Xylenes (o-, m-, p- isomers) (constituent)	1330-20-7	0.1 - < 1

US State Regulations

Chemical name	Massachusetts
Copper	X
7440-50-8	
1,2,4-Trimethylbenzene (constituent)	X
95-63-6	
1,3,5-Trimethylbenzene (constituent)	X
108-67-8	
Zinc powder (stabilized)	X
7440-66-6	
Cumene (constituent)	X
98-82-8	
Silicon dioxide, amorphous	X
7631-86-9	

Chemical name	Minnesota Right To Know
Copper 7440-50-8	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Cumene (constituent)	×

Page 10/12

Item Numbers: 43212-4712 Page 10 of 12

98-82-8		
Silicon dioxide, amorphous	X	
7631-86-9		
Chemical name	New Jersey	
Copper	X	
7440-50-8		
1,2,4-Trimethylbenzene (constituent)	X	
95-63-6		
Ethylene glycol monopropyl ether	X	
2807-30-9		
Zinc powder (stabilized)	X	
7440-66-6		
Cumene (constituent)	X	
98-82-8		
Chamiaal mama	Dannardinanta	
Chemical name	Pennsylvania	
Copper 7440-50-8	X	
	x	
1,2,4-Trimethylbenzene (constituent) 95-63-6	^	
Ethylene glycol monopropyl ether	X	
2807-30-9	^	
Zinc powder (stabilized)	X	
7440-66-6	^	
Cumene (constituent)	X	
98-82-8		
Silicon dioxide, amorphous	X	
7631-86-9		

<u>California Proposition 65</u>
This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

	To productive right	
C	Chemical name	California Proposition 65
C	Cumene (constituent)	Carcinogen

Canada

Chemical name	NPRI - National Pollutant Release Inventory
Solvent naphtha, petroleum, light aromatic	Part 5 Substance - Volatile Organic Compounds with Additional
64742-95-6	Reporting Requirements
Petroleum distillates, hydrotreated light	Part 5 Substance - Volatile Organic Compounds with Additional
64742-47-8	Reporting Requirements
Copper	Part 1, Group A Substance
7440-50-8	
1,2,4-Trimethylbenzene (constituent)	Part 1, Group A Substance
95-63-6	Part 5 Substance - Volatile Organic Compounds with Additional
	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants
Ethylene glycol monopropyl ether 2807-30-9	Part 5 Substance - Volatile Organic Compounds with Additional
	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants
Naphtha, petroleum, hydrotreated heavy	Part 5 Substance - Volatile Organic Compounds with Additional
64742-48-9	Reporting Requirements
1,3,5-Trimethylbenzene (constituent) 108-67-8	Part 5 Substance - Volatile Organic Compounds with Additional
	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants
Zinc powder (stabilized)	Part 1, Group A Substance
7440-66-6	
Cumene (constituent)	Part 1, Group A Substance
98-82-8	Part 4 Substance - Criteria Air Contaminants
1,2,3-Trimethylbenzene (constituent)	Part 5 Substance - Volatile Organic Compounds with Additional
526-73-8	Reporting Requirements
	Part 4 Substance - Criteria Air Contaminants

Page 11 of 12 Item Numbers: 43212-4712

16. OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2A - Probably Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date Nov-13-2023

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Page 12/12