47109-XXXX

Article Print o Versio	date 15.02.20			EN Page 1 / 6			
1.	Identification of th	ne substance/mixture and	d of the company/undertal	king			
1.1.	Product identifiers						
	Article No. (manufact Identification of the s	,	127XXX011 SYSTEM 3 SCREEN PRIN	TING MEDIUM			
1.2.	Relevant identified	uses of the substance or m	ixture and uses advised aga	inst			
1.3.	Details of the suppli	ier of the safety data sheet					
	Supplier (manufacturer/importer/downstream user/distributor): Daler-Rowney Ltd						
	Peacock Lane Bracknell, RG12 8SS ENGLAND	;	Telephone: +44 (0) 1344 46 Telefax: +44 (0) 1344 4865				
	Dept. responsible fo	or information:					
	E-mail		Philip.Gray@daler-rowney.	com			
1.4.	Emergency telephor						
	Emergency telephone		+44 (0) 1344 461000				
2.	Hazards identifica	tion					
2.1.		e substance or mixture					
	Classification according to Regulation (EC) No. 1272/2008 [CLP]						
		This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].					
2.2.	Label elements						
	The product is classif	The product is classified and labelled according to EC directives or corresponding national laws.					
		to Regulation (EC) No. 127	2/2008 [CLP]				
	Hazard pictograms	lazard pictograms					
	Hazard statements						
	n.a. Precautionary statements n.a.						
	contains:	1.4.					
	n.a.						
	Supplemental Hazar EUH210	rd information (EU) Safety data sheet available	on request				
2.3.	Other hazards	Galety data sheet available	on request.				
3.	Composition / Info	ormation on ingredients					
3.2.	Mixtures	.					
	Product description	/ chemical characterization	n				
	Description	Medium for watercolors					
	Hazardous ingredients						
	Classification according to Regulation (EC) No. 1272/2008 [CLP] EC No. REACH No.						
	CAS No.	Chemical name			Wt %		
	INDEX No. 204-709-8	classification:			Remark		
	204-709-8 124-68-5 603-070-00-6	2-amino-2-methylpropanol Eye Irrit. 2 H319 / Skin Irr	it. 2 H315 / Aquatic Chronic 3	8 H412	1 - 2,5		
	Additional information Full text of classification: see section 16						
4.	First-aid measures	S					

Item Numbers: 47109-3001, 47109-3005

SafetysData7Sbeet/STEM 3 PRINTMAKING according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.:	127XXX011	SYSTEM 3 SCREEN PRINTING MEDIUM		
Print date	15.02.2017	Revision date 15.02.2017	EN	
Version	1.0	Issue date 21.09.2016	Page 2 / 6	
			-	

4.1. Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with molten product, cool skin area rapidly with cold water. Allow stiffening. Take up mechanically. When in doubt or if symptoms are observed, get medical advice.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases:

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Special protective equipment for firefighters:

Provide a conveniently located respiratory protective device.

Additional information

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Take up mechanically, placing in appropriate containers for disposal. Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

7. Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Usual measures for fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

SafetysData7Sbeet/STEM 3 PRINTMAKING according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

1. Control parameters Occupational exposure limit values: n.a. 2. Exposure controls Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerose solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used. Occupational exposure controls Respiratory protection If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory prot apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material of 4mm; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacture. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Eye protection Wear closely fitting protective glasses in case of splashes. Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. 1. Physical and chemical properties Appearance: Physical state Colour refer to label Colour characteristic Safety relevant basis data Lower explosion limit n. n.a. Upper explosion limit n	.3. Specific end use(s) Observe technical data	a sheet.Observe instructio	ns for use.					
Occupational exposure limit values: n.a. 2. Expoure controls Provide good ventilation. This can be achieved with local or nom suction. If this should not be sufficient to keep aerose solvent vapour concentration of solvents is beyond the exposure limit values, a suitable respiratory protection must be used. Occupational exposure controls Respiratory protection If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protoms be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protoms be used. (BGR 190). Use only respiratory protocom equipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Trickness of the glove material > 0.4 mm; Breakthrough time (maximum wearing time) > 400 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm gloveritoes DiN BM 200 recording Wear closely filing protective glasses in case of splashes. Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties	Exposure controls /	Personal protection						
n.a. 12. Exposure controls Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerose solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used. Cocupational exposure controls Respiratory protection Respiratory protection If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protein apparatus (BGR 190). Use only respiratory protection quipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nithile rubber) Thickness of the glove material > 0.4 mm; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Eye protection Wear closely fitting protective glasses in case of splashes. Protective cloating the protecting Meter contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.	-	•						
2.2. Exposure controls Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerose solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used. Occupational exposure controls Respiratory protection If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection equipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0.4 mm; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Evp protection Wear closely fitting protective glasses in case of splashes. Protective neasures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Imprint the protective lobel obol Odour n.a. </td <td></td> <td colspan="5"></td>								
Priovide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosc solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used. Occupational exposure controls Respiratory protection If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory prot must be used. Observe the wear time limits according GetStoffV in combination with the rules for using respiratory protection apparatus (GR 180). Use only respiratory protection equipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0.4 mm ; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Eye protection Wear closely fitting protective glasses in case of splashes. Protective closting Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. Protective active askin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter link sufface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state Physical state Physica	n.a.							
solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used. Cocupational exposure controls Respiratory protection If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory prot apparatus (BGR 180). Use only respiratory protection equipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0.4 mm; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protective glasses in case of splashes. Protective clothing Wear closely fitting protective glasses in case of splashes. Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state iquid Colour characteristic Safety relevant basis data Fere ontact log in no. Completely mixed to the no. Completely mixed to the note of the sploy of th	.2. Exposure controls							
Respiratory protection If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protaparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0.4 mm; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Eye protection Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data n.a. Information on basic physical and chemical properties Appearance: Physical stata	5	Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and						
If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory prod must be used. Observe the wear time limits according defStoffV in combination with the rules for using respiratory prod apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0.4 mm ; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and defails for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Eye protection Wear closely fitting protective glasses in case of splashes. Protective clothing Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. Protective measures After contact cleam skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data to enerical properties Appearance: Information emperture in °C: n.a. Lower explosion limit n.a. Vapour pressure at 20 °C: n.a. Lower explosion limit n.a. Vapour pressure at 20 °C: n.a. Density at 20 °C: n.a. Density at 20 °C: solution of mPars Solvent content: Organic solvents: 0 Wt %	Occupational exposu							
must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus; (BCR 190). Use only respiratory protection equipment with CE-symbol including four digit test number. Hand protection For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0.4 mm; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Eye protection Wear closely fitting protective glasses in case of splashes. Protective closting Wear antistatic clothing Wear antistatic clothing the following use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Apparance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data I no.a. Lower explosion limit n.a. Density at 20 °C: n.a. Lower explosion limit n.a. Density at 20 °C: n.a. Density at 20 °C: n.a. Do not separater net (%) < 3 % Solid content (%): 0,00 Wt % Solvent content: Organic solvents: 0 Wt %	Respiratory protectio	'n						
For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0.4 mm; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Eye protection Wear closely fitting protective glasses in case of splashes. Protective clothing Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Remark Flash point (°C) n.a. Ignition temperature in °C: n.a. Lower explosion limit n.a. Upper explosion limit n.a. Upper explosion limit n.a. Vapour pressure at 20 °C: 0.300 7.0 Viscosity at 20 °C: 0.400 7.0 Viscosity at 20 °C: 0.500 7.0 Viscosity at 20 °C: 0.5000 7.0 Viscosity at 20 °C: 0.5000 7.0 Viscosity at	must be used. Observ	If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protectic must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection.						
Thickness of the glove material > 0.4 mm : Breaktfrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recomm glove articles DIN EN 374 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact. Eye protection Wear closely fitting protecting exposed skin areas. In no case should they be used after contact. Eye protective clothing Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. Protective clothing Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data <u>na.</u> Upper explosion limit n.a. Upper explosion limit n.a. Upper explosion limit n.a. Vapour pressure at 20 °C: n.a. Density at 20 °C: n.a. Density at 20 °C: 50,00 7,0 Viscosity at 20 °C: 50,00 7,0 Viscosity at 20 °C: 50,00 7,0 Viscosity at 20 °C: 0.00 Solid content (%): 0.00 Wt % solvent content: Organic solvents:: 0 Wt %		ated handling the following	u alove material i	must he use	d: NBR (Nitrile rubber)			
Eye protection Wear closely fitting protective glasses in case of splashes. Protective clothing Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Ignition temperature in °C: n.a. Lower explosion limit n.a. Upper explosion limit n.a. Upper explosion limit n.a. Vapour pressure at 20 °C: 1,00 grid content (%) 50,00 Viscosity at 20 °C > 200 Mater solubility (gL) completely miscible pH at 20 °C: 50,00 Solivent separation test (%) 0,00 Solivent content (%): 0,00	Thickness of the glove Observe the instruction manufacturer. Penetra glove articles DIN EN 3	Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommender glove articles DIN EN 374						
Protective clothing Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers. Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. • Physical and chemical properties Appearance: Physical state Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Remark Flash point (°C) n.a. Lower explosion limit n.a. Upper explosion limit n.a. Density at 20 °C: 1.00 g/cm³ Water solubility (g/L) completely miscible pH at 20 °C: 50,00 7.0 Viscosity at 20 °C 50,00 7.0 Viscosity at 20 °C: 3 % Solvent separation test (%) < 3 %	Eye protection	Eye protection						
Protective measures After contact clean skin thoroughly with water and soap or use appropriate cleanser. Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Flash point (°C) n.a. Lower explosion limit n.a. Upper explosion limit n.a. Upper explosion limit n.a. Vapour pressure at 20 °C: 1.00 g/cm³ Water solubility (g/L) completely miscible pH at 20 °C: 50.00 7.0 Viscosity at 20 °C > 200 mPa·s Solvent separation test (%) < 3 % Solid content (%): 0,00 Wt % solvent content: 0 Wt %	Protective clothing	Protective clothing						
Environmental exposure controls Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Remark Flash point (°C) n.a. Ina. Ignition temperature in °C: n.a. Lower explosion limit n.a. Upper explosion limit n.a. Upper explosion limit 0.a. Upper explosion limit 0.a. Vapour pressure at 20 °C: 1,00 g/cm³ g/cm³ Water solubility (g/L) completely miscible Flash 20 °C: > 200 mPa·s Solid content (%): 0,00 Wt % Solid content (%): 0,00								
Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary. Physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Remark Flash point (°C) n.a. n.a. Ignition temperature in °C: n.a. Lower explosion limit n.a. Vapour pressure at 20 °C: n.a. Vapour pressure at 20 °C: n.a. Density at 20 °C: 50,00 7,0 Viscosity at 20 °C > 200 mPa·s Solvent separation test (%) < 3 %	After contact clean ski							
Physical and chemical properties 1. Information on basic physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Flash point (°C) n.a. Ignition temperature in °C: n.a. Lower explosion limit n.a. Vapour pressure at 20 °C: n.a. Density at 20 °C: 1,00 g/cm³ Water solubility (g/L) completely miscible pH at 20 °C: 50,00 7,0 Viscosity at 20 °C > 200 mPa·s Solvent separation test (%) < 3 %								
.1. Information on basic physical and chemical properties Appearance: Physical state liquid Colour refer to label Odour Odour characteristic Safety relevant basis data Unit Method Remark Flash point (°C) n.a. Ignition temperature in °C: n.a. Ignition temperature in °C: n.a. Lower explosion limit n.a. Density at 20 °C: n.a. Density at 20 °C: n.a. Vapour pressure at 20 °C: 1,00 g/cm³ Water solubility (g/L) completely miscible pH at 20 °C: > 200 mPa ·s Solvent separation test (%) < 3 %	Do not allow to enter in	Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.						
Appearance: Iiquid Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Remark Flash point (°C) n.a. Ignition temperature in °C: n.a. Ignition temperature in °C: n.a. Ignition temperature in °C: n.a. Lower explosion limit n.a. Upper explosion limit n.a. Upper explosion limit n.a. Density at 20 °C: n.a. Density at 20 °C: 1,00 g/cm³ Water solubility (g/L) completely miscible pH at 20 °C: > 200 pH at 20 °C: > 200 mPa·s Solvent separation test (%) < 3 % Solid content (%): 0,00 Wt % solvent content: 0 Organic solvents:: 0 Wt % Kt % Kt %	. Physical and chem	Physical and chemical properties						
Physical state liquid Colour refer to label Odour characteristic Safety relevant basis data Unit Method Remark Flash point (°C) n.a. Ignition temperature in °C: n.a. Ignition temperature in °C: n.a. Ignition temperature in °C: n.a. Lower explosion limit n.a. Ignition temperature in °C: n.a. Upper explosion limit n.a. Ignition temperature in °C: n.a. Upper explosion limit n.a. Ignition temperature in °C: n.a. Vapour pressure at 20 °C: n.a. Ignition temperature in °C: n.a. Vapour pressure at 20 °C: n.a. Ignition temperature in °C: n.a. Vapour pressure at 20 °C: n.a. Ignition temperature in °C: n.a. Vapour pressure at 20 °C: 50,00 7,0 Viscosity at 20 °C > 200 mPa·s Solvent separation test (%) < 3	.1. Information on basic	physical and chemical p	properties					
Colourrefer to label characteristicSafety relevant basis dataUnitMethodRemarkFlash point (°C)n.a.Ignition temperature in °C:n.a.Lower explosion limitn.a.Upper explosion limitn.a.Vapour pressure at 20 °C:n.a.Density at 20 °C:1,00g/cm³Water solubility (g/L)completely misciblepH at 20 °C:50,007,0Viscosity at 20 °C> 200mParsSolvent separation test (%)< 3		11 averaged						
OdourcharacteristicSafety relevant basis dataUnitMethodRemarkFlash point (°C)n.a.Ignition temperature in °C:n.a.Lower explosion limitn.a.Lower explosion limitn.a.Upper explosion limitn.a.Vapour pressure at 20 °C:n.a.Density at 20 °C:1,00g/cm³Water solubility (g/L)completely misciblepH at 20 °C:50,007,0Viscosity at 20 °C> 200Solvent separation test (%)< 3	-							
Safety relevant basis dataUnitMethodRemarkFlash point (°C)n.a.Ignition temperature in °C:n.a.Lower explosion limitn.a.Upper explosion limitn.a.Upper explosion limitn.a.Vapour pressure at 20 °C:n.a.Density at 20 °C:1,00 g/cm³Water solubility (g/L)completely misciblepH at 20 °C:50,00 7,0Viscosity at 20 °C> 200 mPa·sSolvent separation test (%)< 3 %			2					
Flash point (°C)n.a.Ignition temperature in °C:n.a.Lower explosion limitn.a.Upper explosion limitn.a.Vapour pressure at 20 °C:n.a.Density at 20 °C:1,00 g/cm³Water solubility (g/L)completely misciblepH at 20 °C:50,00 7,0Viscosity at 20 °C> 200 mPa·sSolvent separation test (%)< 3 %				Unit	Method	Remark		
Ignition temperature in °C:n.a.Lower explosion limitn.a.Upper explosion limitn.a.Vapour pressure at 20 °C:n.a.Density at 20 °C:1,00 g/cm³Water solubility (g/L)completely misciblepH at 20 °C:50,00 7,0Viscosity at 20 °C> 200 mPa·sSolvent separation test (%)< 3 %								
Upper explosion limitn.a.Vapour pressure at 20 °C:n.a.Density at 20 °C:1,00 g/cm³Water solubility (g/L)completely misciblepH at 20 °C:50,00 7,0Viscosity at 20 °C> 200 mPa sSolvent separation test (%)< 3 %		in °C:	n.a.					
Vapour pressure at 20 °C:n.a.Density at 20 °C:1,00 g/cm³Water solubility (g/L)completely misciblepH at 20 °C:50,00 7,0Viscosity at 20 °C> 200 mPa·sSolvent separation test (%)< 3 %	Lower explosion limi	t	n.a.					
Density at 20 °C:1,00 g/cm³Water solubility (g/L)completely misciblepH at 20 °C:50,00 7,0Viscosity at 20 °C> 200 mPa·sSolvent separation test (%)< 3 %	Upper explosion limi	t	n.a.					
Water solubility (g/L)completely misciblepH at 20 °C:50,007,0Viscosity at 20 °C> 200mPa·sSolvent separation test (%)< 3	Vapour pressure at 2	0 °C:	n.a.					
pH at 20 °C: 50,00 7,0 Viscosity at 20 °C > 200 mPa·s Solvent separation test (%) < 3 %	Density at 20 °C:		1,00 g	g/cm³				
pH at 20 °C: 50,00 7,0 Viscosity at 20 °C > 200 mPa·s Solvent separation test (%) < 3 %	Water solubility (g/L)	comp	letely miscible					
Solvent separation test (%)< 3 %Solid content (%):0,00 Wt %solvent content:0 Wt %			50,00	7,0				
Solid content (%): 0,00 Wt % solvent content: 0 Wt %	Viscosity at 20 °C		> 200 I	mPa∙s				
solvent content: Organic solvents:: 0 Wt %	Solvent separation te	∍st (%)	< 3 '	%				
Organic solvents:: 0 Wt %	Solid content (%):		0,00	Nt %				
tem Numbers: 47109-3001, 47109-3005	Organic solvents::		0 \	Nt %				
tem Numbers: 47109-3001, 47109-3005								
	tem Numbers: 47109-3001, 47109-3005					Pag		

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed.

SYSTEM 3 SCREEN PRINTING MEDIUM Revision date 15.02.2017 Issue date 21.09.2016

Further information on storage conditions

127XXX011 15.02.2017

1.0

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

EN Page 3 / 6

7.3. Specific end use(s)

Article No.: Print date

Version

SafetysData7Sbeet/STEM 3 PRINTMAKING according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article Print d Versio	late	127XXX011 15.02.2017 1.0	SYSTEM 3 SCREEN PRINTING MEDIUM Revision date 15.02.2017 EN Issue date 21.09.2016 Page 4 / 6				
	Water:		50 Wt %				
9.2.	Other info	ormation:					
10.	Stability	and reactivity					
10.1	Reactivity	J.					
	Chemical	stability en applying the re	commended regulations for storage and handling. Further information on correct storage: refer to				
10.3.	Possibility of hazardous reactions Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.						
10.4.	Conditions to avoid Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer t chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.						
10.5.	Incompat	ible materials					
10.6.	 Hazardous decomposition products Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon mo smoke. Decomposition takes place from temperatures above: at 160 °C 						
11.	Toxicolo	gical information	on				
		tion according to F n preparation itsel	Regulation (EC) No. 1272/2008 [CLP] f available.				
11.1.	Information	on on toxicologic ticity	cal effects				
	2-amino-2-methylpropanol oral, LD50, Rat: 2900 mg/kg						
	skin corrosion/irritation; Serious eye damage/eye irritation						
	Toxicologi	ical data are not a	vailable.				
	Respiratory or skin sensitisation						
	Toxicological data are not available.						
	CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)						
	Toxicological data are not available.						
	Specific t	Specific target organ toxicity					
	Toxicological data are not available.						
	Aspiration hazard						
	Toxicological data are not available.						
	Practical experience/human evidence						
	Other observations:						
	Overall Assessment on CMR properties						
	The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP. Remark						
	There is no information available on the preparation itself .						
12.	Ecological information						
	overall ev Classifica There is n	valuation tion according to F o information avai	Regulation (EC) No. 1272/2008 [CLP] lable on the preparation itself . rface water or drains.				
12.1.	Toxicity						
	2-amino-2	2-methylpropanol toxicity, EC50: 19	3 mg/L (48 h)				
	•	n Ecotoxicity					
	Toxicologi	ical data are not a	vailable.				
	-						
			David				

Article Print d Versio	late 15.02.2017	SYSTEM 3 SCREEN PRINTING MEDIUM Revision date 15.02.2017 EN Issue date 21.09.2016 Page 5 / 6					
12.2.	Persistence and degrada Toxicological data are not						
12.3.	Bioaccumulative potential Toxicological data are not available.						
	Bioconcentration factor	(BCF)					
	Toxicological data are not	available.					
12.4.	 Mobility in soil Toxicological data are not available. 						
12.5.	Results of PBT assessm	Results of PBT assessment					
	The substances in the mix	ture do not meet the PBT/vPvB criteria according to REACH, annex XIII.					
12.6.	Other adverse effects						
13.	Disposal consideratio	15					
13.1.	Waste treatment method	S					
		roduct surface water or drains. This material and its container must be disposed of in a safe way. Waste ctive 2008/98/EC, covering waste and dangerous waste.					
		codes/waste designations in accordance with EWC er solvents and solvent mixtures					
	packaging Recommendation Non-contaminated packag	es may be recycled. Vessels not properly emptied are special waste.					
14.	Transport information						
	No dangerous good in s	ense of this transport regulation.					
14.1.	UN number						
		n.a.					
14.2.	UN proper shipping name	•					
14.3.	Transport hazard class(e	s)					
		n.a.					
14.4.	Packing group	n.a.					
145	Environmental hazards	II.a.					
14.5.	Land transport (ADR/RID)	n.a.					
	Marine pollutant	n.a.					
14.6	Special precautions for						
14.0.		l, upright and safe containers. Make sure that persons transporting the product know what to do in kage.					
	Additional information						
	Land transport (ADR/RIE tunnel restriction code)					
	Sea transport (IMDG)						
	EmS-No.	n.a.					
14.7.	•	ing to Annex II of MARPOL and the IBC Code					
14.7.	Transport in bulk accord not applicable	ing to Annex II of MARPOL and the IBC Code					

Item Numbers: 47109-3001, 47109-3005

SafeigsData7Sbeet/STEM 3 PRINTMAKING according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Print o Versio		127XXX011 15.02.2017 1.0	SYSTEM 3 SCREEN PRINTING MEE Revision date 15.02.2017 Issue date 21.09.2016	DIUM EN Page 6 / 6		
EU legislation						
	Information according to 1999/13/EC VOC-value (in g/L) ISO 11890-2: VOC-value (in g/L) ASTM D 2369:		2: 0	s of volatile organic compounds (VO	C-guideline).	
	National re	gulations				
	Restrictions of occupation Observe employment restrictions under the Maternity Pro Observe restrictions to employment for juvenils according					
	Other regu	lations, restriction	s and prohibition regulations			
15.2.	5.2. Chemical Safety Assessment Chemical safety assessments for substances in this preparation were not carried out.					
16. Other information						
16.		Full text of classification in section 3:				
10.	Full text of	classification in s	ection 3:			

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.