

09/25/2015 FRI 9:18 FAX 1 715 674 6202 PINE RIVER LUMBER

001/007

Safety Data Sheet (SDS)

Wood and Wood Dust (Without Chemical Treatments or Resins/Adhesives)

Pine River Lumber Co., Ltd.
3249 Cooks Lane South
PO Box 139
Long Lake, WI 54542

Emergency Phone: (715) 674-4444
Additional Information: (253) 924-3865
CHEMTREC: (800) 424-9300
Revised Date: January 1, 2015

1: Product Identification

Product	Manufacturing Location(s)
Wood and Wood Dust (Without Chemical Treatments or Resins/Additives))	USA: Various Canada: Various
Synonyms: Untreated wood, Sawdust, Sanderdust	

2: Hazardous Ingredients/Identify Information

Name	CAS#	Percent	Agency	Exposure Limits	Comments
Wood (softwood and hardwood)	None	100	OSHA	PEL-TWA 15 mg/m ³ (see footnote ^A below)	Total dust (PNOR)
			OSHA	PEL-TWA 5 mg/m ³ (see footnote ^A below)	Respirable dust fraction (PNOR)
			ACGIH	TLV-TWA 1 mg/m ³	Inhalable fraction

^A In AFL-CIO v OSHA, 965 F. 2d 962 (11th Cir. 1992), the Court overturned OSHA's 1989 Air Contaminants Rule, including the specific PEL's for wood dust that OSHA had established at that time. The 1989 vacated PEL's were: 5 mg/m³ PEL-TWA and 10 mg/m³ STEL (15 min), all softwood and hardwood except Western Red Cedar. Wood dust is now regulated by OSHA as "Particulates Not Otherwise Regulated" (PNOR), which is also referred to as "nuisance dust".

09/25/2015 FRI 9:18 FAX 1 715 674 6202 PINE RIVER LUMBER

002/007

However, some states have incorporated the 1989 OSHA PEL's in their state plans. Additionally, OSHA indicated that it may cite employers under the OSH Act general duty clause in appropriate circumstances for noncompliance with the 1989 PEL's.

3. Hazard Identification

Primary Safety/Health Hazards:

Warning: Wood dust may pose a combustible dust explosion hazard if suspended in air in sufficient concentrations in a contained area in proximity to an ignition source. Users of wood products which may generate wood dust solids during handling and processing should evaluate combustibility hazards and controls. See additional comments in MSDS.

The primary health hazard posed by this product is thought to be due to exposure to airborne wood dust.

Appearance and Odor: Depending on wood species, light to dark colored, granular solid. Color and odor are dependent on the wood species and time since dust was generated. Particles may be generated by any manual or mechanical cutting or abrasion process performed on wood.

Primary Route(s) of Exposure:

- Ingestion:
- Skin:
- Inhalation:
- Eye:

Medical Conditions Generally Aggravated by Exposure: Wood dust may aggravate pre-existing respiratory conditions or allergies.

Signs and Symptoms of Exposure:

Acute Health Hazards: Wood dust can cause eye irritation. Certain species of wood dust can elicit allergic contact dermatitis in sensitized individuals. Inhalation of wood dust may cause respiratory irritation, nasal dryness, coughing, sneezing, and wheezing as a result of inhalation.

Chronic Health Hazards: Wood dust, depending on the species, may cause allergic contact dermatitis and respiratory sensitization with prolonged, repetitive contact or exposure to elevated dust levels. Exposure to wood dust has been reported by some organizations to cause nasal cancer.

Carcinogenicity Listing:

- NTP: Wood dust, Known Human Carcinogen.
- IARC Monographs: Wood dust, Group 1 - carcinogenic to humans.
- OSHA Regulated:

Wood Dust - NTP: According to its Report on Carcinogens, Eleventh Edition, NTP states, "Wood dust is known to be a human carcinogen based on sufficient evidence of carcinogenicity from studies in humans". An association between wood dust exposure and cancer of the nasal cavity has been observed in many case reports, cohort studies, and case-control studies that specifically addressed nasal cancer. Strong and consistent associations with cancer of the nasal cavities and paranasal sinuses were observed both in studies of people whose occupations are associated with wood dust exposure and in studies that directly estimated wood dust exposure. This classification is based primarily on increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. The evaluation did not find sufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to wood dust. There is inadequate evidence for the carcinogenicity of wood dust from studies in experimental animals according to NTP.

Wood Dust: IARC – Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily based on studies showing an association between occupational exposure to wood dust and adenocarcinoma to the nasal cavities and paranasal sinuses. IARC did not find

09/25/2015 FRI 9:18 FAX 1 715 674 6202 PINE RIVER LUMBER

003/007

sufficient evidence of an association between occupational exposure to wood dust and cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum.

4. Emergency and First-Aid Procedures

Ingestion: Not applicable under normal use.

Eye Contact: Wood dust may cause mechanical irritation. Treat dust in eye as foreign object. Flush with water to remove dust particles. Seek medical help if irritation persists.

Skin Contact: Wood dust of certain species can elicit allergic contact dermatitis in sensitized individuals, as well as mechanical irritation resulting in erythema and hives. Seek medical help if rash, irritation or dermatitis persists.

Skin Absorption: Not known to occur under normal use.

Inhalation: Wood dust may cause unpleasant obstruction in the nasal passages, resulting in dryness of nose, dry cough, and sneezing. Remove to fresh air. Seek medical help if persistent irritation, severe coughing, allergic-type responses or breathing difficulty occurs.

5. Fire and Explosion Data

Flash Point (Method Used):

Flammable Limits:

LFL = See below under "Unusual
Fire and Explosion Hazards"

UFL = NAP

Extinguishing Media: Water, carbon dioxide, sand

Autoignition Temperature: Variable (typically 400°-500°F (204°-260°C))

Special Firefighting Procedures: None

Unusual Fire and Explosion Hazards: Depending on moisture content, and more importantly, particle diameter and airborne concentration, wood dust in a contained area may explode in the presence of an ignition source. Wood dust may similarly deflagrate (combustion without detonation like an explosion) if ignited in an open or loosely contained area. An airborne concentration of 40 grams (40,000 mg) of dust per cubic meter of air is often used as the LEL for wood dusts. Reference NFPA Standards- 654 and 664 for guidance. Ventilation systems should be kept clean and precautions should be taken to prevent sparks or other ignition sources.

HMIS Rating (Scale 0-4): Health = 2* Fire = 1 Physical Hazard = 0

NFPA Rating (Scale 0-4): Health = 1 Fire = 1 Reactivity = 0

6. Accidental Release Measures

Steps to be Taken In Case Material Is Released or Spilled: Sweep or vacuum up for recovery and disposal. Avoid creating dusty conditions whenever feasible. Maintain good housekeeping to avoid accumulation of dried wood dust on exposed surfaces. Dried wood dust may pose a combustible dust hazard. Place recovered wood dust in a container for proper disposal.

7. Handling and Storage

Precautions to be Taken In Handling and Storage: Wood dust may pose a combustible dust hazard. Keep away from ignition sources. Avoid eye contact. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of wood dust. Store in well-ventilated, dry place away from open flame.

8. Exposure Control Measures, Personal Protection

Personal Protective Equipment:

09/25/2015 FRI 9:18 FAX 1 715 674 6202 PINE RIVER LUMBER

004/007

RESPIRATORY PROTECTION – Use NIOSH approved filtering face piece respirator (“dust mask”) or higher levels of respiratory protection as indicated if there is a potential to exceed the exposure limits or for symptom relief or worker comfort. Use respiratory protection in accordance with regulatory requirements such as the OSHA respiratory protection standard 29 CFR 1910.134.

8. Exposure Control Measures, Personal Protection (cont'd.)

EYE PROTECTION – Goggles or safety glasses are recommended when excessive exposures to wood dust may occur (e.g. during clean up).

PROTECTIVE GLOVES – Not required. However, cloth, canvas, or leather gloves are recommended to minimize potential slivers or mechanical irritation from handling generated wood dust.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT – Outer garments which cover the arms may be desirable in extremely dusty areas.

WORK/HYGIENE PRACTICES – Follow good hygienic and housekeeping practices. Clean up areas where wood dust settles to avoid excessive accumulation of this combustible material. Minimize compressed air blowdown or other practices that generate high airborne-dust concentrations.

Ventilation:

LOCAL EXHAUST – Provide local exhaust as needed so that exposure limits are met. Ventilation to control dust should be considered where potential explosive concentrations and ignition sources are present. The design and operation of any exhaust system should consider the possibility of explosive concentrations of wood dust within the system. See “SPECIAL” section below. Use of tool mounted exhaust systems should also be considered, especially when working in enclosed areas.

MECHANICAL (GENERAL) – Provide general ventilation in processing and storage areas so that exposure limits are met.

SPECIAL – Ensure that exhaust ventilation and material transport systems involved in handling this product contain explosion relief vents or suppression systems designed and operated in accordance with applicable standards if the operating conditions justify their use.

OTHER – Cutting & Machining of product should preferably be done outdoors or with adequate ventilation & containment.

9. Physical/Chemical Properties

Physical Description: Light to dark colored, granular solid. Color and odor are dependent on the wood species and time since dust was generated.

Boiling Point (@ 760 mm Hg):	NAP
Evaporation Rate (Butyl Acetate = 1):	NAP
Freezing Point:	NAP
Melting Point:	NAP
Molecular Formula:	NAP
Molecular Weight:	NAP
Oil-water Distribution Coefficient:	NAP
Odor Threshold:	NAP
pH:	NAP
Solubility in Water (% by weight):	Insoluble
Specific Gravity (H₂O = 1):	Variable; depends on wood species and moisture
Vapor Density (air = 1; 1 atm):	NAP
Vapor Pressure (mm Hg):	NAP
Viscosity:	NAP
% Volatile by Volume [@ 70°F (21°C)]:	0

09/25/2015 FRI 9:19 FAX 1 715 674 6202 PINE RIVER LUMBER

005/007

10. Stability and Reactivity**Stability:** Unstable Stable**Conditions to Avoid:** Avoid open flame. Product may ignite at temperatures in excess of 400°F (204°C).**Incompatibility (Materials to Avoid):** Avoid contact with oxidizing agents.**10. Stability and Reactivity (cont'd.)****Hazardous Decomposition or By-Products:** Thermal decomposition (i.e. smoldering, burning) products include carbon monoxide, carbon dioxide, oxides of nitrogen, aliphatic aldehydes, terpenes, and polycyclic aromatic hydrocarbons. Natural decomposition of organic materials such as wood may produce toxic gases and an oxygen deficient atmosphere in enclosed or poorly ventilated areas. Spontaneous and rapid hazardous decomposition will not occur.**Hazardous Polymerization:** May occur Will not occur**Sensitivity to Mechanical Impact:** NAP**Sensitivity to Static Discharge:** NAP**11. Toxicological Information****Toxicity Data:****Wood dust (softwood or hardwood)**Wood dust – generated from sawing, sanding or machining wood products – may cause nasal dryness, irritation, coughing and sinusitis. NTP and IARC classify wood dust as a human carcinogen (IARC Group 1). See Section 3 above. **Components:** NAP**Target Organs:** Eyes, skin, respiratory system.**12. Ecological Information****Environmental Fate:** Wood dust would be expected to be biodegradable.**Environmental Toxicity:** NAP**13. Disposal Considerations****Waste Disposal Method:** Incineration in accordance with local, state, and federal regulations is preferred because fugitive emissions can be effectively controlled. Landfill disposal in accordance with local, state, and federal regulations is acceptable if actions are taken to contain the material until it can be covered by other wastes or landfill cover materials.**14. Transport Information****Mode:** (Air, Land, water) Not regulated as a hazardous material by the U.S. Department of Transportation. Not listed as a hazardous material in Canadian Transportation of Dangerous Goods (TDG).**Proper Shipping Name:** NAP**Hazard Class:** NAP**UN/NA ID Number:** NAP**Packing Group:** NAP Information Reported for**Product/Size:** NAP**15. Regulatory Information****TSCA:** NAP

09/25/2015 FRI 9:19 FAX 1 715 674 6202 PINE RIVER LUMBER

006/007

CERCLA: NAP**DSL:** NAP**OSHA:** Wood products per se are not hazardous under the criteria of the federal OSHA Hazard Communication Standard 29CFR 1910.1200. However, wood dust generated by sawing, sanding or machining wood products may be hazardous and hence included under 1910.1200.**STATE RIGHT-TO-KNOW:**

California Prop 65:

Warning: Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer.

Pennsylvania – When cut or otherwise machined, wood products may emit wood dust. Wood dust appears on Pennsylvania's Appendix A, Hazardous Substance List.

New Jersey – When cut or otherwise machined, wood products may emit wood dust. Wood dust appears on New Jersey's Environmental Hazardous Substance List.

SARA 313 Information: This product does not contain any chemical ingredient (s) with known CAS numbers that exceed the de minimis reporting levels established by SARA Title III, section 313 and 40 CFR section 372.**SARA 311/312 Hazard Category:** This product has been reviewed according to the EPA "Hazard Categories" promulgated under SARA Title III Sections 311 and 312 and is considered, under applicable definitions, to meet the following categories:

An immediate (acute) health hazard	Yes
A delayed (chronic) health hazard	Yes
A corrosive hazard	No
A fire hazard	No
A reactivity hazard	No
A sudden release hazard	No

FDA: Not intended for use as a food additive or indirect food contact item.**WHMIS Classification:** Controlled Product: D2A (wood dust: IARC Group 1)**16. Additional Information**

The information contained in this Material Safety Data Sheet is based on the experience of occupational health and safety professionals and comes from sources believed to be accurate or otherwise technically correct. It is the user's responsibility to determine if the product is suitable for its proposed application(s) and to follow necessary safety precautions. The user has the responsibility to make sure that this MSDS is the most up-to-date issue.

Definition of Common Terms:

ACGIH	= American Conference of Governmental Industrial Hygienists
C	= Ceiling Limit
CAS#	= Chemical Abstracts System Number
DOT	= U. S. Department of Transportation
DSL	= Domestic Substance List
EC50	= Effective concentration that inhibits the endpoint to 50% of control population
EPA	= U.S. Environmental Protection Agency

16. Additional Information (cont'd.)

HMIS	= Hazardous Materials Identification System
IARC	= International Agency for Research on Cancer

09/25/2015 FRI 9:19 FAX 1 715 674 6202 PINE RIVER LUMBER

007/007

IATA	= International Air Transport Association
IMDG	= International Maritime Dangerous Goods
LC50	= Concentration in air resulting in death to 50% of experimental animals
LCLo	= Lowest concentration in air resulting in death
LD50	= Administered dose resulting in death to 50% of experimental animals
LDLo	= Lowest dose resulting in death
LEL	= Lower Explosive Limit
LFL	= Lower Flammable Limit
MSHA	= Mine Safety and Health Administration
NAP	= Not Applicable
NAV	= Not Available
NIOSH	= National Institute for Occupational Safety and Health
NFPA	= National Fire Protection Association
NPRI	= Canadian National Pollution Release Inventory
NTP	= National Toxicology Program
OSHA	= Occupational Safety and Health Administration
PEL	= Permissible Exposure Limit
RCRA	= Resource Conservation and Recovery Act
STEL	= Short-Term Exposure Limit (15 minutes)
STP	= Standard Temperature and Pressure
TCLo	= Lowest concentration in air resulting in a toxic effect
TDG	= Canadian Transportation of Dangerous Goods
TDLo	= Lowest dose resulting in a toxic effect
TLV	= Threshold Limit Value
TSCA	= Toxic Substance Control Act
TWA	= Time-Weighted Average (8 hours)
UFL	= Upper Flammable Limit
WHMIS	= Workplace Hazardous Materials Information System

Safety Data Sheet

Midwest Products White Glue

Date of Preparation: 3/1/2016

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Midwest Products White Glue

General Use:

Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number	%wt or %vol

Section 3 - Hazards Identification

Emergency Overview

HMIS
H 1
F 0
R 0

Potential Health Effects

Inhalation: Vapors may cause respiratory irritation.

Eye: Contact with eyes may cause irritation.

Skin: Contact with skin may result in irritation.

Medical Conditions Aggravated by Long-Term Exposure:

Chronic Effects: There are no known chronic effects associated with this material.

Section 4 - First Aid Measures

Inhalation: Move to fresh air. Aid in breathing, if necessary, and get immediate medical attention.

Eye Contact: Immediately wash eyes with running water for 15 minutes. Get immediate medical attention.

Skin Contact: Wash affected areas with running water while removing contaminated clothing. Get immediate medical attention. Launder contaminated clothing before reuse.

Ingestion: Dilute by drinking water or milk. Induce vomiting by sticking finger down throat or by giving syrup of Ipecac.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Autoignition Temperature: N/A

Flammability Classification: 0

Extinguishing Media: Use water fog, alcohol foam or dry chemical extinguishing media.

Unusual Fire or Explosion Hazards: None Known.

Fire-Fighting Instructions: If water is evaporated, dry polymer could burn. Water spray, ABC dry chemical and protein type air foams are effective. Carbon dioxide may be ineffective on larger fires due to a lack of cooling capacity which may result in reignition.

Fire Fighting Equipment: Wear positive pressure self-contained breathing apparatus (SCBA). Personnel not having suitable respiratory protection must leave the area to prevent significant exposure to toxic combustion gases from any source. In enclosed or poorly ventilated areas, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Spills should be contained. Recover as much as possible for reuse. Absorb remainder with an inert material. Place into closed container and store in a safe location to await disposal. Wash the spill area with soap and water. Do not flush liquid latex into public sewer or water system.

Waste Disposal Method: Dispose of waste in accordance with federal, state and local regulations. For waste disposal purposes, a liquid with a pH between 2.0 -12.5 is not defined or designated as hazardous by current provisions of the federal resource Conservation and Recovery act (RCRA, 40CFR261). Products with a pH above or below the range listed above must be managed as a hazardous waste. Liquid latex or Dry material may be disposed of by incineration. Most states prohibit disposal of liquids in landfills.

Section 7 - Handling and Storage

Handling Precautions: Wear appropriate protective equipment when handling material. Avoid skin and eye contact.

Storage Requirements: Store at temperatures between 50-100F ideally 70F

Regulatory Requirements: Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Effective exhaust ventilation should always be provided to draw mists, fumes and vapors away from workers to prevent routine inhalation. Ventilation should be adequate to maintain the ambient workplace atmosphere.

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: White to cream colored liquid.
Slight acrylate odor.

Boiling Point: 212 F (100C)

Freezing: 32F (0 C)

% Volatile: N/A

Odor Threshold:

Vapor Pressure: (Air=1) 0.62 (Water)

Specific Gravity (H2O=1) 0.99-1.07

pH:5.0-9.0

Section 10 - Stability and Reactivity

Stability: product is stable.

Chemical Incompatibilities: (Materials to avoid)

Reacts with strong oxidizing agents such as hydrogen peroxide, permanganate and perchlorates. Depending on the amount and specific materials involved, contact can result in intense heat, boiling, flame development, explosion or toxic gas generation.

Conditions to Avoid: Freezing temperatures.

Section 11- Toxicological Information

Eye Effects: N/A

Skin Effects: N/A

Toxicity Data:*

Acute Inhalation Effects:

N/A

Acute Oral Effects:

N/A

Chronic Effects: There are no known chronic effects associated with this material.

Section 12 - Ecological Information

Ecotoxicity: N/A

Environmental Fate N/A
Environmental Transport: N/A
Environmental Degradation: N/A
Soil Absorption/Mobility: N/A

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Disposal Regulatory Requirements: Incinerate or bury in a licensed facility. Do not discharge into waterways or sewer systems without proper authority.

Container Cleaning and Disposal: **Dispose of in a licensed facility. Recommended crushing or other means to prevent unauthorized use.**

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name:N/A
Shipping Symbols:N/A

Hazard Class: N/A

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA N/A

CERCLA Hazardous Substance (40 CFR 302.4) unlisted

CERCLA Reportable Quantity N/A

OSHA Regulations:

Air Contaminant : Not listed

OSHA Specifically Regulated Substance N/A

T.R.I. Reportable (No)

Section 16 - Other Information

Prepared By: Pete Ryan

Revision Notes:

Additional Hazard Rating Systems:

	Health:	Fire:	Reactivity:	Special:
HMIS	0	0	0	NA
HMIS	0	0	0	NA

Disclaimer: The information accumulated herein is based on data which Beacon Chemical Co., Inc. considers to be accurate; provided however, that the company makes no warranty as to the accuracy of the data. Anyone intending to use the information contained herein shall assume sole and complete responsibility for the results of said use including loss or damage resulting from the handling of the material.