

81903-1207

SAFETY DATA SHEET**Section 1 - Product and Company Identification**

Product Name: 5366 JOLIE PAINT ANTIQUE WHITE Product Code: 5366

Trade Name: 5366 JOLIE PAINT ANTIQUE WHITE

Company Identification:**Davis Paint Company**1311 Iron Street
P.O. Box 7589
N. Kansas City, MO 64116**Contact Information :**Emergency Phone : (816)-471-4447
Information Phone : (816)-471-4447
Name of Preparer : Env., Health, & Safety Dept.For emergencies involving a spill, leak, fire, exposure,
or accident - Contact INFOTRAC phone: (800)-535-5053

Product Use: PAINT - General Purpose Use.

Not recommended for: No data available.

Section 2 - Hazards Identification**GHS Ratings:**

Carcinogen 1A Known Human Carcinogen Based on human evidence

GHS Hazards

H350 May cause cancer

GHS PrecautionsP201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P281 Use personal protective equipment as required
P308+P313 IF exposed or concerned: Get medical advice/attention
P405 Store locked up
P501 Dispose of contents/container that comply with local, State, Federal, or International regulations as applicable.Signal Word: **Danger****Section 3 - Composition / Information on Ingredients**

Chemical Name	CAS number	Weight Concentration %
Limestone	1317-65-3	20.00% - 30.00%
Talc	14807-96-6	10.00% - 20.00%
Titanium dioxide	13463-67-7	13.00%
Quartz	14808-60-7	0.30%

Section 4 - First Aid Measures**Inhalation:**

Remove to fresh air. Vapor or mist can cause headache, nausea, and irritation of the nose, throat and lungs, in a poorly ventilated area. If symptoms persist, seek medical attention.

Eye contact:

Direct contact may cause irritation. Remove contact lenses if necessary, and flush with plenty of clean water while holding eyelids open. Do not rub eyes. Get medical attention if irritation or symptoms persist.

Skin contact:

Irritating to the skin on repeated or prolonged contact. Wash with plenty of soap and water. If irritation persists or a rash develops, seek medical attention.

Ingestion:

Can cause gastrointestinal irritation. If swallowed, wash mouth out with water. Do not induce vomiting unless directed by medical personnel. If large amounts are swallowed, give one or two glasses of water and seek medical attention.

Notes to Physician:

Treat symptomatically. Contact Poison Control Center if large quantities have been inhaled or ingested.

Section - 5 Fire Fighting Measures

Flash Point: 100 C (212 F)

LEL:

UEL:

Extinguishing media:

Foam, CO2, Dry Chemical.

Unusual Fire and Explosion Hazards:

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product generally will not burn but may spatter if temperature exceeds the boiling point of product.

Hazardous Combustion Products:

Carbon monoxide, carbon dioxide, aldehydes, hydrocarbons, and other products of incomplete combustion.

Firefighting Procedure:

Firefighters should wear self contained breathing apparatus if material is involved in a general fire.

Section 6 - Accidental Release Measures**Spill Leak / Procedures:**

Dike spill area. Ensure adequate ventilation. Wear appropriate personal protective equipment.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See section #12 for further Ecological information.

Methods and Materials for Containment and Cleaning Up:

Contain spillage. Then collect with inert absorbent materials. Dispose of in accordance with applicable regulations.

Section 7 - Handling and Storage**Handling Precautions:**

Do not use until all safety precautions have been read and understood. Use personal protection found in section 8.

Smoking, eating, or drinking should be prohibited in the application area.

Storage Requirements:

Keep containers closed and upright when not in use. Store in cool well ventilated areas away from heat and direct sunlight. Previously opened containers, carefully reseal. KEEP FROM FREEZING! Wash thoroughly after handling.

Section 8 - Exposure Control and Personal Protection

Engineering Controls:

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits.

Provide readily accessible eye wash station.

Use of protective creams, head caps etc, is recommended.

Personal Protective Equipment

Respiratory Protection:

Do not breathe vapors or mist. Wear an appropriate, properly fitted respirator (NIOSH approved) during the use of this product until vapor and mists are exhausted, unless air monitoring demonstrates vapor and mist levels are below applicable exposure limits.

Skin and Body Protection:

Use polyethylene gloves to avoid contact with product. Gloves must be impervious to soap and water. Wear suitable protective clothing.

Eye Protection:

Use safety eyewear with splash guards or side shields, or goggles.

Section 9 - Physical and Chemical Properties

<p>Explosive Limits: N/A</p> <p>Autoignition temperature: N/A</p> <p>Physical State Liquid</p> <p>COATING VOC #/G 0.000</p> <p>Vapor Pressure: 13.3 mmHg</p> <p>Vapor Density Heavier than air.</p> <p>Specific Gravity 1.56</p> <p>Freezing point: No Data Found</p> <p>Boiling range: 100°C</p> <p>Evaporation Rate Slower than ether.</p> <p>Flammability: No Data Found</p>	<p>Partition coefficient (n- No Data Found octanol/water):</p> <p>Decomposition temperature: No Data Found</p> <p>Coating VOC g/L 0.00</p> <p>Odor Mild</p> <p>Odor threshold: No Data Found</p> <p>pH: No Data Found</p> <p>Melting point: No Data Found</p> <p>Solubility: No Data Found</p> <p>Flash point (TCC): 212°F,100°C</p> <p>Appearance White, Colors and Clear.</p> <p>Viscosity No Data Found</p>
--	---

Section 10 - Stability and Reactivity

Conditions to Avoid:

Excessive heat, poor ventilation, excessive aging.

Stability:

STABLE

Materials to Avoid:

None known.

No Data Found

Hazardous Decomposition Products:

Thermal decomposition or combustion can produce fumes of carbon monoxide and carbon dioxide.

No Data Found

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity**Component Toxicity**

Routes of Entry:

No Data Found

Exposure to this material may affect the following organs:

Eyes Skin Cardiovascular System Respiratory System

Effects of Overexposure**Acute and chronic effects from short and long term exposure:**

Inhalation: Vapor or mist can cause nausea, headache, and irritation of the nose, throat, and lungs .

Eye contact: Direct contact can cause irritation.

Skin contact: Irritating to the skin on repeated or prolonged contact.

Ingestion: If swallowed, can cause irritation, nausea or vomiting.

Section 12 - Ecological Information
--

Ecological information: No data found.

Component Ecotoxicity

Talc

96 Hr LC50 Brachydanio rerio: >100 g/L [semi-static]

Section 13 - Disposal Considerations

Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state, and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Obey relevant laws.

Section 14 - Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Not regulated, Non Hazardous			
IATA	Not regulated, Non Hazardous			
IMDG	Not regulated, Non Hazardous			

Section 15 - Regulatory Information
--

This SDS has been compiled in accordance with Appendix D of OSHA Hazcom 2012.

United States TSCA Inventory: All components of this product are listed and/or are exempt.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

14808-60-7 Quartz Carcinogen

13463-67-7 Titanium dioxide Carcinogen

Canada DSL -- Components are listed or exempt:

